Subject: Re: [PATCH 2/3] memcgroup: fix typo in VM_BUG_ON() Posted by Balbir Singh on Mon, 18 Feb 2008 07:01:27 GMT

View Forum Message <> Reply to Message

```
Li Zefan wrote:
> Balbir Singh wrote:
>> YAMAMOTO Takashi wrote:
>>>> Li Zefan wrote:
>>>> No need for VM BUG ON(pc), since 'pc' is the list entry. This should
>>>> be VM BUG ON(page).
>>>>
>>>> Signed-off-by: Li Zefan < lizf@cn.fujitsu.com>
>>>> Acked-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>
>>> pc is of type page_cgroup and we use list_for_each_entry_safe_reverse. Not sure
>>>> why we can't bug on pc.
>>> pc is dereferenced before this VM_BUG_ON.
>>> YAMAMOTO Takashi
>>>
>> OK, so the VM_BUG_ON needs to move to an earlier location. Agreed.
>>
>
> No, 'pc' has been dereferenced in list_for_each_entry_safe_reverse().
>
> #define list_for_each_entry_safe_reverse(pos, n, head, member) \
> for (pos = list_entry((head)->prev, typeof(*pos), member), \
  n = list_entry(pos->member.prev, typeof(*pos), member); \
                    ^^^^^
>
     &pos->member != (head);
>
          ^^^^
>
     pos = n, n = list_entry(n->member.prev, typeof(*n), member))
>
>
Hmm.. We used to have a for loop with !list_empty() as a termination condition
and VM BUG ON(!pc) is a spill over. With the new loop, VM BUG ON(!pc) does not
make sense.
Warm Regards,
Balbir Singh
Linux Technology Center
IBM, ISTL
Containers mailing list
Containers@lists.linux-foundation.org
```

https://lists.linux-foundation.org/mailman/listinfo/containers

Subject: Re: [PATCH 2/3] memcgroup: fix typo in VM_BUG_ON() Posted by Li Zefan on Mon, 18 Feb 2008 07:14:25 GMT

View Forum Message <> Reply to Message

```
Balbir Singh wrote:
> Li Zefan wrote:
>> Balbir Singh wrote:
>>> YAMAMOTO Takashi wrote:
>>>> Li Zefan wrote:
>>>>> No need for VM_BUG_ON(pc), since 'pc' is the list entry. This should
>>>> be VM_BUG_ON(page).
>>>>>
>>>> Signed-off-by: Li Zefan < lizf@cn.fujitsu.com>
>>>>> Acked-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>
>>>> pc is of type page_cgroup and we use list_for_each_entry_safe_reverse. Not sure
>>>> why we can't bug on pc.
>>> pc is dereferenced before this VM_BUG_ON.
>>>>
>>>> YAMAMOTO Takashi
>>>>
>>> OK, so the VM BUG ON needs to move to an earlier location. Agreed.
>>>
>> No, 'pc' has been dereferenced in list_for_each_entry_safe_reverse().
>>
>>
>> #define list for each entry safe reverse(pos, n, head, member) \
>> for (pos = list_entry((head)->prev, typeof(*pos), member), \
    n = list_entry(pos->member.prev, typeof(*pos), member); \
                     ^^^^^
>>
      &pos->member != (head);
>>
           ^^^^
      pos = n, n = list_entry(n->member.prev, typeof(*n), member))
>>
>>
> Hmm.. We used to have a for loop with !list_empty() as a termination condition
> and VM BUG ON(!pc) is a spill over. With the new loop, VM BUG ON(!pc) does not
> make sense.
>
>
I see, and I'll post a new patch to just remove it.
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers
```

Subject: [PATCH] memcgroup: remove a useless VM_BUG_ON()

View Forum Message <> Reply to Message

Remove this VM_BUG_ON(), as Balbir stated:

We used to have a for loop with !list_empty() as a termination condition and VM_BUG_ON(!pc) is a spill over. With the new loop, VM_BUG_ON(!pc) does not make sense.

```
Signed-off-by: Li Zefan < lizf@cn.fujitsu.com>
mm/memcontrol.c |
1 files changed, 0 insertions(+), 1 deletions(-)
diff --git a/mm/memcontrol.c b/mm/memcontrol.c
index 718acf8..631002d 100644
--- a/mm/memcontrol.c
+++ b/mm/memcontrol.c
@@ -534,7 +534,6 @@ unsigned long mem_cgroup_isolate_pages(unsigned long nr_to_scan,
 if (scan >= nr_to_scan)
  break:
 page = pc->page;
VM_BUG_ON(!pc);
 if (unlikely(!PageLRU(page)))
  continue:
1.5.4.rc3
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers
```