
Subject: [PATCH 1/3] res_counter: introduce res_counter_write_u64()

Posted by Li Zefan on Tue, 11 Mar 2008 10:08:39 GMT

[View Forum Message](#) <> [Reply to Message](#)

This function can be used to assign the value of a resource counter member.

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

```
include/linux/res_counter.h |  9 ++++++---  
kernel/res_counter.c      |  9 ++++++++  
2 files changed, 15 insertions(+), 3 deletions(-)
```

```
diff --git a/include/linux/res_counter.h b/include/linux/res_counter.h
```

```
index 8cb1ecd..8c23f7f 100644
```

```
--- a/include/linux/res_counter.h
```

```
+++ b/include/linux/res_counter.h
```

```
@@ -41,9 +41,10 @@ struct res_counter {
```

```
/**
```

```
 * Helpers to interact with userspace
```

```
- * res_counter_read_u64() - returns the value of the specified member.
```

```
- * res_counter_read/_write - put/get the specified fields from the
```

```
- * res_counter struct to/from the user
```

```
+ * res_counter_read_64/_write_u64 - returns/assigns the value of the
```

```
+ * specified member
```

```
+ * res_counter_read/_write - puts/gets the specified fields from the
```

```
+ * res_counter struct to/from the user
```

```
*
```

```
 * @counter: the counter in question
```

```
 * @member: the field to work with (see RES_xxx below)
```

```
@@ -53,6 +54,8 @@ struct res_counter {
```

```
*/
```

```
u64 res_counter_read_u64(struct res_counter *counter, int member);
```

```
+void res_counter_write_u64(struct res_counter *counter, int member,
```

```
+    unsigned long long val);
```

```
ssize_t res_counter_read(struct res_counter *counter, int member,
```

```
    const char __user *buf, size_t nbytes, loff_t *pos,
```

```
diff --git a/kernel/res_counter.c b/kernel/res_counter.c
```

```
index 791ff2b..a16b727 100644
```

```
--- a/kernel/res_counter.c
```

```
+++ b/kernel/res_counter.c
```

```
@@ -97,6 +97,15 @@ u64 res_counter_read_u64(struct res_counter *counter, int member)
```

```
    return *res_counter_member(counter, member);
```

```
}
```

```
+void res_counter_write_u64(struct res_counter *counter, int member,
```

```
+     unsigned long long val)
+{
+ unsigned long long *tmp;
+
+ tmp = res_counter_member(counter, member);
+ *tmp = val;
+}
+
ssize_t res_counter_write(struct res_counter *counter, int member,
 const char __user *userbuf, size_t nbytes, loff_t *pos,
 int (*write_strategy)(char *st_buf, unsigned long long *val))
--
```

1.5.4.rc3

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH 1/3] res_counter: introduce res_counter_write_u64()
Posted by [KAMEZAWA Hiroyuki](#) on Tue, 11 Mar 2008 10:21:17 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Tue, 11 Mar 2008 19:08:39 +0900
Li Zefan <lizf@cn.fujitsu.com> wrote:

> This function can be used to assign the value of a resource counter member.

>

Why don't you make this function to do the same work as res_counter_write() ?

Thanks,
-Kame

> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>
> ---
> include/linux/res_counter.h | 9 +++++++--
> kernel/res_counter.c | 9 ++++++++-
> 2 files changed, 15 insertions(+), 3 deletions(-)
>
> diff --git a/include/linux/res_counter.h b/include/linux/res_counter.h
> index 8cb1ecd..8c23f7f 100644
> --- a/include/linux/res_counter.h
> +++ b/include/linux/res_counter.h
> @@ -41,9 +41,10 @@ struct res_counter {
>
> /**

> * Helpers to interact with userspace
> - * res_counter_read_u64() - returns the value of the specified member.
> - * res_counter_read/_write - put/get the specified fields from the
> - * res_counter struct to/from the user
> + * res_counter_read_64/_write_u64 - returns/assigns the value of the
> + * specified member
> + * res_counter_read/_write - puts/gets the specified fields from the
> + * res_counter struct to/from the user
> *
> * @counter: the counter in question
> * @member: the field to work with (see RES_xxx below)
> @@ -53,6 +54,8 @@ struct res_counter {
> */
>
> u64 res_counter_read_u64(struct res_counter *counter, int member);
> +void res_counter_write_u64(struct res_counter *counter, int member,
> + unsigned long long val);
>
> ssize_t res_counter_read(struct res_counter *counter, int member,
> const char __user *buf, size_t nbytes, loff_t *pos,
> diff --git a/kernel/res_counter.c b/kernel/res_counter.c
> index 791ff2b..a16b727 100644
> --- a/kernel/res_counter.c
> +++ b/kernel/res_counter.c
> @@ -97,6 +97,15 @@ u64 res_counter_read_u64(struct res_counter *counter, int member)
> return *res_counter_member(counter, member);
> }
>
> +void res_counter_write_u64(struct res_counter *counter, int member,
> + unsigned long long val)
> +{
> + unsigned long long *tmp;
> +
> + tmp = res_counter_member(counter, member);
> + *tmp = val;
> +}
> +
> ssize_t res_counter_write(struct res_counter *counter, int member,
> const char __user *userbuf, size_t nbytes, loff_t *pos,
> int (*write_strategy)(char *st_buf, unsigned long long *val))
> --
> 1.5.4.rc3
>
> --
> To unsubscribe, send a message with 'unsubscribe linux-mm' in
> the body to majordomo@kvack.org. For more info on Linux MM,
> see: http://www.linux-mm.org/ .
> Don't email: email@kvack.org

>

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH 1/3] res_counter: introduce res_counter_write_u64()
Posted by [Li Zefan](#) on Thu, 13 Mar 2008 23:34:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

KAMEZAWA Hiroyuki wrote:

> On Tue, 11 Mar 2008 19:08:39 +0900

> Li Zefan <lizf@cn.fujitsu.com> wrote:

>

>> This function can be used to assign the value of a resource counter member.

>>

> Why don't you make this function to do the same work as res_counter_write() ?

>

You mean to deal with write strategy? We don't need that complexity. If it does the same work as res_counter_write(), it's just a redundant function. ;)

But I forgot to take res_counter->lock ...

> Thanks,

> -Kame

>

>

>> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

>> ---

>> include/linux/res_counter.h | 9 ++++++---

>> kernel/res_counter.c | 9 ++++++++

>> 2 files changed, 15 insertions(+), 3 deletions(-)

>>

>> diff --git a/include/linux/res_counter.h b/include/linux/res_counter.h

>> index 8cb1ecd..8c23f7f 100644

>> --- a/include/linux/res_counter.h

>> +++ b/include/linux/res_counter.h

>> @@ -41,9 +41,10 @@ struct res_counter {

>>

>> /**

>> * Helpers to interact with userspace

>> - * res_counter_read_u64() - returns the value of the specified member.

>> - * res_counter_read/_write - put/get the specified fields from the

>> - * res_counter struct to/from the user

>> + * res_counter_read_64/_write_u64 - returns/assigns the value of the

```

>> + * specified member
>> + * res_counter_read/_write - puts/gets the specified fields from the
>> + * res_counter struct to/from the user
>> *
>> * @counter: the counter in question
>> * @member: the field to work with (see RES_xxx below)
>> @@ -53,6 +54,8 @@ struct res_counter {
>> */
>>
>> u64 res_counter_read_u64(struct res_counter *counter, int member);
>> +void res_counter_write_u64(struct res_counter *counter, int member,
>> +    unsigned long long val);
>>
>> ssize_t res_counter_read(struct res_counter *counter, int member,
>>   const char __user *buf, size_t nbytes, loff_t *pos,
>> diff --git a/kernel/res_counter.c b/kernel/res_counter.c
>> index 791ff2b..a16b727 100644
>> --- a/kernel/res_counter.c
>> +++ b/kernel/res_counter.c
>> @@ -97,6 +97,15 @@ u64 res_counter_read_u64(struct res_counter *counter, int member)
>>   return *res_counter_member(counter, member);
>> }
>>
>> +void res_counter_write_u64(struct res_counter *counter, int member,
>> +    unsigned long long val)
>> +{
>> +    unsigned long long *tmp;
>> +
>> +    tmp = res_counter_member(counter, member);
>> +    *tmp = val;
>> +}
>> +
>> sszie_t res_counter_write(struct res_counter *counter, int member,
>>   const char __user *userbuf, size_t nbytes, loff_t *pos,
>>   int (*write_strategy)(char *st_buf, unsigned long long *val))
>> --
>> 1.5.4.rc3
>>
>> --
>> To unsubscribe, send a message with 'unsubscribe linux-mm' in
>> the body to majordomo@kvack.org. For more info on Linux MM,
>> see: http://www.linux-mm.org/ .
>> Don't email: <a href="mailto:dont@kvack.org"> email@kvack.org </a>
>>
>
>
>

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
