
Subject: [PATCH net-2.6.26 2/4][NETNS][ICMP]: Move ICMP sysctls on struct net.

Posted by [Pavel Emelianov](#) on Wed, 26 Mar 2008 08:53:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

Initialization is moved to icmp_sk_init, all the places, that refer to them use init_net for now.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
include/net/icmp.h      |  7 -----
include/net/netns/ipv4.h |  7 ++++++
net/ipv4/icmp.c        | 60 ++++++-----+
net/ipv4/sysctl_net_ipv4.c | 12 +++++-
4 files changed, 44 insertions(+), 42 deletions(-)
```

```
diff --git a/include/net/icmp.h b/include/net/icmp.h
index faba64d..dddb839 100644
--- a/include/net/icmp.h
+++ b/include/net/icmp.h
@@ -65,11 +65,4 @@ static inline struct raw_sock *raw_sk(const struct sock *sk)
    return (struct raw_sock *)sk;
}
```

```
-extern int sysctl_icmp_echo_ignore_all;
-extern int sysctl_icmp_echo_ignore_broadcasts;
-extern int sysctl_icmp_ignore_bogus_error_responses;
-extern int sysctl_icmp_errors_use_inbound_ifaddr;
-extern int sysctl_icmp_ratelimit;
-extern int sysctl_icmp_ratemask;
```

-

```
#endif /* _ICMP_H */
diff --git a/include/net/netns/ipv4.h b/include/net/netns/ipv4.h
index 504fde1..e3de0ff 100644
```

```
--- a/include/net/netns/ipv4.h
+++ b/include/net/netns/ipv4.h
```

```
@@ -35,5 +35,12 @@ struct netns_ipv4 {
```

```
    struct xt_table *iptable_raw;
    struct xt_table *arptable_filter;
#endif
+
+ int sysctl_icmp_echo_ignore_all;
+ int sysctl_icmp_echo_ignore_broadcasts;
+ int sysctl_icmp_ignore_bogus_error_responses;
+ int sysctl_icmp_ratelimit;
+ int sysctl_icmp_ratemask;
+ int sysctl_icmp_errors_use_inbound_ifaddr;
};
```

```

#endif
diff --git a/net/ipv4/icmp.c b/net/ipv4/icmp.c
index f38f093..958a384 100644
--- a/net/ipv4/icmp.c
+++ b/net/ipv4/icmp.c
@@@ -188,29 +188,6 @@ struct icmp_err icmp_err_convert[] = {
 },
};

/* Control parameters for ECHO replies. */
-int sysctl_icmp_echo_ignore_all __read_mostly;
-int sysctl_icmp_echo_ignore_broadcasts __read_mostly = 1;
-
-/* Control parameter - ignore bogus broadcast responses? */
-int sysctl_icmp_ignore_bogus_error_responses __read_mostly = 1;
-
-/*
- * Configurable global rate limit.
- *
- * ratelimit defines tokens/packet consumed for dst->rate_token bucket
- * ratemask defines which icmp types are ratelimited by setting
- * its bit position.
- *
- * default:
- * dest unreachable (3), source quench (4),
- * time exceeded (11), parameter problem (12)
- */
-
-int sysctl_icmp_ratelimit __read_mostly = 1 * HZ;
-int sysctl_icmp_ratemask __read_mostly = 0x1818;
-int sysctl_icmp_errors_use_inbound_ifaddr __read_mostly;
-
/*
 * ICMP control array. This specifies what to do with each ICMP.
 */
@@@ -310,8 +287,8 @@ static inline int icmpv4_xrlim_allow(struct rtable *rt, int type, int code)
    goto out;

/* Limit if icmp type is enabled in ratemask. */
-if ((1 << type) & sysctl_icmp_ratemask)
-    rc = xrlim_allow(dst, sysctl_icmp_ratelimit);
+ if ((1 << type) & init_net.ipv4.sysctl_icmp_ratemask)
+    rc = xrlim_allow(dst, init_net.ipv4.sysctl_icmp_ratelimit);
out:
    return rc;
}
@@@ -523,7 +500,8 @@ void icmp_send(struct sk_buff *skb_in, int type, int code, __be32 info)
    if (!(rt->rt_flags & RTCF_LOCAL)) {

```

```

struct net_device *dev = NULL;

- if (rt->fl.iif && sysctl_icmp_errors_use_inbound_ifaddr)
+ if (rt->fl.iif &&
+ init_net.ipv4.sysctl_icmp_errors_use_inbound_ifaddr)
    dev = dev_get_by_index(net, rt->fl.iif);

    if (dev) {
@@ -745,7 +723,7 @@ static void icmp_unreach(struct sk_buff *skb)
    * get the other vendor to fix their kit.
    */

- if (!sysctl_icmp_ignore_bogus_error_responses &&
+ if (!init_net.ipv4.sysctl_icmp_ignore_bogus_error_responses &&
    inet_addr_type(net, iph->daddr) == RTN_BROADCAST) {
    if (net_ratelimit())
        printk(KERN_WARNING "%u.%u.%u.%u sent an invalid ICMP "
@@ -840,7 +818,7 @@ out_err:

static void icmp_echo(struct sk_buff *skb)
{
- if (!sysctl_icmp_echo_ignore_all) {
+ if (!init_net.ipv4.sysctl_icmp_echo_ignore_all) {
    struct icmp_bxm icmp_param;

    icmp_param.data.icmph = *icmp_hdr(skb);
@@ -1051,7 +1029,7 @@ int icmp_rcv(struct sk_buff *skb)
    */
    if ((icmph->type == ICMP_ECHO ||
         icmph->type == ICMP_TIMESTAMP) &&
-    sysctl_icmp_echo_ignore_broadcasts) {
+    init_net.ipv4.sysctl_icmp_echo_ignore_broadcasts) {
        goto error;
    }
    if (icmph->type != ICMP_ECHO &&
@@ -1195,6 +1173,30 @@ int __net_init icmp_sk_init(struct net *net)
    */
    sk->sk_prot->unhash(sk);
}
+
+ /* Control parameters for ECHO replies. */
+ net->ipv4.sysctl_icmp_echo_ignore_all = 0;
+ net->ipv4.sysctl_icmp_echo_ignore_broadcasts = 1;
+
+ /* Control parameter - ignore bogus broadcast responses? */
+ net->ipv4.sysctl_icmp_ignore_bogus_error_responses = 1;
+
+ /*

```

```

+ * Configurable global rate limit.
+
+ * ratelimit defines tokens/packet consumed for dst->rate_token
+ * bucket ratemask defines which icmp types are ratelimited by
+ * setting it's bit position.
+
+ *
+ * default:
+ * dest unreachable (3), source quench (4),
+ * time exceeded (11), parameter problem (12)
+ */
+
+ net->ipv4.sysctl_icmp_ratelimit = 1 * HZ;
+ net->ipv4.sysctl_icmp_ratemask = 0x1818;
+ net->ipv4.sysctl_icmp_errors_use_inbound_ifaddr = 0;
+
return 0;

fail:
diff --git a/net/ipv4/sysctl_net_ipv4.c b/net/ipv4/sysctl_net_ipv4.c
index c2fca30..e9585c0 100644
--- a/net/ipv4/sysctl_net_ipv4.c
+++ b/net/ipv4/sysctl_net_ipv4.c
@@ -406,7 +406,7 @@ static struct ctl_table ipv4_table[] = {
{
    .ctl_name = NET_IPV4_ICMP_ECHO_IGNORE_ALL,
    .procname = "icmp_echo_ignore_all",
-   .data = &sysctl_icmp_echo_ignore_all,
+   .data = &init_net.ipv4.sysctl_icmp_echo_ignore_all,
    .maxlen = sizeof(int),
    .mode = 0644,
    .proc_handler = &proc_dointvec
@@ -414,7 +414,7 @@ static struct ctl_table ipv4_table[] = {
{
    .ctl_name = NET_IPV4_ICMP_ECHO_IGNORE_BROADCASTS,
    .procname = "icmp_echo_ignore_broadcasts",
-   .data = &sysctl_icmp_echo_ignore_broadcasts,
+   .data = &init_net.ipv4.sysctl_icmp_echo_ignore_broadcasts,
    .maxlen = sizeof(int),
    .mode = 0644,
    .proc_handler = &proc_dointvec
@@ -422,7 +422,7 @@ static struct ctl_table ipv4_table[] = {
{
    .ctl_name = NET_IPV4_ICMP_IGNORE_BOGUS_ERROR_RESPONSES,
    .procname = "icmp_ignore_bogus_error_responses",
-   .data = &sysctl_icmp_ignore_bogus_error_responses,
+   .data = &init_net.ipv4.sysctl_icmp_ignore_bogus_error_responses,
    .maxlen = sizeof(int),
    .mode = 0644,

```

```

.proc_handler = &proc_dointvec
@@ -430,7 +430,7 @@ static struct ctl_table ipv4_table[] = {
{
    .ctl_name = NET_IPV4_ICMP_ERRORS_USE_INBOUND_IFADDR,
    .procname = "icmp_errors_use_inbound_ifaddr",
-   .data = &sysctl_icmp_errors_use_inbound_ifaddr,
+   .data = &init_net.ipv4.sysctl_icmp_errors_use_inbound_ifaddr,
    . maxlen = sizeof(int),
    .mode = 0644,
    .proc_handler = &proc_dointvec
@@ -588,7 +588,7 @@ static struct ctl_table ipv4_table[] = {
{
    .ctl_name = NET_IPV4_ICMP_RATELIMIT,
    .procname = "icmp_ratelimit",
-   .data = &sysctl_icmp_ratelimit,
+   .data = &init_net.ipv4.sysctl_icmp_ratelimit,
    . maxlen = sizeof(int),
    .mode = 0644,
    .proc_handler = &proc_dointvec
@@ -596,7 +596,7 @@ static struct ctl_table ipv4_table[] = {
{
    .ctl_name = NET_IPV4_ICMP_RATEMASK,
    .procname = "icmp_ratemask",
-   .data = &sysctl_icmp_ratemask,
+   .data = &init_net.ipv4.sysctl_icmp_ratemask,
    . maxlen = sizeof(int),
    .mode = 0644,
    .proc_handler = &proc_dointvec
--
```

1.5.3.4

Subject: Re: [PATCH net-2.6.26 2/4][NETNS][ICMP]: Move ICMP sysctls on struct net.

Posted by [davem](#) on Wed, 26 Mar 2008 08:55:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Pavel Emelyanov <xemul@openvz.org>

Date: Wed, 26 Mar 2008 11:53:03 +0300

> Initialization is moved to icmp_sk_init, all the places, that
 > refer to them use init_net for now.
 >
 > Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

Applied.
