
Subject: Can a VE contain the root filesystem?

Posted by [duyuyang](#) on Wed, 14 May 2008 13:57:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

Can VE use the root filesystem as private filesystem?

Scenario: I first installed Oracle without OpenVz, then I installed OpenVz, but I do not want to install Oracle again in a VE, I wonder if I can let a VE use the original root FS as private FS, then I can use Oracle in VE.

Y. D.

2008-05-14

Subject: Re: Can a VE contain the root filesystem?

Posted by [Vasily Averin](#) on Thu, 15 May 2008 06:47:06 GMT

[View Forum Message](#) <> [Reply to Message](#)

> Can VE use the root filesystem as private filesystem?

>

> Scenario: I first installed Oracle without OpenVz, then I installed OpenVz,
> but I do not want to install Oracle again in a VE, I wonder if I can let a VE
> use the original root FS as private FS, then I can use Oracle in VE.

You can bind-mount any parts of host filesystem into VE.

For example you can use per-ve mount script to bind-mount /opt directory to the /vz/root/<VEID>/opt.

Moreover I think you can try to bind-mount / to some directory inside VE (for example to /vz/root/<VEID>/hostroot/), then call chroot inside VE.

thank you,
Vasily Averin
