
Subject: resolv.conf wont stay on reboot

Posted by [Light Speed](#) on Wed, 21 May 2008 03:07:41 GMT

[View Forum Message](#) <> [Reply to Message](#)

Running CentOS 5.1 in a VE and when the OS is rebooted the contents of the resolv.conf file are overwritten with what I believe are the DNS server IPs of the HN.

Why is this happening and how can I stop it?

I want to stop having to manually re-add the correct IP entries after every reboot!

I am the end user of the VE and not the HN admin.

Subject: Re: resolv.conf wont stay on reboot

Posted by [maratrus](#) on Wed, 21 May 2008 10:15:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

Hi,

1. You can ask HN admin to set inside your VE the correct nameserver. (via --nameserver option)

2. If it's impossible try to add appropriate commands for example in /etc/rc.local file to change /etc/resolv.conf file.

Subject: Re: resolv.conf wont stay on reboot

Posted by [piavlo](#) on Wed, 21 May 2008 11:02:10 GMT

[View Forum Message](#) <> [Reply to Message](#)

Light Speed wrote on Wed, 21 May 2008 06:07Running CentOS 5.1 in a VE and when the OS is rebooted the contents of the resolv.conf file are overwritten with what I believe are the DNS server IPs of the HN.

Why is this happening and how can I stop it?

I want to stop having to manually re-add the correct IP entries after every reboot!

I am the end user of the VE and not the HN admin.

Are you using dhcp client inside VE?

If using <http://sourceforge.net/projects/dhcpv6/>

or <http://www.isc.org/products/DHCP>

try tweaking

prepend domain-name-servers dnsv2,dnssrv2,...

inside /etc/dhclient-eth?.conf

IF using <http://roy.marples.name/dhcpd>
add nodns option to dhcpd daemon
