
Subject: [PATCH] cgroup: anotate two variables with __read_mostly

Posted by [Li Zefan](#) on Thu, 05 Jun 2008 06:02:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

- need_forkexit_callback will be read only after system boot.
- use_task_css_set_links will be read only after it's set.

And these 2 variables are checked when a new process is forked.

Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

```
---
kernel/cgroup.c | 4 +---
1 files changed, 2 insertions(+), 2 deletions(-)

diff --git a/kernel/cgroup.c b/kernel/cgroup.c
index 15ac0e1..f5a1273 100644
--- a/kernel/cgroup.c
+++ b/kernel/cgroup.c
@@ -118,7 +118,7 @@ static int root_count;
 * extra work in the fork/exit path if none of the subsystems need to
 * be called.
 */
-static int need_forkexit_callback;
+static int need_forkexit_callback __read_mostly;
static int need_mm_owner_callback __read_mostly;

/* convenient tests for these bits */
@@ -220,7 +220,7 @@ static struct hlist_head *css_set_hash(struct cgroup_subsys_state *css[])
 * task until after the first call to cgroup_iter_start(). This
 * reduces the fork()/exit() overhead for people who have cgroups
 * compiled into their kernel but not actually in use */
-static int use_task_css_set_links;
+static int use_task_css_set_links __read_mostly;

/* When we create or destroy a css_set, the operation simply
 * takes/releases a reference count on all the cgroups referenced
--
1.5.4.rc3
```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH] cgroup: anotate two variables with __read_mostly

Posted by [Paul Menage](#) on Thu, 05 Jun 2008 06:35:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Wed, Jun 4, 2008 at 11:02 PM, Li Zefan <lizf@cn.fujitsu.com> wrote:

>
> - need_forkexit_callback will be read only after system boot.
> - use_task_css_set_links will be read only after it's set.
>
> And these 2 variables are checked when a new process is forked.
>
> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

Acked-by: Paul Menage <menage@google.com>

Thanks.

Paul

> ---
> kernel/cgroup.c | 4 ++--
> 1 files changed, 2 insertions(+), 2 deletions(-)
>
> diff --git a/kernel/cgroup.c b/kernel/cgroup.c
> index 15ac0e1..f5a1273 100644
> --- a/kernel/cgroup.c
> +++ b/kernel/cgroup.c
> @@ -118,7 +118,7 @@ static int root_count;
> * extra work in the fork/exit path if none of the subsystems need to
> * be called.
> */
> -static int need_forkexit_callback;
> +static int need_forkexit_callback __read_mostly;
> static int need_mm_owner_callback __read_mostly;
>
> /* convenient tests for these bits */
> @@ -220,7 +220,7 @@ static struct hlist_head *css_set_hash(struct cgroup_subsys_state
> *css[])
> * task until after the first call to cgroup_iter_start(). This
> * reduces the fork()/exit() overhead for people who have cgroups
> * compiled into their kernel but not actually in use */
> -static int use_task_css_set_links;
> +static int use_task_css_set_links __read_mostly;
>
> /* When we create or destroy a css_set, the operation simply
> * takes/releases a reference count on all the cgroups referenced
> --
> 1.5.4.rc3
>

Containers mailing list
Containers@lists.linux-foundation.org

Subject: Re: [PATCH] cgroup: anotate two variables with __read_mostly

Posted by [KOSAKI Motohiro](#) on Sat, 07 Jun 2008 04:16:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

>
> - need_forkexit_callback will be read only after system boot.
> - use_task_css_set_links will be read only after it's set.
>
> And these 2 variables are checked when a new process is forked.
>
> Signed-off-by: Li Zefan <lizf@cn.fujitsu.com>

nice :)

Acked-by: KOSAKI Motohiro <kosaki.motohiro@jp.fujitsu.com>

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
