
Subject: [PATCH] cryo: Improve socket support: add UDP and IPv6 - V2

Posted by [Benjamin Thery](#) on Tue, 17 Jun 2008 11:24:14 GMT

[View Forum Message](#) <> [Reply to Message](#)

I played a bit with inet sockets and cryo. With few modifications I managed to "checkpoint-restart" programs that use UDP sockets to listen and send data.

This patch improves socket checkpointing in cryo:

- * Save/restore socket family: we can checkpoint IPv6 sockets now.
- * Save/restore socket type: we can checkpoint UDP sockets too.

Changelog:

* V2:

- Add helper isockbound() to improve readability of getsockinfo()
- Cleaned up a bunch of unneeded casts in getsockinfo()
- Move socket binding code from restore_sock() to bind_sock()

* V1:

- Initial version

Simple test programs for UDP sockets available upon request :)

Regards,
Benjamin

Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

cr.c | 93 ++++++-----
1 file changed, 73 insertions(+), 20 deletions(-)

Index: cryodev/cr.c

--- cryodev.orig/cr.c
+++ cryodev/cr.c
@@ -67,11 +67,15 @@ int pagesize = 0;

```
typedef struct isockinfo_t {
    int fdnum;
- int type; /* socket type: UDP, TCP */
+ int type; /* socket type: SOCK_STREAM, SOCK_DGRAM */
+ int family; /* socket family: AF_INET, AF_INET6 */
    int mode; /* bind, listen, connect */
    int opt; /* various sockopt */
    int backlog; /* for listen(2) */
- struct sockaddr_in locaddr; /* for bind(2) */
+ union {
+     struct sockaddr_in saddr4;
```

```

+ struct sockaddr_in6 saddr6;
+ } locaddr; /* for bind(2) */
char tcpstate[TPI_LEN];
} isockinfo_t;

@@ -177,9 +181,25 @@ int getmaps(pid_t pid, memseg_t **p)
return nseg;
}

+static int issockbound(struct sockaddr *sa)
+{
+ if (sa->sa_family == AF_INET) {
+ struct sockaddr_in *sin = (struct sockaddr_in *) sa;
+ if (sin->sin_addr.s_addr != INADDR_ANY ||
+ sin->sin_port != 0)
+ return 1;
+ } else if (sa->sa_family == AF_INET6) {
+ struct sockaddr_in6 *sin6 = (struct sockaddr_in6 *) sa;
+ if (memcmp(&sin6->sin6_addr, &in6addr_any, 16) != 0 ||
+ sin6->sin6_port != 0)
+ return 1;
+ }
+ return 0;
+}
+
int getsockinfo(pid_t pid, pinfo_t *pi, int num)
{
- struct sockaddr name;
+ struct sockaddr_storage name;
int namelen = (int)sizeof(name), ret = 0;
int tpi_len = TPI_LEN;
int flag, flaglen;
@@ -188,35 +208,46 @@ int getsockinfo(pid_t pid, pinfo_t *pi,
/* get socketname and see if it is an unix or an inet socket */
memset(&name, 0, sizeof(name));
PT_GETSOCKNAME(pid, num, &name, &namelen);
- t_d(name.sa_family);
+ t_d(name.ss_family);

- if (name.sa_family != (sa_family_t)AF_INET) return ret;
+ if (name.ss_family != (sa_family_t)AF_INET &&
+ name.ss_family != (sa_family_t)AF_INET6)
+ return ret;

if (! (pi->si = (isockinfo_t *)realloc(pi->si, sizeof(isockinfo_t) * (pi->ns+1)))) return -1;
psi = &pi->si[pi->ns];
- memset((void *)psi, 0, sizeof(*psi));
+ memset(psi, 0, sizeof(*psi));

```

```

//pi->si[pi->ns].fdnum = num;
psi->fdnum = num;
+ psi->family = name.ss_family;

psi->mode = ISOCK_UNKNOWN;
- memcpy((void *)&psi->locaddr, (void *)&name, sizeof(name));
- if (psi->locaddr.sin_addr.s_addr != 0 || psi->locaddr.sin_port != 0) psi->mode |= ISOCK_BIND;
-
+ memcpy(&psi->locaddr, &name, namelen);
+
+ if (issockbound((struct sockaddr *)&psi->locaddr))
+ psi->mode |= ISOCK_BIND;
+
+ flag = 0;
+ flaglen = sizeof(flag);
+ PT_GETSOCKOPT(pid, num, SOL_SOCKET, SO_TYPE, &flag, &flaglen);
+ if (flag)
+ psi->type = flag;
+
flag = 0;
- flaglen = (int)sizeof(flag);
+ flaglen = sizeof(flag);
PT_GETSOCKOPT(pid, num, SOL_SOCKET, SO_REUSEADDR, &flag, &flaglen);
if (flag) psi->opt |= ISOCK_REUSEADDR;

flag = 0;
- flaglen = (int)sizeof(flag);
+ flaglen = sizeof(flag);
PT_GETSOCKOPT(pid, num, SOL_SOCKET, SO_ACCEPTCONN, &flag, &flaglen);
if (flag) {
    psi->mode |= ISOCK_LISTEN;
    //t_d(PT_GETSOCKOPT(pid, num, SOL_TCP, TPI_INFO, &tpi_info, &tpi_info_len));
}

- namelen = (int)sizeof(name);
+ namelen = sizeof(name);
if (PT_GETPEERNAME(pid, num, &name, &namelen) == 0) {
    t_d(psi->mode |= ISOCK_CONNECT);
    t_d(PT_GETSOCKOPT(pid, num, SOL_TCP, TPI_TCP_STATE, pi->si[pi->ns].tcpstate,
&tpi_len));
    @@ -859,6 +890,31 @@ error:
        return -1;
}

+static void bind_sock(pid_t pid, isockinfo_t *isockinfo)
+{
+ int len;

```

```

+ struct sockaddr *sa;
+ struct sockaddr_in sin;
+ struct sockaddr_in6 sin6;
+
+ if (isockinfo->family == AF_INET) {
+   len = sizeof(sin);
+   memcpy(&sin, &isockinfo->locaddr.saddr4, len);
+   if (isockinfo->mode & ISOCK_CONNECT)
+     sin.sin_port = htons(0);
+   sa = (struct sockaddr *) &sin;
+ } else if (isockinfo->family == AF_INET6) {
+   len = sizeof(sin6);
+   memcpy(&sin6, &isockinfo->locaddr.saddr6, len);
+   if (isockinfo->mode & ISOCK_CONNECT)
+     sin.sin_port = htons(0);
+   sa = (struct sockaddr *) &sin6;
+ } else
+   ERROR("Unsupported socket family: %d\n",
+         isockinfo->family);
+ t_d(PT_BIND(pid, isockinfo->fdnum, sa, len));
+
int restore_sock(int fd, pid_t pid)
{
  char item[64];
@@ -873,21 +929,18 @@ int restore_sock(int fd, pid_t pid)
  else ITEM_SET(isockinfo, isockinfo_t);
  else break; // unknown item

- t_d(sock = PT_SOCKET(pid, AF_INET, SOCK_STREAM, 0));
+ t_d(sock = PT_SOCKET(pid, isockinfo->family, isockinfo->type, 0));
  if (sock < 0) {
    ERROR("PT_SOCKET(%d, %d, %d, %d) errno=%d: %s",
-     pid, AF_INET, SOCK_STREAM, 0, sock, strerror(-sock));
+     pid, isockinfo->family, isockinfo->type, 0,
+     sock, strerror(-sock));
  }
  t_d(PT_DUP2(pid, sock, isockinfo->fdnum));
  if (sock != isockinfo->fdnum) t_d(PT_CLOSE(pid, sock));

- if (isockinfo->mode & ISOCK_BIND) {
-   struct sockaddr_in sin;
+ if (isockinfo->mode & ISOCK_BIND)
+   bind_sock(pid, isockinfo);

-   memcpy((void *)&sin, (void *)&isockinfo->locaddr, sizeof(sin));
-   if (isockinfo->mode & ISOCK_CONNECT) sin.sin_port = htons(0);
-   t_d(PT_BIND(pid, isockinfo->fdnum, &sin, sizeof(sin)));

```

```
- }
if (isockinfo->mode & ISOCK_LISTEN) {
    t_d(PT_LISTEN(pid, isockinfo->fdnum, 64)); //FIXME: get backlog from TPI_INFO
}
```

--

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH] cryo: Improve socket support: add UDP and IPv6 - V2

Posted by [serue](#) on Tue, 17 Jun 2008 14:00:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quoting Benjamin Thery (benjamin.thery@bull.net):

> I played a bit with inet sockets and cryo. With few modifications I
> managed to "checkpoint-restart" programs that use UDP sockets to listen
> and send data.
>
> This patch improves socket checkpointing in cryo:
> * Save/restore socket family: we can checkpoint IPv6 sockets now.
> * Save/restore socket type: we can checkpoint UDP sockets too.
>
> Changelog:
> -----
> * V2:
> - Add helper issockbound() to improve readability of getsockinfo()
> - Cleaned up a bunch of unneeded casts in getsockinfo()
> - Move socket binding code from restore_sock() to bind_sock()
> * V1:
> - Initial version
>
> Simple test programs for UDP sockets available upon request :)
>
> Regards,
> Benjamin
>
> Signed-off-by: Benjamin Thery <benjamin.thery@bull.net>

Applied, thanks.

Please do send the test programs, and I'll add them under cryo/tests.

-serge

> ---

```

> cr.c | 93 ++++++-----+
> 1 file changed, 73 insertions(+), 20 deletions(-)
>
> Index: cryodev/cr.c
> =====
> --- cryodev.orig/cr.c
> +++ cryodev/cr.c
> @@ -67,11 +67,15 @@ int pagesize = 0;
>
> typedef struct isockinfo_t {
>     int fdnum;
> -    int type; /* socket type: UDP, TCP */
> +    int type; /* socket type: SOCK_STREAM, SOCK_DGRAM */
> +    int family; /* socket family: AF_INET, AF_INET6 */
>     int mode; /* bind, listen, connect */
>     int opt; /* various sockopt */
>     int backlog; /* for listen(2) */
> -    struct sockaddr_in locaddr; /* for bind(2) */
> +    union {
> +        struct sockaddr_in saddr4;
> +        struct sockaddr_in6 saddr6;
> +    } locaddr; /* for bind(2) */
>     char tcpstate[TPI_LEN];
> } isockinfo_t;
>
> @@ -177,9 +181,25 @@ int getmaps(pid_t pid, memseg_t **p)
>     return nseg;
> }
>
> +static int issockbound(struct sockaddr *sa)
> +{
> +    if (sa->sa_family == AF_INET) {
> +        struct sockaddr_in *sin = (struct sockaddr_in *) sa;
> +        if (sin->sin_addr.s_addr != INADDR_ANY ||
> +            sin->sin_port != 0)
> +            return 1;
> +    } else if (sa->sa_family == AF_INET6) {
> +        struct sockaddr_in6 *sin6 = (struct sockaddr_in6 *) sa;
> +        if (memcmp(&sin6->sin6_addr, &in6addr_any, 16) != 0 ||
> +            sin6->sin6_port != 0)
> +            return 1;
> +    }
> +    return 0;
> +}
> +
> int getsockinfo(pid_t pid, pinfo_t *pi, int num)
> {
> -    struct sockaddr name;

```

```

> + struct sockaddr_storage name;
> int namelen = (int)sizeof(name), ret = 0;
> int tpi_len = TPI_LEN;
> int flag, flaglen;
> @@ -188,35 +208,46 @@ int getsockinfo(pid_t pid, pinfo_t *pi,
> /* get socketname and see if it is an unix or an inet socket */
> memset(&name, 0, sizeof(name));
> PT_GETSOCKNAME(pid, num, &name, &namelen);
> - t_d(name.sa_family);
> + t_d(name.ss_family);
>
> - if (name.sa_family != (sa_family_t)AF_INET) return ret;
> + if (name.ss_family != (sa_family_t)AF_INET &&
> + name.ss_family != (sa_family_t)AF_INET6)
> + return ret;
>
> if (! (pi->si = (isockinfo_t *)realloc(pi->si, sizeof(isockinfo_t) * (pi->ns+1)))) return -1;
> psi = &pi->si[pi->ns];
> - memset((void *)psi, 0, sizeof(*psi));
> + memset(psi, 0, sizeof(*psi));
>
> //pi->si[pi->ns].fdnum = num;
> psi->fdnum = num;
> + psi->family = name.ss_family;
>
> psi->mode = ISOCK_UNKNOWN;
> - memcpy((void *)&psi->locaddr, (void *)&name, sizeof(name));
> - if (psi->locaddr.sin_addr.s_addr != 0 || psi->locaddr.sin_port != 0) psi->mode |= ISOCK_BIND;
> -
> + memcpy(&psi->locaddr, &name, namelen);
> +
> + if (issockbound((struct sockaddr *)&psi->locaddr))
> + psi->mode |= ISOCK_BIND;
> +
> + flag = 0;
> + flaglen = sizeof(flag);
> + PT_GETSOCKOPT(pid, num, SOL_SOCKET, SO_TYPE, &flag, &flaglen);
> + if (flag)
> + psi->type = flag;
> +
> flag = 0;
> - flaglen = (int)sizeof(flag);
> + flaglen = sizeof(flag);
> PT_GETSOCKOPT(pid, num, SOL_SOCKET, SO_REUSEADDR, &flag, &flaglen);
> if (flag) psi->opt |= ISOCK_REUSEADDR;
>
> flag = 0;
> - flaglen = (int)sizeof(flag);

```

```

> + flaglen = sizeof(flag);
> PT_GETSOCKOPT(pid, num, SOL_SOCKET, SO_ACCEPTCONN, &flag, &flaglen);
> if (flag) {
> psi->mode |= ISOCK_LISTEN;
> //t_d(PT_GETSOCKOPT(pid, num, SOL_TCP, TPI_INFO, &tpi_info, &tpi_info_len));
> }
>
> - namelen = (int)sizeof(name);
> + namelen = sizeof(name);
> if (PT_GETPEERNAME(pid, num, &name, &namelen) == 0) {
> t_d(psi->mode |= ISOCK_CONNECT);
> t_d(PT_GETSOCKOPT(pid, num, SOL_TCP, TPI_TCP_STATE, pi->si[pi->ns].tcpstate,
&tpi_len));
> @@ -859,6 +890,31 @@ error:
> return -1;
> }
>
> +static void bind_sock(pid_t pid, isockinfo_t *isockinfo)
> +{
> + int len;
> + struct sockaddr *sa;
> + struct sockaddr_in sin;
> + struct sockaddr_in6 sin6;
> +
> + if (isockinfo->family == AF_INET) {
> + len = sizeof(sin);
> + memcpy(&sin, &isockinfo->locaddr.saddr4, len);
> + if (isockinfo->mode & ISOCK_CONNECT)
> + sin6.sin6_port = htons(0);
> + sa = (struct sockaddr *) &sin;
> + } else if (isockinfo->family == AF_INET6) {
> + len = sizeof(sin6);
> + memcpy(&sin6, &isockinfo->locaddr.saddr6, len);
> + if (isockinfo->mode & ISOCK_CONNECT)
> + sin.sin_port = htons(0);
> + sa = (struct sockaddr *) &sin6;
> + } else
> + ERROR("Unsupported socket family: %d\n",
> + isockinfo->family);
> + t_d(PT_BIND(pid, isockinfo->fdnum, sa, len));
> +}
> +
> int restore_sock(int fd, pid_t pid)
> {
> char item[64];
> @@ -873,21 +929,18 @@ int restore_sock(int fd, pid_t pid)
> else ITEM_SET(isockinfo, isockinfo_t);
> else break; // unknown item

```

```

>
> - t_d(sock = PT_SOCKET(pid, AF_INET, SOCK_STREAM, 0));
> + t_d(sock = PT_SOCKET(pid, isockinfo->family, isockinfo->type, 0));
>   if (sock < 0) {
>     ERROR("PT_SOCKET(%d, %d, %d, %d) errno=%d: %s",
> -   pid, AF_INET, SOCK_STREAM, 0, sock, strerror(-sock));
> +   pid, isockinfo->family, isockinfo->type, 0,
> +   sock, strerror(-sock));
>   }
>   t_d(PT_DUP2(pid, sock, isockinfo->fdnum));
>   if (sock != isockinfo->fdnum) t_d(PT_CLOSE(pid, sock));
>
> - if (isockinfo->mode & ISOCK_BIND) {
> -   struct sockaddr_in sin;
> +   if (isockinfo->mode & ISOCK_BIND)
> +     bind_sock(pid, isockinfo);
>
> -   memcpy((void *)&sin, (void *)&isockinfo->locaddr, sizeof(sin));
> -   if (isockinfo->mode & ISOCK_CONNECT) sin.sin_port = htons(0);
> -   t_d(PT_BIND(pid, isockinfo->fdnum, &sin, sizeof(sin)));
> - }
>   if (isockinfo->mode & ISOCK_LISTEN) {
>     t_d(PT_LISTEN(pid, isockinfo->fdnum, 64)); //FIXME: get backlog from TPI_INFO
>   }
>
> --

```

Containers mailing list
 Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
