

---

Subject: vztmpl-centos-5-2.0-3.i386.rpm  
Posted by [johan\\_hammy](#) on Fri, 22 Aug 2008 12:25:09 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Here is the end of my vzpkgcache:

Quote:Complete!  
sed: can't read /etc/init.d/syslog: No such file or directory  
ERROR: Script install-post failed

What does that mean?

---

---

Subject: Re: vztmpl-centos-5-2.0-3.i386.rpm  
Posted by [ft.linux](#) on Tue, 02 Sep 2008 02:47:49 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

vi /vz/template/centos/5/i386/config/install.post

The following is no longer required as there is no separate klogd daemon in rsyslog:

```
# Disable klogd
#$VZCTL exec2 $VEID \
#   "sed -i -e 's/daemon\\ klogd/passed\\ klogd\\ skipped/' \
#       -e 's/killproc\\ klogd/passed\\ klogd\\ skipped/' \
#       /etc/init.d/syslog"
# FIXME: fix '/etc/init.d/syslog status' to return 0
# even if klogd is not running
```

Change the /etc/syslog.conf to /etc/rsyslog.conf in the following area of the file:

```
# Disable fsync() in syslog
$VZCTL exec2 $VEID \
    'sed -i -e s@[[:space:]]\\)\\(/var/log/\\)@\\1-\\2@' \
    /etc/rsyslog.conf
```

Now your templates should build perfectly.

---