
Subject: How about post-VE-start scripts?
Posted by [VinzC](#) on Wed, 10 Dec 2008 15:54:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi.

I want to mount a filesystem that I dedicated for SAMBA storage for use in a virtual environment. I explored several threads here and I saw a) ext3 cannot be mounted from a VE (because of threading issues) and b) mount --bind should be used instead from the physical host.

While I have nothing against the --bind way I must first make sure the VE is mounted in /vz/root/<VEID> an running before binding. Hence my question is: does OpenVZ support post-start/post-mount scripts? Or do I have to tweak OpenVZ init script on my Gentoo machine?

Thanks for any hint/suggestion.

Subject: Re: How about post-VE-start scripts?
Posted by [piavlo](#) on Thu, 11 Dec 2008 08:57:55 GMT
[View Forum Message](#) <> [Reply to Message](#)

You can use /etc/vz/conf/vps.mount & /etc/vz/conf/vps.umount scripts, here is how i've done it:

```
projsrv3 ~ # cat /etc/vz/conf/vps.mount
#!/bin/bash
```

```
if [ -x /vz/root/${VEID}/.cs-chroot.start ]; then
    /vz/root/${VEID}/.cs-chroot.start
    exit $?
fi
```

```
projsrv3 ~ # cat /etc/vz/conf/vps.umount
#!/bin/bash
```

```
if [ -x /vz/root/${VEID}/.cs-chroot.stop ]; then
    /vz/root/${VEID}/.cs-chroot.stop
    exit $?
fi
```

```
projsrv3 ~ # cat /vz/root/103/.cs-chroot.start
#!/bin/bash
```

```
mount -n --bind /vz/template/portage $(dirname $0)/usr/portage || exit ${?}
mount -n --bind /vz/template/portage-distfiles $(dirname $0)/usr/portage/distfiles || exit ${?}
mount -n --bind /vz/template/portage-packages $(dirname $0)/usr/portage/packages || exit ${?}
projsrv3 ~ # cat /vz/root/103/.cs-chroot.stop
#!/bin/bash
```

```
umount $(dirname $0)/usr/portage/packages
umount $(dirname $0)/usr/portage/distfiles
```

umount \$(dirname \$0)/usr/portage
projsrv3 ~ #

Subject: Re: How about post-VE-start scripts?
Posted by [VinzC](#) on Fri, 12 Dec 2008 16:33:50 GMT
[View Forum Message](#) <> [Reply to Message](#)

Cool, thanks a lot! I completely overlooked that from the documentation. Fortunately Gentoo Wiki (from Google cache) mentions such a thing, including per-VE mount/umount scripts.

OpenVZ is definitely well thought. Respect!
