

---

Subject: \*SOLVED\* OpenVZ mount script works incorrectly

Posted by [cray](#) on Thu, 22 Oct 2009 13:58:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

MySQL database works on host. I want to share /var/run/mysqld/ directory to guest system.

Here is my 101.mount script

```
#!/bin/bash
```

```
mount --bind -n /var/run/mysqld /home/vz/root/${VEID}/var/run/mysqld
```

When I run

```
vzctl start 101
```

it wipes whole host directory /var/run/mysqld, and mysql went down. So I have no '/var/run/mysqld' and no '/home/vz/root/\${VEID}/var/run/mysqld'.

When I'm trying to mount this directory manually after the guest system was started - everything works fine.

What is wrong?

I'm running Debian Lenny Linux host 2.6.26-2-openvz-686 #1 SMP Wed Aug 19 07:30:34 UTC 2009 i686 GNU/Linux

```
vzctl --version
```

```
vzctl version 3.0.22
```

---

---

Subject: Re: OpenVZ mount script works incorrectly

Posted by [kir](#) on Thu, 22 Oct 2009 14:05:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Why do you think it's vzctl that wipes /var/run/mysql? It can be anything else, such as in-container scripts.

---

---

Subject: Re: OpenVZ mount script works incorrectly

Posted by [cray](#) on Thu, 22 Oct 2009 14:46:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I used the Debian template from [openvz.org](http://download.openvz.org)

<http://download.openvz.org/template/precreated/debian-5.0-x86.tar.gz>

I have grep'ed it, and didn't find anything strange on first glance. I will check more deeply.

---

---

Subject: Re: OpenVZ mount script works incorrectly

---

Posted by [cray](#) on Thu, 22 Oct 2009 14:48:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Which scripts should I check?

/etc dir doesn't have anything strange with the mysqld word.

---

---

Subject: Re: OpenVZ mount script works incorrectly

Posted by [cray](#) on Thu, 22 Oct 2009 14:54:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

I have just found the following scripts:

/etc/init.d/mountall-bootclean.sh

/lib/init/bootclean.sh

First one run /lib/init/bootclean.sh and it cleans the /var/run dir.

Thanks for help =)

---