
Subject: Debug upstart

Posted by [Macumazan](#) on Mon, 27 Sep 2010 06:25:18 GMT

[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart

Posted by [RXL_](#) on Mon, 27 Sep 2010 18:05:07 GMT

[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart

Posted by [Macumazan](#) on Mon, 27 Sep 2010 19:22:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart

Posted by [RXL_](#) on Mon, 27 Sep 2010 20:58:21 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
+ len = sprintf(page, "%s\n",  
+ ve_is_super(get_exec_env()) ? saved_command_line : "quiet");
```

Subject: Re: Debug upstart
Posted by [Macumazan](#) on Tue, 28 Sep 2010 07:01:53 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
# rc-sysinit - System V initialisation compatibility  
#  
# This task runs the old System V-style system initialisation scripts,  
# and enters the default runlevel when finished.  
  
description    "System V initialisation compatibility"  
author        "Scott James Remnant <scott@netsplit.com>"  
  
start on filesystem  
stop on runlevel  
  
# Default runlevel, this may be overridden on the kernel command-line  
# or by faking an old /etc/inittab entry  
env DEFAULT_RUNLEVEL=2  
  
# There can be no previous runlevel here, but there might be old  
# information in /var/run/utmp that we pick up, and we don't want  
# that.  
#  
# These override that  
env RUNLEVEL=  
env PREVLEVEL=  
  
#console output  
env INIT_VERBOSE  
  
task  
  
script  
# Check for default runlevel in /etc/inittab  
if [ -r /etc/inittab ]  
then  
    eval "$(sed -nre 's/^[^#][^:]*:([0-6sS]):initdefault:./DEFAULT_RUNLEVEL="\1";/p' /etc/inittab
```

```

|| true)"
fi

# Check kernel command-line for typical arguments
for ARG in $(cat /proc/cmdline)
do
    case "${ARG}" in
        -b|emergency)
            # Emergency shell
            [ -n "${FROM_SINGLE_USER_MODE}" ] || sulogin
            ;;
        [0123456sS])
            # Override runlevel
            DEFAULT_RUNLEVEL="${ARG}"
            ;;
        -s|single)
            # Single user mode
            [ -n "${FROM_SINGLE_USER_MODE}" ] || DEFAULT_RUNLEVEL=S
            ;;
    esac
done

# Run the system initialisation scripts
[ -n "${FROM_SINGLE_USER_MODE}" ] || /etc/init.d/rcS

# Switch into the default runlevel
telinit "${DEFAULT_RUNLEVEL}"
end script

```

```
telinit "${DEFAULT_RUNLEVEL}"
```

```
telinit -v "${DEFAULT_RUNLEVEL}"
```

Subject: Re: Debug upstart
 Posted by [RXL_](#) on Tue, 28 Sep 2010 07:56:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart
Posted by [Macumazan](#) on Tue, 28 Sep 2010 09:09:17 GMT
[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart
Posted by [RXL_](#) on Tue, 28 Sep 2010 10:44:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart
Posted by [Macumazan](#) on Tue, 28 Sep 2010 13:49:33 GMT
[View Forum Message](#) <> [Reply to Message](#)

```
static int cmdline_proc_show(struct seq_file *m, void *v)
{
    seq_printf(m, "%s\n",
        ve_is_super(get_exec_env()) ? saved_command_line : "quiet");
    return 0;
}
```

Subject: Re: Debug upstart
Posted by [RXL_](#) on Tue, 28 Sep 2010 15:40:32 GMT
[View Forum Message](#) <> [Reply to Message](#)

Subject: Re: Debug upstart
Posted by [Macumazan](#) on Tue, 28 Sep 2010 17:42:10 GMT
[View Forum Message](#) <> [Reply to Message](#)
