Subject: VE "route" command shows 191.255.255.1 Posted by John Kelly on Tue, 01 Aug 2006 21:39:42 GMT

View Forum Message <> Reply to Message

Why?

daves:~ # route

Kernel IP routing table

Destination Gateway Genmask Flags Metric Ref Use Iface

191.255.255.0 * 255.255.255.0 U 0 0 venet0

loopback * 255.0.0.0 U 0 0 0 lo

default 191.255.255.1 0.0.0.0 UG 0 0 venet0

rfc3330 says:

191.255.0.0/16 - This block, corresponding to the numerically highest to the former Class B addresses, was initially and is still reserved by the IANA. Given the present classless nature of the IP address space, the basis for the reservation no longer applies and addresses in this block are subject to future allocation to a Regional Internet Registry for assignment in the normal manner.

Subject: Re: VE "route" command shows 191.255.255.1 Posted by Vasily Tarasov on Wed, 02 Aug 2006 07:46:32 GMT

View Forum Message <> Reply to Message

HOST node is a gateway for VE.

VE is connected to HOST usign venet interface.

So in routing table of VE appropriate gateway must be set.

Why IP address 191.255.255.1 is used? You've already answered on

it:

Quote:rfc3330 says:...

Subject: Re: VE "route" command shows 191.255.255.1 Posted by hvdkamer on Wed, 02 Aug 2006 07:47:44 GMT

View Forum Message <> Reply to Message

For the same reason I changed the debian-add_ip.sh script to something more meaningful for my VEx's. In the distro-add_ip.sh script you see:

FAKEGATEWAY=192.168.13.1 FAKEGATEWAYNET=192.168.13.0

I've no idea why OpenVZ chooses the one it is now using. May be it has to change to something

Subject: Re: VE "route" command shows 191.255.255.1 Posted by aistis on Wed, 02 Aug 2006 10:15:17 GMT

View Forum Message <> Reply to Message

I'm sorry, less harmful than what? While IANA decides on future fate of those subnets, they are perfectly fit for such stuff.

Subject: Re: VE "route" command shows 191.255.255.1 Posted by hvdkamer on Wed, 02 Aug 2006 10:29:35 GMT

View Forum Message <> Reply to Message

I disagree. If IANA says it is going to reassign those IP-addresses, it is better to not use them anymore. For now the old situation is not a problem, but it will become one!

I recall a session with a computer user group. One visitor had problems to connect to its home computer. So we decided to tackle the problem. After a lot of investigation we discoverd that the helpdesk of his router had said that the IP-adresses 192.168.x.y where way to common and you shouldn't use them. Therfore he had picked one at random. So on this meeting we were actively hacking a computer which was own by a Swiss bank. Luckiley we weren't arrested

The moral of this story? Don't use IP-adresses which don't belong to you. Even if it is at this moment not used. It can change and funny problems can occur. So why risk that?

Subject: Re: VE "route" command shows 191.255.255.1 Posted by aistis on Wed, 02 Aug 2006 10:48:49 GMT

View Forum Message <> Reply to Message

alright, so your proposal is to use one of the following:

172.16.0.0/12 192.168.0.0/16

?

Subject: Re: VE "route" command shows 191.255.255.1 Posted by hvdkamer on Wed, 02 Aug 2006 11:11:18 GMT

View Forum Message <> Reply to Message

Yep. Or the 10.0.0.0/8 series? Those three ar private and I think perfect for this kind of things. Or are there other reasons why the current one was choosen? On my box the 192.168.13.x series work...

Subject: Re: VE "route" command shows 191.255.255.1 Posted by aistis on Wed, 02 Aug 2006 11:43:01 GMT View Forum Message <> Reply to Message

my bet - because such subnets never appear on internal networks, while 192.168.0.0/16 / 172.16.0.0/12 / 10.0.0.0/8 are fairly common.

Subject: Re: VE "route" command shows 191.255.255.1 Posted by John Kelly on Wed, 02 Aug 2006 12:07:57 GMT

View Forum Message <> Reply to Message

At http://www.iana.org/faqs/abuse-faq.htm

IANA says about "Unallocated" IP addresses:

Quote:The IPv4 Address Registry and the Whois use the word unallocated (sometimes "reserved") to mean that the addresses are reserved for future allocation. No one should be using these addresses now. These addresses will be assigned for use in the public Internet in the future. If addresses are needed for private networks then the private-use addresses mentioned [in rfc1918] should be used.

Of the rfc1918 private addresses, I might chose something like 10.254.254.0/24. Problem is, no matter what rfc1918 block is chosen for the script default, it may collide with some user's private allocations.

According to rfc3330, a better choice may be:

192.0.2.0/24 - This block is assigned as "TEST-NET" for use in documentation and example code. It is often used in conjunction with domain names example.com or example.net in vendor and protocol documentation. Addresses within this block should not appear on the public Internet.

If that disturbs an end user, they can modify the scripts to an rfc1918 value which does not collide with their own private allocations.

Subject: Re: VE "route" command shows 191.255.255.1 Posted by Valmont on Wed, 02 Aug 2006 18:00:47 GMT

View Forum Message <> Reply to Message

I agree with it. 192.0.2.0/24 looks more preferable, rather than use local subnet's (192.168.0.0/16 / 172.16.0.0/12 / 10.0.0.0/8). To avoid of possible conflicts with already existing local subnet's.