
Posted by [cac2s](#) on Thu, 09 Dec 2010 16:06:37 GMT

[View Forum Message](#) <> [Reply to Message](#)

- * debian squeeze
- * eth0 - wan
- * eth1 - lan (192.168.1.0/24)

```
$TC qdisc del dev venet0 root >/dev/null 2>&1
$TC qdisc del dev venet0 ingress >/dev/null 2>&1
$TC qdisc del dev ifb0 root >/dev/null 2>&1
$TC qdisc del dev ifb0 ingress >/dev/null 2>&1
```

```
$TC qdisc add dev venet0 ingress
$TC filter add dev venet0 parent ffff: protocol ip u32 match u32 0 0 action mirred egress redirect
dev ifb0
```

```
$TC qdisc add dev ifb0 root handle 1: htb default 10
$TC class add dev ifb0 parent 1: classid 1:10 htb rate 800kbit ceil 800kbit
  $TC qdisc add dev ifb0 parent 1:10 handle 10: sfq perturb 5
```

```
ifconfig ifb0 up
```

Posted by [cac2s](#) on Wed, 15 Dec 2010 11:44:47 GMT

[View Forum Message](#) <> [Reply to Message](#)

```
#!/bin/bash
```

```
IPT="/sbin/iptables"
```

```
TC="/sbin/tc"
```

```
IP="/bin/ip"
```

```
$TC qdisc del dev venet0 root >/dev/null 2>&1
$TC qdisc del dev venet0 ingress >/dev/null 2>&1
$TC qdisc del dev ifb0 root >/dev/null 2>&1
$TC qdisc del dev ifb0 ingress >/dev/null 2>&1
```

```
$IP link set ifb0 down
rmmod ifb
modprobe ifb numifbs=1
$IP link set ifb0 up
```

```
=====
```

```
=====
```

```
$TC qdisc add dev venet0 root handle 1: prio
```

```
$TC qdisc add dev venet0 ingress
```

```
  $TC filter add dev venet0 parent 1: protocol ip u32 match u32 0 0 action mirred egress redirect
dev ifb0
```

```
=====
```

```
=====
```

```
$TC qdisc add dev ifb0 root handle 1: htb
```

```
$TC class add dev ifb0 parent 1: classid 1:10 htb rate 80kbit ceil 80kbit
```

```
  $TC qdisc add dev ifb0 parent 1:10 handle 10: sfq perturb 5
```

```
  $TC filter add dev ifb0 parent 1: prio 10 protocol ip u32 match ip dst 192.168.254.254 flowid
1:10
```
