
Subject: Problems with Gentoo template creation
Posted by [Ronald Tanner](#) on Wed, 09 Aug 2006 15:54:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi

On a Gentoo/OpenVZ system with kernel 2.6.16-026test015 I created a gentoo template by following the instructions on

http://wiki.openvz.org/Gentoo_template_creation

I am now encountering several problems with the VPS that are created using this template
I cannot find the "random" devices that are needed for example to generate the host key for ssh. The problem is maybe somehow related with the link of /etc/mtab -> /proc/mounts.
After removing the link and adding the following line into /etc/mtab on the VPS:

```
proc /proc proc rw 0 0
```

at least the device urandom exists and I am able to create the host keys. But now I cannot ping the VPS:

VPSID	NPROC	STATUS	IP_ADDR	HOSTNAME
500	3	running	10.0.186.10	-

```
ping 10.0.186.10 (no answer)
```

entering works:

```
vzctl enter 500
```

Thanks for any help.

Ronald

Subject: Re: Problems with Gentoo template creation
Posted by [dwebwarm](#) on Wed, 09 Aug 2006 20:07:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

Actually /proc is not related to u/random. This are regular devices in /dev. Can you try to create the devices using mknod inside the VPS...

```
vzctl exec 500 mknod -m 666 /dev/random c 1 8  
vzctl exec 500 mknod -m 444 /dev/urandom c 1 9
```

Martin

Ronald Tanner wrote:

```
> Hi
>
> On a Gentoo/OpenVZ system with kernel 2.6.16-026test015 I created a
> gentoo template by following the instructions on
>
> http://wiki.openvz.org/Gentoo_template_creation
>
> I am now encountering several problems with the VPS
> that are created using this template
> I cannot find the "random" devices that are needed for example
> to generate the host key for ssh. The problem is maybe somehow
> related with the link of /etc/mtab -> /proc/mounts.
> After removing the link and adding the following
> line into /etc/mtab on the VPS:
>
> proc /proc proc rw 0 0
>
> at least the device urandom exists and I am able to create the
> host keys. But now I cannot ping the VPS:
>
>   VPSID   NPROC STATUS IP_ADDR   HOSTNAME
>   500     3 running 10.0.186.10  -
>
> ping 10.0.186.10 (no answer)
>
> entering works:
>
> vzctl enter 500
>
>
> Thanks for any help.
>
> Ronald
>
```

Subject: Re: Problems with Gentoo template creation
Posted by [Ronald Tanner](#) on Thu, 10 Aug 2006 05:59:57 GMT
[View Forum Message](#) <> [Reply to Message](#)

No problem, I can create these devices.
However after a reboot they are lost because /dev is mounted
on tmpfs and gentoo uses udev.

Besides: do you have any idea why I have to set the routes

```
/sbin/route add -net 191.255.255.1 netmask 255.255.255.255 dev venet0  
/sbin/route add default gw 191.255.255.1
```

on the VE by hand to get the net working?

Regards
Ronald

Martin Dobrev wrote:

> Actually /proc is not related to u/random. This are regular devices in
> /dev. Can you try to create the devices using mknod inside the VPS...

```
>  
> vzctl exec 500 mknod -m 666 /dev/random c 1 8  
> vzctl exec 500 mknod -m 444 /dev/urandom c 1 9
```

> Martin

> Ronald Tanner wrote:

>> Hi

>>

>> On a Gentoo/OpenVZ system with kernel 2.6.16-026test015 I created a
>> gentoo template by following the instructions on

>>

>> http://wiki.openvz.org/Gentoo_template_creation

>>

>> I am now encountering several problems with the VPS

>> that are created using this template

>> I cannot find the "random" devices that are needed for example

>> to generate the host key for ssh. The problem is maybe somehow

>> related with the link of /etc/mtab -> /proc/mounts.

>> After removing the link and adding the following

>> line into /etc/mtab on the VPS:

>>

```
>> proc /proc proc rw 0 0
```

>>

>> at least the device urandom exists and I am able to create the

>> host keys. But now I cannot ping the VPS:

>>

```
>>  VPSID    NPROC STATUS IP_ADDR    HOSTNAME  
>>   500      3 running 10.0.186.10  -
```

>>

```
>> ping 10.0.186.10 (no answer)
```

>>

>> entering works:

>>

```
>> vzctl enter 500
```

>>
>>
>> Thanks for any help.
>>
>> Ronald
>>
--

Ronald Tanner
SEMAFOR Informatik & Energie AG tel. +41 61 690 9888
Sperrstrasse 104B fax. +41 61 690 9880
CH 4057 Basel Switzerland mailto:tanner@semafor.ch

Subject: Re: Problems with Gentoo template creation
Posted by [kir](#) on Thu, 10 Aug 2006 08:21:19 GMT
[View Forum Message](#) <> [Reply to Message](#)

Ronald Tanner wrote:

> No problem, I can create these devices.
> However after a reboot they are lost because /dev is mounted
> on tmpfs and gentoo uses udev.
>
> Can you make it NOT use udev? The thing is udev is really useless in a VE.
> Probably setting RC_DEVICES="static" in /etc/conf.d/rc helps.
> Besides: do you have any idea why I have to set the routes
>
> /sbin/route add -net 191.255.255.1 netmask 255.255.255.255 dev venet0
> /sbin/route add default gw 191.255.255.1
>
> on the VE by hand to get the net working?
>
> This is a trick to have everything routed to venet0. To set it
> automatically (by vzctl) you have to name your template
> gentoo-(something), so vzctl will guess this is gentoo (by looking at
> the value of OSTEMPLATE in /etc/vz/conf/NNN.conf) and will apply the
> appropriate scripts when doing vzctl set NNN --ipadd --save

Can you try this instead:
/sbin/route add default dev venet0
and check if it will work for you?

Subject: Re: Problems with Gentoo template creation
Posted by [Ronald Tanner](#) on Thu, 10 Aug 2006 12:12:13 GMT
[View Forum Message](#) <> [Reply to Message](#)

Thanks. Setting RC_DEVICES to static on the gentoo VE seems to fix

the dev problem.

I am currently not able to check the routing as I must rebuild the kernel to include iptables. We want to use NAT for our VEs.

I will come back.

Ronald

Kir Kolyshkin wrote:

> Ronald Tanner wrote:

>> No problem, I can create these devices.

>> However after a reboot they are lost because /dev is mounted

>> on tmpfs and gentoo uses udev.

>>

> Can you make it NOT use udev? The thing is udev is really useless in a VE.

> Probably setting RC_DEVICES="static" in /etc/conf.d/rc helps.

>> Besides: do you have any idea why I have to set the routes

>>

>> /sbin/route add -net 191.255.255.1 netmask 255.255.255.255 dev venet0

>> /sbin/route add default gw 191.255.255.1

>>

>> on the VE by hand to get the net working?

>>

> This is a trick to have everything routed to venet0. To set it

> automatically (by vzctl) you have to name your template

> gentoo-(something), so vzctl will guess this is gentoo (by looking at

> the value of OSTEMPLATE in /etc/vz/conf/NNN.conf) and will apply the

> appropriate scripts when doing vzctl set NNN --ipadd --save

>

> Can you try this instead:

> /sbin/route add default dev venet0

> and check if it will work for you?

Subject: Re: Problems with Gentoo template creation

Posted by [kir](#) on Thu, 10 Aug 2006 12:20:22 GMT

[View Forum Message](#) <> [Reply to Message](#)

Ronald Tanner wrote:

> Thanks. Setting RC_DEVICES to static on the gentoo VE seems to fix

> the dev problem.

>

Can you put this finding (as well as anything else you found) to the appropriate wiki page?

> I am currently not able to check the routing as I must rebuild

> the kernel to include iptables. We want to use NAT for our VEs.

>

> I will come back.

> Ronald
>
> Kir Kolyshkin wrote:
>
>> Ronald Tanner wrote:
>>
>>> No problem, I can create these devices.
>>> However after a reboot they are lost because /dev is mounted
>>> on tmpfs and gentoo uses udev.
>>>
>>>
>> Can you make it NOT use udev? The thing is udev is really useless in a VE.
>> Probably setting RC_DEVICES="static" in /etc/conf.d/rc helps.
>>
>>> Besides: do you have any idea why I have to set the routes
>>>
>>> /sbin/route add -net 191.255.255.1 netmask 255.255.255.255 dev venet0
>>> /sbin/route add default gw 191.255.255.1
>>>
>>> on the VE by hand to get the net working?
>>>
>>>
>> This is a trick to have everything routed to venet0. To set it
>> automatically (by vzctl) you have to name your template
>> gentoo-(something), so vzctl will guess this is gentoo (by looking at
>> the value of OSTEMPLATE in /etc/vz/conf/NNN.conf) and will apply the
>> appropriate scripts when doing vzctl set NNN --ipadd --save
>>
>> Can you try this instead:
>> /sbin/route add default dev venet0
>> and check if it will work for you?
>>
>

Subject: Re: Problems with Gentoo template creation
Posted by [Ronald Tanner](#) on Thu, 10 Aug 2006 12:32:04 GMT
[View Forum Message](#) <> [Reply to Message](#)

I'll care about that.

Kir Kolyshkin wrote:
> Can you put this finding (as well as anything else you found) to the
> appropriate wiki page?

Subject: Re: Problems with Gentoo template creation

Posted by [Ronald Tanner](#) on Fri, 11 Aug 2006 12:53:45 GMT

[View Forum Message](#) <> [Reply to Message](#)

My experiments show that setting the route with

```
/sbin/route add default dev venet0
```

on the VPS is sufficient.

```
localhost / # route -n
```

```
Kernel IP routing table
```

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
127.0.0.0	127.0.0.1	255.0.0.0	UG	0	0	0	lo
0.0.0.0	0.0.0.0	0.0.0.0	U	0	0	0	venet0

But if you have the line

```
OSTEMPLATE=gentoo-something
```

in your config file (eg. `/etc/vz/777.conf`) the routes are added automatically when you set up the ip address. However they look different:

```
localhost / # route -n
```

```
Kernel IP routing table
```

Destination	Gateway	Genmask	Flags	Metric	Ref	Use	Iface
191.255.255.0	0.0.0.0	255.255.255.0	U	0	0	0	venet0
127.0.0.0	127.0.0.1	255.0.0.0	UG	0	0	0	lo
0.0.0.0	191.255.255.1	0.0.0.0	UG	0	0	0	venet0

for me these routes are somehow strange.

And there is another step in the preparation of the os template which needs some explanation. Why do I have to replace `/etc/mstab` with a link to `/proc/mounts`?

Regards

Ronald

Subject: Re: Problems with Gentoo template creation

Posted by [kir](#) on Fri, 11 Aug 2006 16:31:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

Ronald Tanner wrote:

> And there is another step in the preparation of the os template which
> needs some explanation. Why do I have to replace `/etc/mstab` with
> a link to `/proc/mounts`?

This is because VE root filesystem is mounted by the host system, not the guest -- and therefore root fs will not appear in /etc/mtab. It will lead to df command non-working.

If you will replace /etc/mtab with a symlink to /proc/mounts, you will always have up-to-date information of what is mounted in /etc/mtab.

Subject: Re: Problems with Gentoo template creation
Posted by [Ronald Tanner](#) on Tue, 15 Aug 2006 07:45:31 GMT
[View Forum Message](#) <> [Reply to Message](#)

Thanks. I have just updated the wiki page
http://wiki.openvz.org/Gentoo_template_creation
with your comments.

one last (?) question remains:
Don't you think that the steps described in "Set up udev"
http://wiki.openvz.org/Gentoo_template_creation#Set_up_udev
are obsolete when RC_DEVICES is set to "static" in /etc/conf.d/rc?

Regards
Ronald

Kir Kolyshkin wrote:

> Ronald Tanner wrote:

>> And there is another step in the preparation of the os template which
>> needs some explanation. Why do I have to replace /etc/mtab with
>> a link to /proc/mounts?

> This is because VE root filesystem is mounted by the host system, not
> the guest -- and therefore root fs will not appear in /etc/mtab. It will
> lead to df command non-working.

>

> If you will replace /etc/mtab with a symlink to /proc/mounts, you will
> always have up-to-date information of what is mounted in /etc/mtab.

--

Ronald Tanner
SEMAFOR Informatik & Energie AG tel. +41 61 690 9888
Sperrstrasse 104B fax. +41 61 690 9880
CH 4057 Basel Switzerland mailto:tanner@semafor.ch
