
Subject: [PATCH] Reduce uidhash lock hold time when lookup succeeds

Posted by Matt Helsley on Thu, 17 Feb 2011 23:52:53 GMT

[View Forum Message](#) <> [Reply to Message](#)

When lookup succeeds we don't need the "new" user struct which hasn't been linked into the uidhash. So we can immediately drop the lock and then free "new" rather than free it with the lock held.

Signed-off-by: Matt Helsley <matthltc@us.ibm.com>

Cc: David Howells <dhowells@redhat.com>

Cc: Pavel Emelyanov <xemul@parallels.com>

Cc: Alexey Dobriyan <adobriyan@gmail.com>

Cc: "Serge E. Hallyn" <serge@hallyn.com>

Cc: containers@lists.linux-foundation.org

kernel/user.c | 12 ++++++-----

1 files changed, 7 insertions(+), 5 deletions(-)

diff --git a/kernel/user.c b/kernel/user.c

index 5c598ca..4ea8e58 100644

--- a/kernel/user.c

+++ b/kernel/user.c

@@ -157,16 +157,18 @@ struct user_struct *alloc_uid(struct user_namespace *ns, uid_t uid)

*/

spin_lock_irq(&uidhash_lock);
up = uid_hash_find(uid, hashent);

- if (up) {

+ if (!up) {

+ uid_hash_insert(new, hashent);

+ up = new;

+ }

+ spin_unlock_irq(&uidhash_lock);

+

+ if (up != new) {

put_user_ns(ns);

key_put(new->uid_keyring);

key_put(new->session_keyring);

kmem_cache_free(uid_cachep, new);

- } else {

- uid_hash_insert(new, hashent);

- up = new;

}

- spin_unlock_irq(&uidhash_lock);

}

return up;

--

1.6.3.3

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>

Subject: Re: [PATCH] Reduce uidhash lock hold time when lookup succeeds

Posted by [Serge E. Hallyn](#) on Fri, 18 Feb 2011 18:25:02 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quoting Matt Helsley (matthltc@us.ibm.com):

> When lookup succeeds we don't need the "new" user struct which hasn't
> been linked into the uidhash. So we can immediately drop the lock and
> then free "new" rather than free it with the lock held.

>

> Signed-off-by: Matt Helsley <matthltc@us.ibm.com>
> Cc: David Howells <dhowells@redhat.com>
> Cc: Pavel Emelyanov <xemul@parallels.com>
> Cc: Alexey Dobriyan <adobriyan@gmail.com>
> Cc: "Serge E. Hallyn" <serge@hallyn.com>

Acked-by: Serge E. Hallyn <serge@hallyn.com>

And might I say that the label 'out_unlock' in that function is
sadly named :)

> Cc: containers@lists.linux-foundation.org
> ---
> kernel/user.c | 12 ++++++-----
> 1 files changed, 7 insertions(+), 5 deletions(-)
>
> diff --git a/kernel/user.c b/kernel/user.c
> index 5c598ca..4ea8e58 100644
> --- a/kernel/user.c
> +++ b/kernel/user.c
> @@ -157,16 +157,18 @@ struct user_struct *alloc_uid(struct user_namespace *ns, uid_t uid)
> */
> spin_lock_irq(&uidhash_lock);
> up = uid_hash_find(uid, hashent);
> - if (up) {
> + if (!up) {
> + uid_hash_insert(new, hashent);
> + up = new;
> + }
> + spin_unlock_irq(&uidhash_lock);
> +
> + if (up != new) {

```
>     put_user_ns(ns);
>     key_put(new->uid_keyring);
>     key_put(new->session_keyring);
>     kmem_cache_free(uid_cachep, new);
> - } else {
> -     uid_hash_insert(new, hashent);
> -     up = new;
> - }
> - spin_unlock_irq(&uidhash_lock);
> }
>
> return up;
> --
> 1.6.3.3
>
> _____
```

> Containers mailing list
> Containers@lists.linux-foundation.org
> <https://lists.linux-foundation.org/mailman/listinfo/containers>

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
