

---

Subject: [PATCH] cgroup: prefer [kv]zalloc over [kv]malloc+memset in memory controller code.

Posted by [Jesper Juhl](#) on Mon, 01 Nov 2010 19:40:56 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hi (please CC me on replies),

Apologies to those who receive this multiple times. I screwed up the To: field in my original mail :-(

In `mem_cgroup_alloc()` we currently do either `kmalloc()` or `vmalloc()` then followed by `memset()` to zero the memory. This can be more efficiently achieved by using `kzalloc()` and `vzalloc()`.

Signed-off-by: Jesper Juhl <[jj@chaosbits.net](mailto:jj@chaosbits.net)>

---

memcontrol.c | 5 ++---

1 file changed, 2 insertions(+), 3 deletions(-)

diff --git a/mm/memcontrol.c b/mm/memcontrol.c

index 9a99cfa..90da698 100644

--- a/mm/memcontrol.c

+++ b/mm/memcontrol.c

@@ -4199,14 +4199,13 @@ static struct mem\_cgroup \*mem\_cgroup\_alloc(void)

/\* Can be very big if MAX\_NUMNODES is very big \*/

if (size < PAGE\_SIZE)

- mem = kmalloc(size, GFP\_KERNEL);

+ mem = kzalloc(size, GFP\_KERNEL);

else

- mem = vmalloc(size);

+ mem = vzalloc(size);

if (!mem)

return NULL;

- memset(mem, 0, size);

mem->stat = alloc\_percpu(struct mem\_cgroup\_stat\_cpu);

if (!mem->stat) {

if (size < PAGE\_SIZE)

--

Jesper Juhl <[jj@chaosbits.net](mailto:jj@chaosbits.net)>

<http://www.chaosbits.net/>

Plain text mails only, please

<http://www.expita.com/nomime.html>

Don't top-post <http://www.catb.org/~esr/jargon/html/T/top-post.html>

---

Containers mailing list

[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---