
Subject: [PATCH cgroups] Remove deprecated subsystem from examples.

Posted by [Trevor Woerner](#) on Wed, 15 Dec 2010 02:28:08 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Trevor Woerner <twoerner@gmail.com>

The 'ns' cgroup is considered deprecated. Change the cgroup subsystem used in the examples of the cgroup documentation from 'ns' to 'blkio'.

Acked-by: Li Zefan <lizf@cn.fujitsu.com>

Acked-by: Paul Menage <menage@google.com>

Signed-off-by: Trevor Woerner <twoerner@gmail.com>

Documentation/cgroups/cgroups.txt | 8 ++++----

1 files changed, 4 insertions(+), 4 deletions(-)

diff --git a/Documentation/cgroups/cgroups.txt b/Documentation/cgroups/cgroups.txt

index 190018b..44b8b7a 100644

--- a/Documentation/cgroups/cgroups.txt

+++ b/Documentation/cgroups/cgroups.txt

@@ -355,13 +355,13 @@ subsystems, type:

To change the set of subsystems bound to a mounted hierarchy, just remount with different options:

-# mount -o remount,cpuset,ns hier1 /dev/cgroup

+# mount -o remount,cpuset,blkio hier1 /dev/cgroup

-Now memory is removed from the hierarchy and ns is added.

+Now memory is removed from the hierarchy and blkio is added.

-Note this will add ns to the hierarchy but won't remove memory or

+Note this will add blkio to the hierarchy but won't remove memory or cpuset, because the new options are appended to the old ones:

-# mount -o remount,ns /dev/cgroup

+# mount -o remount,blkio /dev/cgroup

To Specify a hierarchy's release_agent:

mount -t cgroup -o cpuset,release_agent="/sbin/cpuset_release_agent" \

--

1.7.1

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
