
Subject: How to repair a container startup ?
Posted by [Cyrille37](#) on Tue, 19 Apr 2011 02:37:19 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi,

My container startup is in interactive mode ... How to answer to it ?

Here is the container log :

```
...
raidautorun: failed to open /dev/md0: Operation not permitted
awk: cmd. line:1: fatal: cannot open file `/proc/misc' for reading (No such file or directory)
Mounting local filesystems: [ OK ]
ng /etc/fstab swaps: [ OK ]
INIT: Entering runlevel: 3
Entering interactive startup
Start service iscsid (Y)es/(N)o/(C)ontinue? [Y]
```

I'd try to start it with --wait, but it do not give the chance to answer to the interactive startup ...

```
# vzctl start 101 --wait
```

```
...
File resolv.conf was modified
Setting quota ugidlimit: 0
Container start in progress, waiting ...
```

I try "vzctl enter 101" but it does not work :

```
# vzctl enter 101
enter into CT 101 failed
Unable to open pty: No such file or directory
```

Have you got an idea ? Should the only solution is to destroy the VM ?

Regards
Cyrille

Subject: Re: How to repair a container startup ?
Posted by [curtis_isparks](#) on Fri, 22 Apr 2011 18:05:46 GMT
[View Forum Message](#) <> [Reply to Message](#)

I don't know if this is what you are looking for, but you can disable the interactive prompts (so that your container will boot) by editing /etc/sysconfig/init and switching the PROMPT setting to no...

```
PROMPT=no
```

Hope this helps.

Subject: Re: How to repair a container startup ?
Posted by [Cyrille37](#) on Mon, 25 Apr 2011 13:12:08 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi
and thanks for your answer.

The fact is that I didn't see that I can easily access to the container file-system to apply your trick and other configuration. I was afraid that VMs are contained in a obscure file like with VirtualBox.

Thanks
Cyrille
