
Subject: OpenVZ Container with a PCI ISDN Card
Posted by [Daniel Bauer](#) on Tue, 31 May 2011 11:10:11 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hello,

I'm new to OpenVZ and wonder if it's possible to run an asterisk inside a container and give him full access to a digium B410 ISDN Card.

Thanks a lot for any hint
Daniel

Subject: Re: OpenVZ Container with a PCI ISDN Card
Posted by [Adeel Nazir](#) on Thu, 09 Jun 2011 07:05:19 GMT
[View Forum Message](#) <> [Reply to Message](#)

In theory, you should be able to. from the man pages of vzctl:

--devnodes device:r|w|rw|none

Give the container an access (r - read only, w - write only, rw - read/write, none - no access) to a device designated by the special file /dev/device. Device file is created in a container by vzctl.

--devices b|c:major:minor|all:[r|w|rw|none]

Give the container an access to a block or character device designated by its major and minor numbers. Device file have to be created manually.

----- Original Message -----

From: Daniel Bauer <mlist@dsb-gmbh.de>
To: users@openvz.org
Sent: Tue, May 31, 2011 4:10:11 AM
Subject: [Users] OpenVZ Container with a PCI ISDN Card

Hello,

I'm new to OpenVZ and wonder if it's possible to run an asterisk inside a container and give him full access to a digium B410 ISDN Card.

Thanks a lot for any hint
Daniel

Subject: Re: OpenVZ Container with a PCI ISDN Card - SOLVED
Posted by [Daniel Bauer](#) on Mon, 05 Dec 2011 07:55:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: "Adeel Nazir" <adeel_n@yahoo.com>

> In theory, you should be able to. from the man pages of vzctl:
>
> --devnodes device:r|w|rw|none
> Give the container an access (r - read only, w - write only,
> rw -
> read/write, none - no access) to a device designated by the
> special
> file /dev/device. Device file is created in a container by
> vzctl.

it really takes a long time, but now it's solved. You're absolutly
right, my mistake was, to look for the PCI Card without any drivers
installed in the HN. After loading the correct modules, I moved the
access to the asterisk in the VPS.

Thanks
Daniel

> --devices b|c:major:minor|all:[r|w|rw|none]
> Give the container an access to a block or character
> device
> designated by its major and minor numbers. Device file have to be
> created
> manually.

> ----- Original Message -----

> From: Daniel Bauer <mlist@dsb-gmbh.de>

> To: users@openvz.org

> Sent: Tue, May 31, 2011 4:10:11 AM

> Subject: [Users] OpenVZ Container with a PCI ISDN Card

>

> Hello,

>

> I'm new to OpenVZ and wonder if it's possible to run an asterisk

> inside a

> container and give him full access to a digium B410 ISDN Card.

>

> Thanks a lot for any hint

> Daniel