
Subject: Right use of Hostname and Name

Posted by [Sebastian Bachmann](#) on Sun, 03 Jul 2011 11:26:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

-----BEGIN PGP SIGNED MESSAGE-----

Hash: SHA1

Hello,

We have some servers with some more OpenVZs installed. All running Debian lenny, squeeze and lenny bpo.

Now we have some troubles with the Hostname and FQDN of some VZ's. In the config files of all VZs is the HOSTNAME set to the FQDN. The NAME is set to the Hostname of the host.

In some hosts we can now see, that /etc/hostname is the FQDN, in some not. In the VZ's where in the /etc/hostname is the hostname, \$(hostname -f) gives the FQDN... So i think some hosts have some problems with the hostname and the real FQDN...

So what is the right usage of HOSTNAME and NAME in the VZ conf? where i should use the FQDN and where just the hostname?

thanks!

sebastian

-----BEGIN PGP SIGNATURE-----

Version: GnuPG/MacGPG2 v2.0.14 (Darwin)

Comment: Using GnuPG with Mozilla - <http://enigmail.mozdev.org/>

iQEcBAEBAGAGBQJOEFHpAAoJEAhgHfPCcybQg8H/jQIz7280XJXSRgg5jma RWaT
1DDPtW2A2fc9P1FedtEyKAU37zR8PwuWdyBNA1CQGqY6Wvi+oCGY0zqhTl8+7 Q+F3
qbbXVINtrXGFY115hO9O1/IXt/R0zDF22APbVeyvFNRKHS6IFLDHSAp39Y34 fuXa
FbqyVfDyq+dnmm+MBVi8pIHxXOMMPJ+x5pbYsOufHJDrdDVCEu6FuUaOf4vn dFuo
NQuwq7bfoza18nBND8VksbCwD8iHLCW8p4vWhbQlmwvPGwF8baVCP9IABL9L zdcN
oABN9SH5IIPRRmtzzWeYG+14d42pE8WI7DahOAvu6duNcKMhWHrdSBbCK7+O G/s=
=h403

-----END PGP SIGNATURE-----

Subject: Re: Right use of Hostname and Name

Posted by [dowdle](#) on Tue, 05 Jul 2011 18:54:02 GMT

[View Forum Message](#) <> [Reply to Message](#)

Greetings,

----- Original Message -----

> So what is the right usage of HOSTNAME and NAME in the VZ conf? where i
> should use the FQDN and where just the hostname?

vzctl's --name flag is just for vzctl so you can use a name rather than the ctid... just like hostnames

are generally friendlier than IP addresses. It is really just a symlink in /etc/vz/names/ that points to the config. To the best of my knowledge, only vzctl allows you to use it... whereas, for example, vzmigrate does not.

The --hostname flag is for setting the hostname of the container. Where the value gets written into the container is distro specific. For example, in Red Hat / Fedora OS Templates, the value gets written to /etc/sysconfig/network. Other distros might expect it to be elsewhere.

The man page for vzctl is a little lean in the descriptions for --name and --hostname but I think it is clear enough.

TYL,

--

Scott Dowdle
704 Church Street
Belgrade, MT 59714
(406)388-0827 [home]
(406)994-3931 [work]
