
Subject: Re: Network Routing Question

Posted by [mperkel](#) on Tue, 06 Mar 2007 09:10:33 GMT

[View Forum Message](#) <> [Reply to Message](#)

Thanks for the quick response. I figured I'd have to create a route-eth0 file or something.

ip ro ls

```
69.50.231.4 dev venet0 scope link
69.50.231.240 dev venet0 scope link
69.50.231.7 dev venet0 scope link
69.50.231.3 dev venet0 scope link
69.50.231.8 dev venet0 scope link
69.50.231.0/28 dev eth0 proto kernel scope link src 69.50.231.13
69.50.231.128/26 dev eth0 proto kernel scope link src 69.50.231.131
169.254.0.0/16 dev eth0 scope link
default via 69.50.231.129 dev eth0 src 69.50.231.131
default via 69.50.231.1 dev eth0
```

ip a ls

```
2: lo: <LOOPBACK,UP,LOWER_UP> mtu 16436 qdisc noqueue
    link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
    inet 127.0.0.1/8 scope host lo
    inet6 ::1/128 scope host
        valid_lft forever preferred_lft forever
4: sit0: <NOARP> mtu 1480 qdisc noop
    link/sit 0.0.0.0 brd 0.0.0.0
6: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast qlen 1000
    link/ether 00:18:f3:b3:cc:50 brd ff:ff:ff:ff:ff:ff
    inet 69.50.231.13/28 brd 69.50.231.15 scope global eth0
    inet 69.50.231.131/26 brd 69.50.231.191 scope global eth0:1
    inet6 fe80::218:f3ff:feb3:cc50/64 scope link
        valid_lft forever preferred_lft forever
3: venet0: <BROADCAST,POINTOPOINT,NOARP,UP,LOWER_UP> mtu 1500 qdisc noqueue
    link/void
```