Subject: [PATCH] Protect tty drivers list a little
Posted by Alexey Dobriyan on Thu, 22 Mar 2007 11:18:03 GMT
View Forum Message <> Reply to Message

Additions and removal from tty_drivers list were just done as well as
iterating on it for /proc/tty/drivers generation.

testing: modprobe/rmmod loop of simple module which does nothing but
tty_register_driver() vs cat /proc/tty/drivers loop

BUG: unable to handle kernel paging request at virtual address 6b6b6b6b
 printing eip:
c01cefa7
*pde = 00000000
Oops: 0000 [#1]
PREEMPT
last sysfs file: devices/pci0000:00/0000:00:1d.7/usb5/5-0:1.0/bInterfaceProto col
Modules linked in: ohci_hcd af_packet e1000 ehci_hcd uhci_hcd usbcore xfs
CPU: 0
EIP: 0060:[<c01cefa7>]   Not tainted VLI
EFLAGS: 00010297   (2.6.21-rc4-mm1 #4)
EIP is at vsnprintf+0x3a4/0x5fc
eax: 6b6b6b6b   ebx: f6cb50f2   ecx: 6b6b6b6b   edx: fffffffe
esi: c0354700   edi: f6cb6000   ebp: 6b6b6b6b   esp: f31f5e68
ds: 007b   es: 007b   fs: 00d8 gs: 0033 ss: 0068
Process cat (pid: 31864, ti=f31f4000 task=c1998030 task.ti=f31f4000)
Stack: 00000000 c0103f20 c013003a c0103f20 00000000 f6cb50da 0000000a 00000f0e
       f6cb50f2 00000010 00000014 ffffffff ffffffff 00000007 c0354753 f6cb50f2
       f73e39dc f73e39dc 00000001 c0175416 f31f5ed8 f31f5ed4 0ee00000 f32090bc
Call Trace:
 [<c0103f20>] restore_nocheck+0x12/0x15
 [<c013003a>] mark_held_locks+0x6d/0x86
 [<c0103f20>] restore_nocheck+0x12/0x15
 [<c0175416>] seq_printf+0x2e/0x52
 [<c0192895>] show_tty_range+0x35/0x1f3
 [<c0175416>] seq_printf+0x2e/0x52
 [<c0192add>] show_tty_driver+0x8a/0x1d9
 [<c01758f6>] seq_read+0x70/0x2ba
 [<c0175886>] seq_read+0x0/0x2ba
 [<c018d8e6>] proc_reg_read+0x63/0x9f
 [<c015e764>] vfs_read+0x7d/0xb5
 [<c018d883>] proc_reg_read+0x0/0x9f
 [<c015eab1>] sys_read+0x41/0x6a
 [<c0103e4e>] sysenter_past_esp+0x5f/0x99
 =======================
Code: 00 8b 4d 04 e9 44 ff ff ff 8d 4d 04 89 4c 24 50 8b 6d 00 81 fd ff 0f 00 00 b8 a4 c1 35 c0 0f
46 e8 8b 54 24 2c 89 e9 89 c8 eb 06 <80> 38 00 74 07 40 4a 83 fa ff 75 f4 29 c8 89 c6 8b 44 24
28 89

```
EIP: [<c01cefa7>] vsnprintf+0x3a4/0x5fc SS:ESP 0068:f31f5e68

Signed-off-by: Alexey Dobriyan <adobriyan@sw.ru>
---

 drivers/char/tty_io.c      |    9 ++++++++-
 fs/proc/proc_tty.c         |    3 +++
 include/linux/tty_driver.h |    2 ++
 3 files changed, 13 insertions(+), 1 deletion(-)

--- a/drivers/char/tty_io.c
+++ b/drivers/char/tty_io.c
@@ -127,6 +127,7 @@ EXPORT_SYMBOL(tty_std_termios);
    into this file */

 LIST_HEAD(tty_drivers);   /* linked list of tty drivers */
+DEFINE_SPINLOCK(tty_drivers_lock);

 /* Mutex to protect creating and releasing a tty. This is shared with
    vt.c for deeply disgusting hack reasons */
@@ -1086,13 +1087,16 @@ static struct tty_driver *get_tty_driver
 {
  struct tty_driver *p;

+ spin_lock(&tty_drivers_lock);
  list_for_each_entry(p, &tty_drivers, tty_drivers) {
   dev_t base = MKDEV(p->major, p->minor_start);
   if (device < base || device >= base + p->num)
    continue;
+  spin_unlock(&tty_drivers_lock);
   *index = device - base;
   return p;
  }
+ spin_unlock(&tty_drivers_lock);
  return NULL;
 }

@@ -3767,7 +3771,9 @@ int tty_register_driver(struct tty_drive
  if (!driver->put_char)
   driver->put_char = tty_default_put_char;

+ spin_lock(&tty_drivers_lock);
  list_add(&driver->tty_drivers, &tty_drivers);
+ spin_unlock(&tty_drivers_lock);

  if ( !(driver->flags & TTY_DRIVER_DYNAMIC_DEV) ) {
   for(i = 0; i < driver->num; i++)
@@ -3793,8 +3799,9 @@ int tty_unregister_driver(struct tty_dri
```

```
  unregister_chrdev_region(MKDEV(driver->major, driver->minor_start),
     driver->num);
-
+ spin_lock(&tty_drivers_lock);
  list_del(&driver->tty_drivers);
+ spin_unlock(&tty_drivers_lock);

  /*
   * Free the termios and termios_locked structures because
--- a/fs/proc/proc_tty.c
+++ b/fs/proc/proc_tty.c
@@ -108,6 +108,8 @@ static void *t_start(struct seq_file *m,
 {
  struct list_head *p;
  loff_t l = *pos;
+
+ spin_lock(&tty_drivers_lock);
  list_for_each(p, &tty_drivers)
   if (!l--)
    return list_entry(p, struct tty_driver, tty_drivers);
@@ -124,6 +126,7 @@ static void *t_next(struct seq_file *m,

 static void t_stop(struct seq_file *m, void *v)
 {
+ spin_unlock(&tty_drivers_lock);
 }

 static struct seq_operations tty_drivers_op = {
--- a/include/linux/tty_driver.h
+++ b/include/linux/tty_driver.h
@@ -118,6 +118,7 @@ #define _LINUX_TTY_DRIVER_H
 #include <linux/fs.h>
 #include <linux/list.h>
 #include <linux/cdev.h>
+#include <linux/spinlock.h>

 struct tty_struct;

@@ -216,6 +217,7 @@ struct tty_driver {
 };

 extern struct list_head tty_drivers;
+extern spinlock_t tty_drivers_lock;

 struct tty_driver *alloc_tty_driver(int lines);
 void put_tty_driver(struct tty_driver *driver);
```