
Subject: Re: [LTP] LTP: serge2 hostname
Posted by [Subrata Modak1](#) on Thu, 24 May 2007 07:08:26 GMT
[View Forum Message](#) <> [Reply to Message](#)

Taken Care.

Regards & Thanks--
Subrata Modak,

=====
=====

"Serge E. Hallyn"
<serue@us.ibm.com>
> To
Sent by: Alexey Dobriyan <adobriyan@sw.ru>
ltp-list-bounces@lists.sourceforge.net cc
ltp-list@lists.sourceforge.net,
.net devel@openvz.org
Subject
Re: [LTP] LTP: serge2 hostname
05/23/07 08:19 PM

Quoting Alexey Dobriyan (adobriyan@sw.ru):
> I ran ltp-full-20070430 and utstest.c forgot to restore original
> hostname from serge2. ;-)

Oh that's just me taking over the world, one workstation at a time.

Hopefully this simple obvious silly workaround fixes it?

It should also fix 'make no_ltp' which I hadn't realized was broken
until I just tried to test the hostname fix...

thanks for spotting that.

-serge

```

Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone:
libcclone.a
Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/libc lone:
libcclone.o
diff -ur ltp-full-20070430/testcases/kernel/containers/utsname/Makefile
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/Makefile
--- ltp-full-20070430/testcases/kernel/containers/utsname/Makefile
2007-04-26 13:02:51.000000000 +0200
+++
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/Makefile
2007-05-23 16:48:26.000000000 +0200
@@ -4,8 +4,9 @@
LDLIBS += -L../lib -L../libclone ../libclone/libclone.a -lltp

SRCS = $(wildcard *.c)
+NOLTPSRCS = utstest.c
TARGETS = $(patsubst %.c,%,$(SRCS))
-NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(SRCS))
+NOLTP_TARGETS = $(patsubst %.c,%_noltp,$(NOLTPSRCS))

%_noltp : %.c
$(CC) -g -DNO_LTP -o $@ $< ../libclone/libclone.a
diff -ur
ltp-full-20070430/testcases/kernel/containers/utsname/runtests_noltp.sh
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runtests_noltp.sh
--- ltp-full-20070430/testcases/kernel/containers/utsname/runtests_noltp.sh
2007-04-26 13:02:51.000000000 +0200
+++
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runtests_noltp.sh
2007-05-23 16:44:32.000000000 +0200
@@ -1,5 +1,6 @@
#!/bin/sh

+oldhostname=`hostname`
+exit_code=0
+echo "unshare tests"
+for i in `seq 1 5`; do
@@ -17,4 +18,5 @@
        exit_code=$?
    fi
done
+hostname "$oldhostname"
+exit $exit_code
diff -ur
ltp-full-20070430/testcases/kernel/containers/utsname/runutstest.sh
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runutstest.sh

```

```
--- ltp-full-20070430/testcases/kernel/containers/utsname/runuts test.sh
2007-04-26 13:02:51.000000000 +0200
+++
ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname/runutstest.sh
2007-05-23 16:44:37.000000000 +0200
@@ -1,5 +1,6 @@
#!/bin/sh

+oldhostname=`hostname`
echo "unshare tests"
for i in `seq 1 5`; do
    echo "test $i (unshare)"
@@ -10,3 +11,4 @@
    echo "test $i (clone)"
    utstest clone $i
done
+hostname "$oldhostname"
Only in ltp-full-20070430-fixserge2/testcases/kernel/containers/utsname:
utstest_noltp
```

This SF.net email is sponsored by DB2 Express
Download DB2 Express C - the FREE version of DB2 express and take
control of your XML. No limits. Just data. Click to get it now.
<http://sourceforge.net/powerbar/db2/>

Ltp-list mailing list
Ltp-list@lists.sourceforge.net
<https://lists.sourceforge.net/lists/listinfo/ltp-list>
