

---

Subject: Re: [PATCH] pci\_get\_device call from interrupt in reboot fixups  
Posted by [den](#) on Tue, 07 Aug 2007 07:49:52 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Greg KH wrote:

> On Tue, Aug 07, 2007 at 12:44:55AM -0700, Andrew Morton wrote:

>> On Tue, 7 Aug 2007 00:24:37 -0700 Andrew Morton <akpm@linux-foundation.org> wrote:  
>>

>>>> Andrew, I really don't want to change the PCI core to handle this, as we  
>>>> finally fixed a lot of issues with drivers trying to walk these lists  
>>>> from interrupt context. So if you want to just hide the warning message  
>>>> as we are shutting down, that's fine with me. Or just don't do the  
>>>> fixups. But grabbing a reference to the pci device is unsafe in my  
>>>> opinion and I do not want to do that.

>>>>

>>> OK, good decision ;)

>>>

>>> One approach would be for some brave soul to pick his way through  
>>> the reboot code and ensure that we are correctly and reliably setting  
>>> system\_state to SYSTEM\_RESTART, then test that in \_\_might\_sleep().  
>>>

>>> But this does suppress somewhat-useful debugging just because of sysrq-B  
>>> and I really wouldn't want to utilise the horrid system\_state any more that  
>>> we are presently doing. I think on balance that it would be better if we  
>>> could do something more targetted, like modify emergency\_restart() to test  
>>> in\_interrupt() and to then apologetically set some well-named global flag  
>>> which will shut up \_\_might\_sleep(). Pretty foul, but I can't think of  
>>> anything better.

>> ok, this might be better. How about we just stop calling mach\_reboot\_fixups()  
>> at sysrq-B time?

>

> Fine with me, but what hardware will be messed up because of this?

```
static struct device_fixup fixups_table[] = {  
> > { PCI_VENDOR_ID_CYRIX, PCI_DEVICE_ID_CYRIX_5530_LEGACY,  
> > cs5530a_warm_reset },  
> > { PCI_VENDOR_ID_AMD, PCI_DEVICE_ID_AMD_CS5536_ISA, cs5536_warm_reset },  
> > };
```

---