
Subject: [PATCH 20/20] Remove the struct pid unneeded fields
Posted by [Pavel Emelianov](#) on Tue, 07 Aug 2007 09:30:14 GMT
[View Forum Message](#) <> [Reply to Message](#)

Since we've switched from using pid->nr to pid->upids->nr some fields on struct pid are no longer needed

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
include/linux/init_task.h | 3 ---
include/linux/pid.h       | 3 ---
kernel/pid.c              | 1 -
3 files changed, 7 deletions(-)
```

```
--- ./include/linux/init_task.h.ve17 2007-08-06 14:14:02.000000000 +0400
+++ ./include/linux/init_task.h 2007-08-06 14:14:02.000000000 +0400
@@ -93,9 +93,6 @@ extern struct group_info init_groups;
```

```
#define INIT_STRUCT_PID { \
    .count = ATOMIC_INIT(1), \
-   .nr = 0, \
-   /* Don't put this struct pid in pid_hash */ \
-   .pid_chain = { .next = NULL, .pprev = NULL }, \
-   .tasks = { \
-       { .first = &init_task.pids[PIDTYPE_PID].node }, \
-       { .first = &init_task.pids[PIDTYPE_PGID].node }, \
--- ./include/linux/pid.h.ve17 2007-08-06 14:14:02.000000000 +0400
+++ ./include/linux/pid.h 2007-08-06 14:14:02.000000000 +0400
@@ -57,9 +57,6 @@ struct upid {
struct pid
{
    atomic_t count;
-   /* Try to keep pid_chain in the same cacheline as nr for find_pid */
-   int nr;
-   struct hlist_node pid_chain;
    /* lists of tasks that use this pid */
    struct hlist_head tasks[PIDTYPE_MAX];
    struct rcu_head rcu;
--- ./kernel/pid.c.ve17 2007-08-06 14:14:02.000000000 +0400
+++ ./kernel/pid.c 2007-08-06 14:14:18.000000000 +0400
@@ -259,7 +259,6 @@ struct pid *alloc_pid(struct pid_namespace
```

```
    get_pid_ns(ns);
    pid->level = ns->level;
-   pid->nr = pid->numbers[0].nr;
    atomic_set(&pid->count, 1);
```

```
for (type = 0; type < PIDTYPE_MAX; ++type)
    INIT_HLIST_HEAD(&pid->tasks[type]);
```
