
Subject: [PATCH] Fix check for return value of create_pid_namespace

Posted by [Pavel Emelianov](#) on Fri, 17 Aug 2007 09:25:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

The function in question returns ERR_PTR-s to indicate the error, while the caller checks for return value to be NULL.

Found during testing the OpenVZ kernel with pid namespaces.

Signed-off-by: Pavel Emelianov <xemul@openvz.org>

Signed-off-by: Alexey Dobriyan <adobriyan@openvz.org>

Cc: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Cc: Oleg Nesterov <oleg@tv-sign.ru>

kernel/pid.c | 2 +-
1 files changed, 1 insertion(+), 1 deletion(-)

diff --git a/kernel/pid.c b/kernel/pid.c

index faad017..cb1f3cb 100644

--- a/kernel/pid.c

+++ b/kernel/pid.c

@@ -543,7 +543,7 @@ struct pid_namespace *copy_pid_ns(unsigned
goto out_put;

new_ns = create_pid_namespace(old_ns->level + 1);

- if (new_ns != NULL)

+ if (!IS_ERR(new_ns))

new_ns->parent = get_pid_ns(old_ns);

out_put:
