
Subject: Re: Network virtualization/isolation

Posted by [Brian Haley](#) on Wed, 29 Nov 2006 20:21:00 GMT

[View Forum Message](#) <> [Reply to Message](#)

Eric W. Biederman wrote:

> I think for cases across network socket namespaces it should
> be a matter for the rules, to decide if the connection should
> happen and what error code to return if the connection does not
> happen.
>
> There is a potential in this to have an ambiguous case where two
> applications can be listening for connections on the same socket
> on the same port and both will allow the connection. If that
> is the case I believe the proper definition is the first socket
> that we find that will accept the connection gets the connection.

Wouldn't you want to catch this at bind() and/or configuration time and fail? Having overlapping namespaces/rules seems undesirable, since as Herbert said, can get you "unexpected behaviour".

> I think with the appropriate set of rules it provides what is needed
> for application migration. I.e. 127.0.0.1 can be filtered so that
> you can only connect to sockets in your current container.
>
> It does get a little odd because it does allow for the possibility
> that you can have multiple connected sockets with same source ip,
> source port, destination ip, destination port. If the rules are
> setup appropriately. I don't see that peculiarity being visible on
> the outside network so it shouldn't be a problem.

So if they're using the same protocol (eg TCP), how is it decided which one gets an incoming packet? Maybe I'm missing something as I don't understand your inside/outside network reference - is that to the loopback address comment in the previous paragraph?

Thanks,

-Brian

Containers mailing list

Containers@lists.osdl.org

<https://lists.osdl.org/mailman/listinfo/containers>
