

---

Subject: [PATCH 21/25] do\_rmdir(): elevate write count  
Posted by [Dave Hansen](#) on Mon, 11 Dec 2006 22:30:17 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Elevate the write count during the vfs\_rmdir() call.

Signed-off-by: Dave Hansen <haveblue@us.ibm.com>

---

lxc-dave/fs/namei.c | 5 +++++  
1 file changed, 5 insertions(+)

```
diff -puN fs/namei.c~20-24-do-rmdir-elevate-write-count fs/namei.c
--- lxc/fs/namei.c~20-24-do-rmdir-elevate-write-count 2006-12-11 14:22:10.000000000 -0800
+++ lxc-dave/fs/namei.c 2006-12-11 14:22:10.000000000 -0800
@@ -2097,7 +2097,12 @@ static long do_rmdir(int dfd, const char
     error = PTR_ERR(dentry);
     if (IS_ERR(dentry))
         goto exit2;
+ error = mnt_want_write(nd.mnt);
+ if (error)
+     goto exit3;
     error = vfs_rmdir(nd.dentry->d_inode, dentry);
+ mnt_drop_write(nd.mnt);
+exit3:
     dput(dentry);
 exit2:
     mutex_unlock(&nd.dentry->d_inode->i_mutex);
```

—

---

Containers mailing list  
Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---