
Subject: Re: [patch 12/12] net namespace : Add broadcasting
Posted by [Herbert Poetzl](#) on Sat, 20 Jan 2007 04:58:37 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Fri, Jan 19, 2007 at 04:47:26PM +0100, dlezcano@fr.ibm.com wrote:

> From: Daniel Lezcano <dlezcano@fr.ibm.com>

>

> Broadcast packets should be delivered to I2 and all I3 childs

hmm, really? shouldn't it only reach those which
actually have related addresses assigned?

best,
Herbert

> Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

>

> ---

> include/linux/net_namespace.h | 11 ++++++++

> net/core/net_namespace.c | 27 ++++++

> net/ipv4/udp.c | 3 ++

> 3 files changed, 40 insertions(+), 1 deletion(-)

>

> Index: 2.6.20-rc4-mm1/include/linux/net_namespace.h

> =====

> --- 2.6.20-rc4-mm1.orig/include/linux/net_namespace.h

> +++ 2.6.20-rc4-mm1/include/linux/net_namespace.h

> @@ -9,6 +9,7 @@

>

> struct in_ifaddr;

> struct sk_buff;

> +struct sock;

>

> struct net_namespace {

> struct kref kref;

> @@ -109,6 +110,9 @@

>

> extern void net_ns_tag_sk_buff(struct sk_buff *skb);

>

> +extern int net_ns_sock_is_visible(const struct sock *sk,

> + const struct net_namespace *net_ns);

> +

> #define SELECT_SRC_ADDR net_ns_select_source_address

>

> #else /* CONFIG_NET_NS */

> @@ -192,6 +196,13 @@

> {

> ;

```

> }
> +
> +static inline int net_ns_sock_is_visible(const struct sock *sk,
> +    const struct net_namespace *net_ns)
> +{
> +    return 1;
> +}
> +
> #define SELECT_SRC_ADDR inet_select_addr
>
> #endif /* !CONFIG_NET_NS */
> Index: 2.6.20-rc4-mm1/net/core/net_namespace.c
> =====
> --- 2.6.20-rc4-mm1.orig/net/core/net_namespace.c
> +++ 2.6.20-rc4-mm1/net/core/net_namespace.c
> @@ -17,6 +17,7 @@
> #include <linux/ip.h>
>
> #include <net/ip_fib.h>
> +#include <net/sock.h>
>
> struct net_namespace init_net_ns = {
>     .kref = {
> @@ -464,4 +465,30 @@
>     struct net_namespace *net_ns = current_net_ns;
>     skb->net_ns = net_ns;
> }
> +
> +/*
> + * This function checks if the socket is visible from the specified
> + * namespace. This is needed to ensure the broadcast and the multicast
> + * for multiple network namespace l2 and l3 to have the packets to be
> + * delivered. If we have a l3 namespace and its parent (l2 namespace)
> + * listening on a broadcast address, we should deliver the packet to
> + * both. That is done by the udp_v4_mcast_next function. But we should
> + * find a common point between sockets which are relatives to a
> + * namespace. The common point is they have the same parent in case
> + * of l3 network namespace.
> + * @sk : the socket to be checked
> + * @net_ns : the receiving network namespace
> + * Returns: 1 if the socket is visible by the namespace, 0 otherwise.
> + */
> +int net_ns_sock_is_visible(const struct sock *sk,
> +    const struct net_namespace *net_ns)
> +{
> +    if (net_ns->level == NET_NS_LEVEL3)
> +        net_ns = net_ns->parent;
> +

```

```

> + if (sk->sk_net_ns->level == NET_NS_LEVEL3)
> + return sk->sk_net_ns->parent == net_ns;
> + else
> + return sk->sk_net_ns == net_ns;
> +}
> #endif /* CONFIG_NET_NS */
> Index: 2.6.20-rc4-mm1/net/ipv4/udp.c
> =====
> --- 2.6.20-rc4-mm1.orig/net/ipv4/udp.c
> +++ 2.6.20-rc4-mm1/net/ipv4/udp.c
> @@ -309,9 +309,10 @@
>     (inet->dport != rmt_port && inet->dport) ||
>     (inet->rcv_saddr && inet->rcv_saddr != loc_addr) ||
>     ipv6_only_sock(s)    ||
> - !net_ns_match(sk->sk_net_ns, ns) ||
>     (s->sk_bound_dev_if && s->sk_bound_dev_if != dif))
>     continue;
> + if (!net_ns_sock_is_visible(sk, ns))
> + continue;
>     if (!ip_mc_sf_allow(s, loc_addr, rmt_addr, dif))
>         continue;
>     goto found;
>
> --
>
> _____
> Containers mailing list
> Containers@lists.osdl.org
> https://lists.osdl.org/mailman/listinfo/containers

```

Containers mailing list
Containers@lists.osdl.org
<https://lists.osdl.org/mailman/listinfo/containers>
