

---

Subject: [patch 1/2] net namespace : assign IP address to specified nsproxy child  
Posted by [Daniel Lezcano](#) on Fri, 26 Jan 2007 09:52:49 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

From: Daniel Lezcano <dlezcano@fr.ibm.com>

All IP configuration is done into the L2 namespace. The L3 namespace gains visibility to an IP address when this one is assigned from the L2 parent's namespace to the L3 child.  
In order to be able to find a L3 child, the namespace identifier should be used to retrieve the namespace.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

---

net/core/net\_namespace.c | 24 ++++++-----  
1 file changed, 18 insertions(+), 6 deletions(-)

Index: 2.6.20-rc4-mm1/net/core/net\_namespace.c

=====

--- 2.6.20-rc4-mm1.orig/net/core/net\_namespace.c

+++ 2.6.20-rc4-mm1/net/core/net\_namespace.c

@ @ -15,6 +15,7 @ @

#include <linux/inetdevice.h>

#include <linux/skbuff.h>

#include <linux/ip.h>

+#include <linux/capability.h>

#include <net/ip\_fib.h>

#include <net/sock.h>

@ @ -57,8 +58,8 @ @

kref\_init(&ns->kref);  
if ((push\_net\_ns(ns)) != old\_ns)

-

BUG();

+

if (level == NET\_NS\_LEVEL2) {  
ns->dev\_base\_p = NULL;  
ns->dev\_tail\_p = &ns->dev\_base\_p;

@ @ -200,25 +201,36 @ @

{

struct ifreq ifr;  
struct sockaddr\_in \*sin = (struct sockaddr\_in \*)&ifr.ifr\_addr;

- struct net\_namespace \*net\_ns = current\_net\_ns;

+ struct net\_namespace \*net\_ns;

+ struct nsproxy \*nsproxy;

struct net\_device \*dev;

struct in\_device \*in\_dev;

```

    struct in_ifaddr **ifap = NULL;
    struct in_ifaddr *ifa = NULL;
    char *colon;
-   int err;
+   int err, id = 0;

    if (!capable(CAP_NET_ADMIN))
        return -EPERM;

-   if (net_ns->level != NET_NS_LEVEL3)
-   return -EPERM;
-
    if (copy_from_user(&ifr, arg, sizeof(struct ifreq)))
        return -EFAULT;

    ifr.ifr_name[IFNAMSIZ - 1] = 0;
+   id = sin->sin_port;

+   nsproxy = find_nsproxy_by_id(id);
+   if (!nsproxy)
+   return -ESRCH;
+
+   net_ns = nsproxy->net_ns;
+   put_nsproxy(nsproxy);
+
+   if (net_ns->parent != current_net_ns)
+   return -EPERM;
+
+   if (net_ns->level != NET_NS_LEVEL3)
+   return -EINVAL;

    colon = strchr(ifr.ifr_name, ':');
    if (colon)

--

```

---

Containers mailing list  
Containers@lists.osdl.org  
<https://lists.osdl.org/mailman/listinfo/containers>

---