Subject: [RFC][PATCH 2/2] introduce proc_mnt for pid_ns
Posted by Dave Hansen on Tue, 20 Feb 2007 19:00:56 GMT
View Forum Message <> Reply to Message

The following patch completes the removal of the global proc_mnt.
It fetches the mnt on which to do dentry invalidations from the
pid_namespace in which the task appears.

For now, there is only one pid namespace in mainline so this is
straightforward. In the -lxc tree we'll have to do something
more complex.

Note that the new proc_compare_super() enforces the "one proc sb
per pid_namespace" limit.

/proc currently has some special code to make sure that the root
directory gets set up correctly. It proc_mnt variable in order
to find its way to the root inode.

Now that we don't have the global proc_mnt, we can fill in the
root inode's data in proc_fill_super(), where it takes a wee bit
less work than in proc_get_sb().

Signed-off-by: Dave Hansen <haveblue@us.ibm.com>

```
 lxc-dave/fs/proc/base.c              |   32 ++++++++++++++++++++++-
 lxc-dave/fs/proc/inode.c             |   10 +++++--
 lxc-dave/fs/proc/root.c              |   46 ++++++++++++++++++++++----------
 lxc-dave/include/linux/pid_namespace.h |    1
 lxc-dave/include/linux/proc_fs.h     |    1
 5 files changed, 67 insertions(+), 23 deletions(-)

diff -puN fs/proc/base.c~A3-remove-proc_mnt-1 fs/proc/base.c
--- lxc/fs/proc/base.c~A3-remove-proc_mnt-1 2007-02-20 10:07:28.000000000 -0800
+++ lxc-dave/fs/proc/base.c 2007-02-20 10:07:29.000000000 -0800
@@ -71,6 +71,7 @@
 #include <linux/seccomp.h>
 #include <linux/cpuset.h>
 #include <linux/audit.h>
+#include <linux/pid_namespace.h>
 #include <linux/poll.h>
 #include <linux/nsproxy.h>
 #include <linux/oom.h>
@@ -2001,9 +2002,11 @@ static const struct inode_operations pro
 };

 /**
```

```
- * proc_flush_task -  Remove dcache entries for @task from the /proc dcache.
+ * proc_flush_task_from_pid_ns -  Remove dcache entries for @task
+ *       from the /proc dcache.
  *
  * @task: task that should be flushed.
+ * @pid_ns: pid_namespace in which that task appears
  *
  * Looks in the dcache for
  * /proc/@pid
@@ -2021,11 +2024,23 @@ static const struct inode_operations pro
  *       that no dcache entries will exist at process exit time it
  *       just makes it very unlikely that any will persist.
  */
-void proc_flush_task(struct task_struct *task)
+void proc_flush_task_from_pid_ns(struct task_struct *task,
+    struct pid_namespace* pid_ns)
 {
  struct dentry *dentry, *leader, *dir;
  char buf[PROC_NUMBUF];
  struct qstr name;
+ struct vfsmount *proc_mnt;
+
+ /*
+  * It is possible that no /procs have been instantiated
+  * for this particular pid namespace, or that we're trying
+  * to flush for a task without a pid_ns, like a kernel
+  * thread.
+  */
+ if (!pid_ns || !pid_ns->proc_mnt)
+  return;
+ proc_mnt = pid_ns->proc_mnt;

  name.name = buf;
  name.len = snprintf(buf, sizeof(buf), "%d", task->pid);
@@ -2067,6 +2082,19 @@ out:
  return;
 }

+void proc_flush_task(struct task_struct *task)
+{
+ struct pid_namespace *pid_ns = NULL;
+ /*
+  * Right now, tasks only appear in their own pid_ns.
+  * With containers this function will change to a loop
+  * over all pid_ns's in which the task appears.
+  */
+ if (task->nsproxy)
+  pid_ns = task->nsproxy->pid_ns;
```

```
+ proc_flush_task_from_pid_ns(task, pid_ns);
+}
+
 static struct dentry *proc_pid_instantiate(struct inode *dir,
        struct dentry * dentry,
        struct task_struct *task, void *ptr)
diff -puN fs/proc/inode.c~A3-remove-proc_mnt-1 fs/proc/inode.c
--- lxc/fs/proc/inode.c~A3-remove-proc_mnt-1 2007-02-20 10:07:28.000000000 -0800
+++ lxc-dave/fs/proc/inode.c 2007-02-20 10:07:29.000000000 -0800
@@ -67,8 +67,6 @@ static void proc_delete_inode(struct ino
  clear_inode(inode);
 }

-struct vfsmount *proc_mnt;
-
 static void proc_read_inode(struct inode * inode)
 {
  inode->i_mtime = inode->i_atime = inode->i_ctime = CURRENT_TIME;
@@ -184,6 +182,8 @@ out_mod:

 int proc_fill_super(struct super_block *s, void *data, int silent)
 {
+ struct pid_namespace *pid_ns = data;
+ struct proc_inode *ei;
  struct inode * root_inode;

  s->s_flags |= MS_NODIRATIME | MS_NOSUID | MS_NOEXEC;
@@ -192,6 +192,7 @@ int proc_fill_super(struct super_block *
  s->s_magic = PROC_SUPER_MAGIC;
  s->s_op = &proc_sops;
  s->s_time_gran = 1;
+ s->s_fs_info = pid_ns;

  root_inode = proc_get_inode(s, PROC_ROOT_INO, &proc_root);
  if (!root_inode)
@@ -201,6 +202,11 @@ int proc_fill_super(struct super_block *
  s->s_root = d_alloc_root(root_inode);
  if (!s->s_root)
   goto out_no_root;
+ /* Seed the root directory with a pid so it doesn't need
+  * to be special in base.c.
+  */
+ ei = PROC_I(root_inode);
+ ei->pid = find_get_pid(1);
  return 0;

 out_no_root:
diff -puN fs/proc/root.c~A3-remove-proc_mnt-1 fs/proc/root.c
```

```
--- lxc/fs/proc/root.c~A3-remove-proc_mnt-1 2007-02-20 10:07:28.000000000 -0800
+++ lxc-dave/fs/proc/root.c 2007-02-20 10:07:29.000000000 -0800
@@ -18,26 +18,42 @@
 #include <linux/bitops.h>
 #include <linux/smp_lock.h>
 #include <linux/mount.h>
+#include <linux/pid_namespace.h>

 #include "internal.h"

 struct proc_dir_entry *proc_net, *proc_net_stat, *proc_bus, *proc_root_fs, *proc_root_driver;

+static int proc_test_sb(struct super_block *s, void *data)
+{
+ struct pid_namespace *pid_ns = data;
+ if (s->s_fs_info == pid_ns)
+  return 1;
+ return 0;
+}
+
+static int proc_set_sb(struct super_block *s, void *data)
+{
+ int ret;
+ ret = set_anon_super(s, NULL);
+ if (!ret)
+  ret = proc_fill_super(s, data, 0);
+ return ret;
+}
+
 static int proc_get_sb(struct file_system_type *fs_type,
  int flags, const char *dev_name, void *data, struct vfsmount *mnt)
 {
- if (proc_mnt) {
-  /* Seed the root directory with a pid so it doesn't need
-   * to be special in base.c.  I would do this earlier but
-   * the only task alive when /proc is mounted the first time
-   * is the init_task and it doesn't have any pids.
-   */
-  struct proc_inode *ei;
-  ei = PROC_I(proc_mnt->mnt_sb->s_root->d_inode);
-  if (!ei->pid)
-   ei->pid = find_get_pid(1);
- }
- return get_sb_single(fs_type, flags, data, proc_fill_super, mnt);
+ struct super_block *s;
+
+ s = sget(fs_type, proc_test_sb, proc_set_sb, current->nsproxy->pid_ns);
+ if (IS_ERR(s))
```

```
+  return PTR_ERR(s);
+ if (!current->nsproxy->pid_ns->proc_mnt)
+  current->nsproxy->pid_ns->proc_mnt = mnt;
+
+ do_remount_sb(s, flags, data, 0);
+ return simple_set_mnt(mnt, s);
 }

 static struct file_system_type proc_fs_type = {
@@ -54,12 +70,6 @@ void __init proc_root_init(void)
  err = register_filesystem(&proc_fs_type);
  if (err)
   return;
- proc_mnt = kern_mount(&proc_fs_type);
- err = PTR_ERR(proc_mnt);
- if (IS_ERR(proc_mnt)) {
-  unregister_filesystem(&proc_fs_type);
-  return;
- }
  proc_misc_init();
  proc_net = proc_mkdir("net", NULL);
  proc_net_stat = proc_mkdir("net/stat", NULL);
diff -puN include/linux/pid_namespace.h~A3-remove-proc_mnt-1 include/linux/pid_namespace.h
--- lxc/include/linux/pid_namespace.h~A3-remove-proc_mnt-1 2007-02-20 10:07:28.000000000
-0800
+++ lxc-dave/include/linux/pid_namespace.h 2007-02-20 10:07:29.000000000 -0800
@@ -20,6 +20,7 @@ struct pid_namespace {
  struct pidmap pidmap[PIDMAP_ENTRIES];
  int last_pid;
  struct task_struct *child_reaper;
+ struct vfsmount *proc_mnt;
 };

 extern struct pid_namespace init_pid_ns;
diff -puN include/linux/proc_fs.h~A3-remove-proc_mnt-1 include/linux/proc_fs.h
--- lxc/include/linux/proc_fs.h~A3-remove-proc_mnt-1 2007-02-20 10:07:28.000000000 -0800
+++ lxc-dave/include/linux/proc_fs.h 2007-02-20 10:07:29.000000000 -0800
@@ -129,7 +129,6 @@ extern struct proc_dir_entry *create_pro
       struct proc_dir_entry *parent);
 extern void remove_proc_entry(const char *name, struct proc_dir_entry *parent);

-extern struct vfsmount *proc_mnt;
 extern int proc_fill_super(struct super_block *,void *,int);
 extern struct inode *proc_get_inode(struct super_block *, unsigned int, struct proc_dir_entry *);


_
_____
Containers mailing list
```