Subject: [PATCH 2/5] Explicitly set pgid and sid of init process
Posted by Sukadev Bhattiprolu on Thu, 01 Mar 2007 03:57:24 GMT
View Forum Message <> Reply to Message

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH 2/5] Explicitly set pgid and sid of init process

Explicitly set pgid and sid of init process to 1.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: Eric Biederman <ebiederm@xmission.com>
Cc: Herbert Poetzl <herbert@13thfloor.at>
Cc: <containers@lists.osdl.org>
Signed-off-by: Andrew Morton <akpm@osdl.org>
---

 init/main.c | 1 +
 1 file changed, 1 insertion(+)

Index: lx26-20-mm2c/init/main.c
===
--- lx26-20-mm2c.orig/init/main.c 2007-02-28 15:49:13.000000000 -0800
+++ lx26-20-mm2c/init/main.c 2007-02-28 15:49:35.000000000 -0800
@@ -791,6 +791,7 @@ static int __init init(void * unused)
   */
  init_pid_ns.child_reaper = current;

+ __set_special_pids(1, 1);
  cad_pid = task_pid(current);

  smp_prepare_cpus(max_cpus);

_____
Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers