Subject: [RFC][PATCH 4/6] Initialize struct pid_nr for swapper
Posted by Sukadev Bhattiprolu on Sat, 10 Mar 2007 03:59:24 GMT
View Forum Message <> Reply to Message

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [RFC][PATCH 4/6] Initialize struct pid_nr for swapper.

Statically initialize a struct pid_nr for the swapper process.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: containers@lists.osdl.org
---
 include/linux/init_task.h | 7 +++++++
 kernel/pid.c | 1 +
 2 files changed, 8 insertions(+)

Index: lx26-20-mm2b/include/linux/init_task.h
===
--- lx26-20-mm2b.orig/include/linux/init_task.h 2007-03-08 17:56:05.000000000 -0800
+++ lx26-20-mm2b/include/linux/init_task.h 2007-03-09 14:56:11.000000000 -0800
@@ -96,6 +96,12 @@ extern struct group_info init_groups;
 #define INIT_PREEMPT_RCU
 #endif

+#define INIT_STRUCT_PID_NR {   \
+ .node = { .next = NULL, .pprev = NULL }, \
+ .nr = 0,   \
+ .pid_ns = &init_pid_ns,   \
+}
+
 #define INIT_STRUCT_PID {   \
   .count   = ATOMIC_INIT(1),   \
   .nr = 0,   \
@@ -106,6 +112,7 @@ extern struct group_info init_groups;
   { .first = &init_task.pids[PIDTYPE_PGID].node }, \
   { .first = &init_task.pids[PIDTYPE_SID].node }, \
  },   \
+ .pid_nrs = { .first = &init_struct_pid_nr.node }, \
   .rcu = RCU_HEAD_INIT,   \
 }

Index: lx26-20-mm2b/kernel/pid.c
===
--- lx26-20-mm2b.orig/kernel/pid.c 2007-03-08 17:56:57.000000000 -0800
+++ lx26-20-mm2b/kernel/pid.c 2007-03-09 14:56:33.000000000 -0800

```
@@ -34,6 +34,7 @@ static struct hlist_head *pid_hash;
 static int pidhash_shift;
 static struct kmem_cache *pid_cachep;
 static struct kmem_cache *pid_nr_cachep;
+struct pid_nr init_struct_pid_nr = INIT_STRUCT_PID_NR;
 struct pid init_struct_pid = INIT_STRUCT_PID;

 int pid_max = PID_MAX_DEFAULT;
```

Containers mailing list
Containers@lists.osdl.org
https://lists.osdl.org/mailman/listinfo/containers