Subject: - explicitly-set-pgid-and-sid-of-init-process.patch removed from -mm tree
Posted by akpm on Sat, 12 May 2007 05:34:32 GMT
View Forum Message <> Reply to Message

The patch titled
    Explicitly set pgid and sid of init process
has been removed from the -mm tree. Its filename was
    explicitly-set-pgid-and-sid-of-init-process.patch

This patch was dropped because it was merged into mainline or a subsystem tree

---
Subject: Explicitly set pgid and sid of init process
From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Explicitly set pgid and sid of init process to 1.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: Eric Biederman <ebiederm@xmission.com>
Cc: Herbert Poetzl <herbert@13thfloor.at>
Cc: <containers@lists.osdl.org>
Acked-by: Eric W. Biederman <ebiederm@xmission.com>
Signed-off-by: Andrew Morton <akpm@linux-foundation.org>
---

 init/main.c | 1 +
 1 file changed, 1 insertion(+)

diff -puN init/main.c~explicitly-set-pgid-and-sid-of-init-process init/main.c
--- a/init/main.c~explicitly-set-pgid-and-sid-of-init-process
+++ a/init/main.c
@@ -801,6 +801,7 @@ static int __init kernel_init(void * unu
   */
  init_pid_ns.child_reaper = current;

+ __set_special_pids(1, 1);
  cad_pid = task_pid(current);

  smp_prepare_cpus(max_cpus);
_

Patches currently in -mm which might be from sukadev@us.ibm.com are

origin.patch

Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers