
Subject: Re: [PATCH] Virtual ethernet tunnel

Posted by [Daniel Lezcano](#) on Thu, 07 Jun 2007 14:42:09 GMT

[View Forum Message](#) <> [Reply to Message](#)

Kirill Korotaev wrote:

> Deniel,

>

> Daniel Lezcano wrote:

>

>> Pavel Emelianov wrote:

>>

>>

>>>> I did this at the very first version, but Alexey showed me that this
>>>> would be wrong. Look. When we create the second device it must be in
>>>> the other namespace as it is useless to have them in one namespace.
>>>> But if we have the device in the other namespace the RTNL_NEWLINK
>>>> message from kernel would come into this namespace thus confusing ip
>>>> utility in the init namespace. Creating the device in the init ns and
>>>> moving it into the new one is rather a complex task.

>>>>

>>>>

>>>>

>>>> Pavel,

>>>>

>>>> moving the netdevice to another namespace is not a complex task. Eric
>>>> Biederman did it in its patchset (cf. <http://lxc.sf.net/network>)

>>>>

>>>>

>>> By saying complex I didn't mean that this is difficult to implement,
>>> but that it consists (must consist) of many stages. I.e. composite.
>>> Making the device right in the namespace is liter.

>>>

>>>

>>>

>>>

>>>> When the pair device is created, both extremeties are into the init
>>>> namespace and you can choose to which namespace to move one extremity.

>>>>

>>>>

>>> I do not mind that.

>>>

>>>

>>>

>>>> When the network namespace dies, the netdev is moved back to the init
>>>> namespace.

>>>> That facilitate network device management.

>>>>

>>>> Concerning netlink events, this is automatically generated when the

>>>> network device is moved through namespaces.
>>>>
>>>> IMHO, we should have the network device movement between namespaces in
>>>> order to be able to move a physical network device too (eg. you have 4
>>>> NIC and you want to create 3 containers and assign 3 NIC to each of them)
>>>>
>>>>
>>> Agree. Moving the devices is a must-have functionality.
>>>
>>> I do not mind making the pair in the init namespace and move the second
>>> one into the desired namespace. But if we **always** will have two ends in
>>> different namespaces what to complicate things for?
>>>
>>>
>> Just to provide a netdev sufficiently generic to be used by people who
>> don't want namespaces but just want to do some network testing, like Ben
>> Greear does. He mentioned in a previous email, he will be happy to stop
>> redirecting people to out of tree patch.
>>
>> <https://lists.linux-foundation.org/pipermail/containers/2007-April/004420.html>
>>
>
> no one is against generic code and ability to create 2 interfaces in **one** namespace.
> (Like we currently allow to do so in OpenVZ)
>
> However, believe me, moving an interface is a **hard** operation. Much harder then netdev
> register from the scratch.
>
> Because it requires to take into account many things like:
> - packets in flight which requires synchronize and is slow on big machines
> - asynchronous sysfs entries registration/deregistration from
> rtln_unlock -> netdev_run_todo
> - name/ifindex collisions
> - shutdown/cleanup of addresses/routes/qdisc and other similar stuff
>
>
All of what you are describing is already implemented in the Eric's
patchset.

You can have a look at :

http://lxc.sourceforge.net/patches/2.6.20/2.6.20-netns1/broken_out/

And more precisely:

for sysfs issues:

http://lxc.sourceforge.net/patches/2.6.20/2.6.20-netns1/broken_out/0065-sysfs-Shadow-directory-support.patch

for network device movement:

http://lxc.sourceforge.net/patches/2.6.20/2.6.20-netns1/broken_out/0096-net-Implement-network-device-movement-between-namesp.patch

Thanks,
Daniel

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
