
Subject: [PATCH 2.6.22-rc5 2/2] System V IPC: new IPC_SETID command to modify an ID

Posted by [Pierre Peiffer](#) on Thu, 21 Jun 2007 14:48:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

This patch adds a new IPC_SETID command to the System V IPCs set of commands, which allows to change the ID of an existing IPC.

This command can be used through the semctl/shmctl/msgctl API, with the new ID passed as the third argument for msgctl and shmctl (instead of a pointer) and through the fourth argument for semctl.

To be successful, the following rules must be respected:

- the IPC exists
- the user must be allowed to change the IPC attributes regarding the IPC permissions.
- the new ID must satisfy the ID computation rule.
- the entry (in the kernel internal table of IPCs) corresponding to the new ID must be free.

Signed-off-by: Pierre Peiffer <pierre.peiffer@bull.net>

```
---
include/linux/ipc.h      |  9 +++++-
ipc/msg.c                | 31 ++++++-----
ipc/sem.c                | 31 ++++++-----
ipc/shm.c                | 55 ++++++-----
security/selinux/hooks.c |  3 ++
5 files changed, 100 insertions(+), 29 deletions(-)
```

Index: b/include/linux/ipc.h

```
=====
--- a/include/linux/ipc.h
+++ b/include/linux/ipc.h
@@ -35,10 +35,11 @@ struct ipc_perm
 * Control commands used with semctl, msgctl and shmctl
 * see also specific commands in sem.h, msg.h and shm.h
 */
-#define IPC_RMID 0 /* remove resource */
-#define IPC_SET 1 /* set ipc_perm options */
-#define IPC_STAT 2 /* get ipc_perm options */
-#define IPC_INFO 3 /* see ipcs */
+#define IPC_RMID 0 /* remove resource */
+#define IPC_SET 1 /* set ipc_perm options */
+#define IPC_STAT 2 /* get ipc_perm options */
+#define IPC_INFO 3 /* see ipcs */
+#define IPC_SETID 4 /* set ipc ID */
```

```

/*
 * Version flags for semctl, msgctl, and shmctl commands
Index: b/ipc/msg.c
=====
--- a/ipc/msg.c
+++ b/ipc/msg.c
@@ -81,6 +81,8 @@ static struct ipc_ids init_msg_ids;
#define msg_buildid(ns, id, seq) \
    ipc_buildid(&msg_ids(ns), id, seq)

+static long msg_chid_nolock(struct ipc_namespace *ns, struct msg_queue *msq,
+    int newid);
static void freeque (struct ipc_namespace *ns, struct msg_queue *msq, int id);
static int newque (struct ipc_namespace *ns, key_t key, int msgflg);
#ifdef CONFIG_PROC_FS
@@ -384,6 +386,21 @@ copy_msqid_from_user(struct msq_setbuf *
    }
}

+static long msg_chid_nolock(struct ipc_namespace *ns, struct msg_queue *msq,
+    int newid)
+{
+    long err;
+    err = ipc_mvid(&msg_ids(ns), msq->q_id,
+        newid, ns->msg_ctlmni);
+
+    if (err)
+        return err;
+
+    msq->q_id = newid;
+    msq->q_ctime = get_seconds();
+    return 0;
+}
+
long msg_mvid(struct ipc_namespace *ns, int id, int newid)
{
    long err;
@@ -400,14 +417,7 @@ long msg_mvid(struct ipc_namespace *ns,
    if(err)
        goto out_unlock_up;

-    err = ipc_mvid(&msg_ids(ns), id,
-        newid, ns->msg_ctlmni);
-
-    if (err)
-        goto out_unlock_up;
-
-    msq->q_id = newid;

```

```

- msq->q_ctime = get_seconds();
+ err = msg_chid_nolock(ns, msq, newid);

out_unlock_up:
    msg_unlock(msq);
@@ -523,6 +533,7 @@ asmlinkage long sys_msgctl(int msqid, in
    if (copy_msqid_from_user(&setbuf, buf, version))
        return -EFAULT;
    break;
+ case IPC_SETID:
    case IPC_RMID:
        break;
    default:
@@ -585,6 +596,10 @@ asmlinkage long sys_msgctl(int msqid, in
    msg_unlock(msq);
    break;
}
+ case IPC_SETID:
+ err = msg_chid_nolock(ns, msq, (int)buf);
+ msg_unlock(msq);
+ break;
    case IPC_RMID:
        freeque(ns, msq, msqid);
        break;

```

Index: b/ipc/sem.c

```

=====
--- a/ipc/sem.c
+++ b/ipc/sem.c
@@ -98,6 +98,8 @@

static struct ipc_ids init_sem_ids;

+static long sem_chid_nolock(struct ipc_namespace *ns, struct sem_array *sma,
+    int newid);
static int newary(struct ipc_namespace *, key_t, int, int);
static void freeary(struct ipc_namespace *ns, struct sem_array *sma, int id);
#ifdef CONFIG_PROC_FS
@@ -908,6 +910,10 @@ static int semctl_down(struct ipc_namesp
    sem_unlock(sma);
    err = 0;
    break;
+ case IPC_SETID:
+ err = sem_chid_nolock(ns, sma, (int)arg.val);
+ sem_unlock(sma);
+ break;
    default:
        sem_unlock(sma);
        err = -EINVAL;

```

```
@@ -920,6 +926,21 @@ out_unlock:
```

```
    return err;
}
```

```
+static long sem_chid_nolock(struct ipc_namespace *ns, struct sem_array *sma,
+    int newid)
```

```
+{
+    long err;
+    err = ipc_mvid(&sem_ids(ns), sma->sem_id,
+        newid, ns->sc_semmni);
+
+    if (err)
+        return err;
+
+    sma->sem_id = newid;
+    sma->sem_ctime = get_seconds();
+    return 0;
+}
```

```
+long sem_mvid(struct ipc_namespace *ns, int id, int newid)
```

```
{
    long err;
@@ -936,14 +957,7 @@ long sem_mvid(struct ipc_namespace *ns,
    if(err)
        goto out_unlock_up;
```

```
- err = ipc_mvid(&sem_ids(ns), id,
-    newid, ns->sc_semmni);
-
-    if (err)
-        goto out_unlock_up;
-
-    sma->sem_id = newid;
-    sma->sem_ctime = get_seconds();
+ err = sem_chid_nolock(ns, sma, newid);
```

```
out_unlock_up:
```

```
    sem_unlock(sma);
@@ -982,6 +996,7 @@ asmlinkage long sys_semctl (int semid, i
    return err;
    case IPC_RMID:
    case IPC_SET:
+ case IPC_SETID:
    mutex_lock(&sem_ids(ns).mutex);
    err = semctl_down(ns, semid, semnum, cmd, version, arg);
    mutex_unlock(&sem_ids(ns).mutex);
```

```
Index: b/security/selinux/hooks.c
```

```
=====
```

```

--- a/security/selinux/hooks.c
+++ b/security/selinux/hooks.c
@@ -4152,6 +4152,7 @@ static int selinux_msg_queue_msgctl(stru
    perms = MSGQ__GETATTR | MSGQ__ASSOCIATE;
    break;
    case IPC_SET:
+ case IPC_SETID:
    perms = MSGQ__SETATTR;
    break;
    case IPC_RMID:
@@ -4300,6 +4301,7 @@ static int selinux_shm_shmctl(struct shm
    perms = SHM__GETATTR | SHM__ASSOCIATE;
    break;
    case IPC_SET:
+ case IPC_SETID:
    perms = SHM__SETATTR;
    break;
    case SHM_LOCK:
@@ -4411,6 +4413,7 @@ static int selinux_sem_semctl(struct sem
    perms = SEM__DESTROY;
    break;
    case IPC_SET:
+ case IPC_SETID:
    perms = SEM__SETATTR;
    break;
    case IPC_STAT:
Index: b/ipc/shm.c
=====
--- a/ipc/shm.c
+++ b/ipc/shm.c
@@ -70,6 +70,8 @@ static struct ipc_ids init_shm_ids;

static int newseg (struct ipc_namespace *ns, key_t key,
    int shmflg, size_t size);
+static long shm_chid_nolock(struct ipc_namespace *ns, struct shmid_kernel *shp,
+    int newid);
static void shm_open(struct vm_area_struct *vma);
static void shm_close(struct vm_area_struct *vma);
static void shm_destroy (struct ipc_namespace *ns, struct shmid_kernel *shp);
@@ -158,6 +160,21 @@ static inline int shm_addid(struct ipc_n
    return ipc_addid(&shm_ids(ns), &shp->shm_perm, ns->shm_ctlmni);
}

+static long shm_chid_nolock(struct ipc_namespace *ns, struct shmid_kernel *shp,
+    int newid)
+{
+    long err;
+    err = ipc_mvid(&shm_ids(ns), shp->id,

```

```

+     newid, ns->shm_ctlmni);
+
+ if (err)
+ return err;
+
+ shp->id = newid;
+ shp->shm_ctim = get_seconds();
+ return 0;
+}
+
long shm_mvid(struct ipc_namespace *ns, int id, int newid)
{
    long err;
@@ -174,14 +191,7 @@ long shm_mvid(struct ipc_namespace *ns,
    if(err)
        goto out_unlock_up;

- err = ipc_mvid(&shm_ids(ns), id,
-     newid, ns->shm_ctlmni);
-
- if (err)
-     goto out_unlock_up;
-
- shp->id = newid;
- shp->shm_ctim = get_seconds();
+ err = shm_chid_nolock(ns, shp, newid);

out_unlock_up:
    shm_unlock(shp);
@@ -839,12 +849,39 @@ asmlinkage long sys_shmctl (int shmid, i
    break;
}

+ case IPC_SETID:
+ {
+     mutex_lock(&shm_ids(ns).mutex);
+     shp = shm_lock(ns, shmid);
+     err = -EINVAL;
+     if(shp == NULL)
+         goto out_up;
+     err = shm_checkid(ns, shp, shmid);
+     if(err)
+         goto out_unlock_up;
+     err = audit_ipc_obj(&(shp->shm_perm));
+     if (err)
+         goto out_unlock_up;
+
+     err = -EPERM;

```

```

+ if (current->euid != shp->shm_perm.uid &&
+     current->euid != shp->shm_perm.cuid &&
+     !capable(CAP_SYS_ADMIN))
+     goto out_unlock_up;
+
+ err = security_shm_shmctl(shp, cmd);
+ if (err)
+     goto out_unlock_up;
+
+ err = shm_chid_nolock(ns, shp, (int)buf);
+ break;
+ }
+
+ default:
+     err = -EINVAL;
+     goto out;
+ }

- err = 0;
out_unlock_up:
    shm_unlock(shp);
out_up:

```

--

Pierre Peiffer

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
