Subject: [net-2.6.24][NETNS][patch 2/3] fix loopback network namespace initialization
Posted by Daniel Lezcano on Wed, 12 Sep 2007 12:38:13 GMT
View Forum Message <> Reply to Message

From: Daniel Lezcano <dlezcano@fr.ibm.com>

The core patchset of the network namespace sent by
Eric Biederman does not do dynamic loopback creation.
So there is no call to alloc_netdev_mq which fills the
network namespace field of the netdevice.

This patch assign the loopback to the init network namespace.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>
---
 drivers/net/loopback.c | 1 +
 1 file changed, 1 insertion(+)

Index: net-2.6.24/drivers/net/loopback.c
===
--- net-2.6.24.orig/drivers/net/loopback.c
+++ net-2.6.24/drivers/net/loopback.c
@@ -225,6 +225,7 @@
       | NETIF_F_LLTX
       | NETIF_F_NETNS_LOCAL,
   .ethtool_ops = &loopback_ethtool_ops,
+ .nd_net   = &init_net,
 };

 /* Setup and register the loopback device. */

--

_____

Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers