Subject: [PATCH] Remove unused member from nsproxy
Posted by Pavel Emelianov on Wed, 26 Sep 2007 13:14:33 GMT
View Forum Message <> Reply to Message

The nslock spinlock is not used in the kernel at all.
Remove it.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/include/linux/init_task.h b/include/linux/init_task.h
index a3f2541..cae35b6 100644
--- a/include/linux/init_task.h
+++ b/include/linux/init_task.h
@@ -73,7 +73,6 @@ extern struct nsproxy init_nsproxy;
 #define INIT_NSPROXY(nsproxy) {      \
  .pid_ns  = &init_pid_ns,     \
  .count  = ATOMIC_INIT(1),    \
- .nslock  = __SPIN_LOCK_UNLOCKED(nsproxy.nslock),  \
  .uts_ns  = &init_uts_ns,     \
  .mnt_ns  = NULL,      \
  INIT_NET_NS(net_ns)                                     \
diff --git a/include/linux/nsproxy.h b/include/linux/nsproxy.h
index 4d564d8..0e66b57 100644
--- a/include/linux/nsproxy.h
+++ b/include/linux/nsproxy.h
@@ -23,7 +23,6 @@ struct pid_namespace;
  */
 struct nsproxy {
  atomic_t count;
- spinlock_t nslock;
  struct uts_namespace *uts_ns;
  struct ipc_namespace *ipc_ns;
  struct mnt_namespace *mnt_ns;
```

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers