
Subject: [PATCH 1/5] The config option itself
Posted by [Pavel Emelianov](#) on Wed, 26 Sep 2007 15:43:28 GMT
[View Forum Message](#) <> [Reply to Message](#)

The option is called NAMESPACES. It can be selectable only if EMBEDDED is chosen (this was Eric's requisition). When the EMBEDDED is off namespaces will be on automatically.

One more option (NAMESPACES_EXPERIMENTAL) was added by Serge's request to move there all the namespaces that are not finished yet. Currently only the user and the network namespaces are such.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/init/Kconfig b/init/Kconfig
index 684ccfb..05a71d7 100644
--- a/init/Kconfig
+++ b/init/Kconfig
@@ -369,6 +360,23 @@ @@ config RELAY
```

If unsure, say N.

```
+config NAMESPACES
+ bool "The namespaces support" if EMBEDDED
+ default !EMBEDDED
+ help
+   Provides the way to make tasks work with different objects using
+   the same id. For example same IPC id may refer to different objects
+   or same user id or pid may refer to different tasks when used in
+   different namespaces.
+
+config NAMESPACES_EXPERIMENTAL
+ bool "Add the experimental namespaces support" if EMBEDDED
+ depends on NAMESPACES && EXPERIMENTAL
+ default !EMBEDDED
+ help
+   Also include the support for the namespaces that are not finished
+   or well developed yet
+
+config BLK_DEV_INITRD
+ bool "Initial RAM filesystem and RAM disk (initramfs/initrd) support"
+ depends on BROKEN || !FRV
```

Containers mailing list
Containers@lists.linux-foundation.org

