
Subject: [PATCH 6/6][NET-2.6.24] Make the sunrpc use the seq_open_private()
Posted by [Pavel Emelianov](#) on Tue, 09 Oct 2007 16:04:23 GMT
[View Forum Message](#) <> [Reply to Message](#)

Just switch to the consolidated code.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>
Cc: Neil Brown <neilb@cse.unsw.edu.au>

```
diff --git a/net/sunrpc/cache.c b/net/sunrpc/cache.c
index ebe344f..8e05557 100644
--- a/net/sunrpc/cache.c
+++ b/net/sunrpc/cache.c
@@ -1218,23 +1218,15 @@ static const struct seq_operations cache

static int content_open(struct inode *inode, struct file *file)
{
- int res;
  struct handle *han;
  struct cache_detail *cd = PDE(inode)->data;

- han = kmalloc(sizeof(*han), GFP_KERNEL);
+ han = __seq_open_private(file, &cache_content_op, sizeof(*han));
  if (han == NULL)
    return -ENOMEM;

  han->cd = cd;
-
- res = seq_open(file, &cache_content_op);
- if (res)
-   kfree(han);
- else
-   ((struct seq_file *)file->private_data)->private = han;
-
- return res;
+ return 0;
}

static const struct file_operations content_file_operations = {
```
