
Subject: Re: [PATCH] namespaces: introduce sys_hijack (v4)

Posted by [serue](#) on Thu, 11 Oct 2007 22:15:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

Quoting Serge E. Hallyn (serue@us.ibm.com):

> >From 945fe66259cd0cfdc2fe846287b7821e329a558c Mon Sep 17 00:00:00 2001

> From: sergeh@us.ibm.com <[hallyn@kernel.\(none\)](mailto:hallyn@kernel.(none))>

> Date: Tue, 9 Oct 2007 08:30:30 -0700

> Subject: [PATCH] namespaces: introduce sys_hijack (v4)

>

> Move most of do_fork() into a new do_fork_task() which acts on

> a new argument, task, rather than on current. do_fork() becomes

> a call to do_fork_task(current, ...).

>

> Introduce sys_hijack (for x86 only so far). It is like clone, but

> in place of a stack pointer (which is assumed null) it accepts a

> pid. The process identified by that pid is the one which is

> actually cloned. Some state - include the file table, the signals

> and sighand (and hence tty), and the ->parent are taken from the

> calling process.

>

> The effect is a sort of namespace enter. The following program

> uses sys_hijack to 'enter' all namespaces of the specified pid.

> For instance in one terminal, do

>

> mount -t cgroup -ons /cgroup

> hostname

> qemu

> ns_exec -u /bin/sh

> hostname serge

> echo \$\$

> 1073

> cat /proc/\$\$/cgroup

> ns:/node_1073

>

> In another terminal then do

>

> hostname

> qemu

> cat /proc/\$\$/cgroup

> ns:/

> hijack 1073

> hostname

> serge

> cat /proc/\$\$/cgroup

> ns:/node_1073

>

> sys_hijack is arch-dependent and is only implemented for i386 so far.

- >
- > Changelog:
- > Aug 23: send a stop signal to the hijacked process
- > (like ptrace does).
- > Oct 09: Update for 2.6.23-rc8-mm2 (mainly pidns)
- > Don't take task_lock under rcu_read_lock
- > Send hijacked process to cgroup_fork() as
- > the first argument.
- > Removed some unneeded task_locks.

Thanks to Cedric for finding an oops when using pid namespaces. The following patch fixes the problem.

In addition, to hijack a process in another pid namespace, the hijack.c test program needs to be updated to do waitpid as

```
while(waitpid(-1, &status, __WALL) != -1)
;
```

as shown below:

```
=====
hijack.c
=====

int do_clone_task(void)
{
    execl("/bin/sh", "/bin/sh", NULL);
}

int main(int argc, char *argv[])
{
    int pid;
    int ret;
    int status;

    if (argc < 2)
        return 1;
    pid = atoi(argv[1]);

    ret = syscall(327, SIGCHLD, pid, NULL, NULL);

    if (ret == 0) {
        return do_clone_task();
    } else if (ret < 0) {
        perror("sys_hijack");
    } else {
        printf("waiting on cloned process %d\n", ret);
        while(waitpid(-1, &status, __WALL) != -1)

```

```

;
printf("cloned process %d exited with %d\n", ret, status);
}

return ret;
}
=====

```

>From f1d9621e8325471e3ccde7f5fc2ed5a7be582524 Mon Sep 17 00:00:00 2001
 From: sergeh@us.ibm.com <hallyn@kernel.(none)>
 Date: Thu, 11 Oct 2007 14:26:05 -0700
 Subject: [PATCH 2/2] hijack: pidns bugfix

My change to alloc_pid was bogus and introduced a pidns bug. Fix.

Signed-off-by: sergeh@us.ibm.com <hallyn@kernel.(none)>

```

---
include/linux/pid.h | 2 +-
kernel/fork.c      | 2 +-
kernel/pid.c       | 5 +++--
3 files changed, 4 insertions(+), 5 deletions(-)

```

```

diff --git a/include/linux/pid.h b/include/linux/pid.h
index 145dce7..e29a900 100644
--- a/include/linux/pid.h
+++ b/include/linux/pid.h
@@ -119,7 +119,7 @@ extern struct pid *find_pid(int nr);
extern struct pid *find_get_pid(int nr);
extern struct pid *find_ge_pid(int nr, struct pid_namespace *);

-extern struct pid *alloc_pid(struct task_struct *task);
+extern struct pid *alloc_pid(struct pid_namespace *ns);
extern void FASTCALL(free_pid(struct pid *pid));
extern void zap_pid_ns_processes(struct pid_namespace *pid_ns);

```

```

diff --git a/kernel/fork.c b/kernel/fork.c
index ac73f3e..c1d4672 100644
--- a/kernel/fork.c
+++ b/kernel/fork.c
@@ -1154,7 +1154,7 @@ static struct task_struct *copy_process(struct task_struct *task,

if (pid != &init_struct_pid) {
    retval = -ENOMEM;
-   pid = alloc_pid(task);
+   pid = alloc_pid(task_active_pid_ns(p));
    if (!pid)
        goto bad_fork_cleanup_namespaces;

```

```

diff --git a/kernel/pid.c b/kernel/pid.c
index b887a6a..d7388d7 100644
--- a/kernel/pid.c
+++ b/kernel/pid.c
@@ -238,15 +238,14 @@ fastcall void free_pid(struct pid *pid)
    call_rcu(&pid->rcu, delayed_put_pid);
}

-struct pid *alloc_pid(struct task_struct *srctsk)
+struct pid *alloc_pid(struct pid_namespace *ns)
{
    struct pid *pid;
    enum pid_type type;
    int i, nr;
- struct pid_namespace *tmp, *ns;
+ struct pid_namespace *tmp;
    struct upid *upid;

- ns = task_active_pid_ns(srctsk);
    pid = kmem_cache_alloc(ns->pid_cachep, GFP_KERNEL);
    if (!pid)
        goto out;
--
1.5.1

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
