Subject: [PATCH 2/2][INET] Move the reqsk_queue_yank_listen_sk from header
Posted by Pavel Emelianov on Wed, 14 Nov 2007 18:11:06 GMT
View Forum Message <> Reply to Message

This function is used in the net/core/request_sock.c only.
No need in keeping it in the header file.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/include/net/request_sock.h b/include/net/request_sock.h
index 0a954ee..e80b53f 100644
--- a/include/net/request_sock.h
+++ b/include/net/request_sock.h
@@ -123,19 +123,6 @@ struct request_sock_queue {

 extern int reqsk_queue_alloc(struct request_sock_queue *queue,
        unsigned int nr_table_entries);
-
-static inline struct listen_sock *reqsk_queue_yank_listen_sk(struct request_sock_queue *queue)
-{
- struct listen_sock *lopt;
-
- write_lock_bh(&queue->syn_wait_lock);
- lopt = queue->listen_opt;
- queue->listen_opt = NULL;
- write_unlock_bh(&queue->syn_wait_lock);
-
- return lopt;
-}
-
 extern void __reqsk_queue_destroy(struct request_sock_queue *queue);
 extern void reqsk_queue_destroy(struct request_sock_queue *queue);

diff --git a/net/core/request_sock.c b/net/core/request_sock.c
index 12a15f5..16b2ef0 100644
--- a/net/core/request_sock.c
+++ b/net/core/request_sock.c
@@ -71,6 +71,19 @@ int reqsk_queue_alloc(struct request_sock_queue *queue,

 EXPORT_SYMBOL(reqsk_queue_alloc);

+static struct listen_sock *reqsk_queue_yank_listen_sk(
+  struct request_sock_queue *queue)
+{
+ struct listen_sock *lopt;
+
```

```
+ write_lock_bh(&queue->syn_wait_lock);
+ lopt = queue->listen_opt;
+ queue->listen_opt = NULL;
+ write_unlock_bh(&queue->syn_wait_lock);
+
+ return lopt;
+}
+
 void __reqsk_queue_destroy(struct request_sock_queue *queue)
 {
  struct listen_sock *lopt = reqsk_queue_yank_listen_sk(queue);
--
1.5.3.4
```
