Subject: [PATCH 2.6.25 5/6] net: Make AF_UNIX per network namespace safe (v2)
Posted by den on Thu, 15 Nov 2007 16:00:41 GMT
View Forum Message <> Reply to Message

>From 337f0867c81ab93a1bc645e62896a798d0c864ac Mon Sep 17 00:00:00 2001
From: Denis V. Lunev <den@openvz.org>
Date: Thu, 15 Nov 2007 15:04:12 +0300
Subject: [PATCH] net: Make AF_UNIX per network namespace safe [v2]

Because of the global nature of garbage collection, and because of the
cost of per namespace hash tables unix_socket_table has been kept
global. With a filter added on lookups so we don't see sockets from
the wrong namespace.

Currently I don't fold the namesapce into the hash so multiple
namespaces using the same socket name will be guaranteed a hash
collision.

Changes from v1:
- fixed unix_seq_open

Signed-off-by: Denis V. Lunev <den@openvz.org>
Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>
---
 net/unix/af_unix.c | 118 ++-----------
 1 files changed, 92 insertions(+), 26 deletions(-)

diff --git a/net/unix/af_unix.c b/net/unix/af_unix.c
index e835da8..93d7e55 100644
--- a/net/unix/af_unix.c
+++ b/net/unix/af_unix.c
@@ -270,7 +270,8 @@ static inline void unix_insert_socket(struct hlist_head *list, struct sock
*sk)
  spin_unlock(&unix_table_lock);
 }

-static struct sock *__unix_find_socket_byname(struct sockaddr_un *sunname,
+static struct sock *__unix_find_socket_byname(struct net *net,
+   struct sockaddr_un *sunname,
           int len, int type, unsigned hash)
 {
  struct sock *s;
@@ -279,6 +280,9 @@ static struct sock *__unix_find_socket_byname(struct sockaddr_un
*sunname,
  sk_for_each(s, node, &unix_socket_table[hash ^ type]) {
   struct unix_sock *u = unix_sk(s);

+ if (s->sk_net != net)

```
+   continue;
+
    if (u->addr->len == len &&
        !memcmp(u->addr->name, sunname, len))
     goto found;
@@ -288,21 +292,22 @@ found:
  return s;
 }

-static inline struct sock *unix_find_socket_byname(struct sockaddr_un *sunname,
+static inline struct sock *unix_find_socket_byname(struct net *net,
+          struct sockaddr_un *sunname,
           int len, int type,
           unsigned hash)
 {
  struct sock *s;

  spin_lock(&unix_table_lock);
- s = __unix_find_socket_byname(sunname, len, type, hash);
+ s = __unix_find_socket_byname(net, sunname, len, type, hash);
  if (s)
   sock_hold(s);
  spin_unlock(&unix_table_lock);
  return s;
 }

-static struct sock *unix_find_socket_byinode(struct inode *i)
+static struct sock *unix_find_socket_byinode(struct net *net, struct inode *i)
 {
  struct sock *s;
  struct hlist_node *node;
@@ -312,6 +317,9 @@ static struct sock *unix_find_socket_byinode(struct inode *i)
       &unix_socket_table[i->i_ino & (UNIX_HASH_SIZE - 1)]) {
    struct dentry *dentry = unix_sk(s)->dentry;

+  if (s->sk_net != net)
+   continue;
+
    if(dentry && dentry->d_inode == i)
    {
     sock_hold(s);
@@ -631,9 +639,6 @@ out:

 static int unix_create(struct net *net, struct socket *sock, int protocol)
 {
- if (net != &init_net)
-  return -EAFNOSUPPORT;
-
```

```
  if (protocol && protocol != PF_UNIX)
   return -EPROTONOSUPPORT;

@@ -677,6 +682,7 @@ static int unix_release(struct socket *sock)
 static int unix_autobind(struct socket *sock)
 {
  struct sock *sk = sock->sk;
+ struct net *net = sk->sk_net;
  struct unix_sock *u = unix_sk(sk);
  static u32 ordernum = 1;
  struct unix_address * addr;
@@ -703,7 +709,7 @@ retry:
  spin_lock(&unix_table_lock);
  ordernum = (ordernum+1)&0xFFFFF;

- if (__unix_find_socket_byname(addr->name, addr->len, sock->type,
+ if (__unix_find_socket_byname(net, addr->name, addr->len, sock->type,
           addr->hash)) {
   spin_unlock(&unix_table_lock);
   /* Sanity yield. It is unusual case, but yet... */
@@ -723,7 +729,8 @@ out: mutex_unlock(&u->readlock);
  return err;
 }

-static struct sock *unix_find_other(struct sockaddr_un *sunname, int len,
+static struct sock *unix_find_other(struct net *net,
+        struct sockaddr_un *sunname, int len,
         int type, unsigned hash, int *error)
 {
  struct sock *u;
@@ -741,7 +748,7 @@ static struct sock *unix_find_other(struct sockaddr_un *sunname, int len,
   err = -ECONNREFUSED;
   if (!S_ISSOCK(nd.dentry->d_inode->i_mode))
    goto put_fail;
-  u=unix_find_socket_byinode(nd.dentry->d_inode);
+  u=unix_find_socket_byinode(net, nd.dentry->d_inode);
   if (!u)
    goto put_fail;

@@ -757,7 +764,7 @@ static struct sock *unix_find_other(struct sockaddr_un *sunname, int len,
   }
  } else {
   err = -ECONNREFUSED;
-  u=unix_find_socket_byname(sunname, len, type, hash);
+  u=unix_find_socket_byname(net, sunname, len, type, hash);
   if (u) {
    struct dentry *dentry;
    dentry = unix_sk(u)->dentry;
```

```
@@ -779,6 +786,7 @@ fail:
 static int unix_bind(struct socket *sock, struct sockaddr *uaddr, int addr_len)
 {
  struct sock *sk = sock->sk;
+ struct net *net = sk->sk_net;
  struct unix_sock *u = unix_sk(sk);
  struct sockaddr_un *sunaddr=(struct sockaddr_un *)uaddr;
  struct dentry * dentry = NULL;
@@ -853,7 +861,7 @@ static int unix_bind(struct socket *sock, struct sockaddr *uaddr, int
addr_len)

  if (!sunaddr->sun_path[0]) {
   err = -EADDRINUSE;
-  if (__unix_find_socket_byname(sunaddr, addr_len,
+  if (__unix_find_socket_byname(net, sunaddr, addr_len,
           sk->sk_type, hash)) {
    unix_release_addr(addr);
    goto out_unlock;
@@ -919,6 +927,7 @@ static int unix_dgram_connect(struct socket *sock, struct sockaddr *addr,
         int alen, int flags)
 {
  struct sock *sk = sock->sk;
+ struct net *net = sk->sk_net;
  struct sockaddr_un *sunaddr=(struct sockaddr_un*)addr;
  struct sock *other;
  unsigned hash;
@@ -935,7 +944,7 @@ static int unix_dgram_connect(struct socket *sock, struct sockaddr *addr,
    goto out;

 restart:
-  other=unix_find_other(sunaddr, alen, sock->type, hash, &err);
+  other=unix_find_other(net, sunaddr, alen, sock->type, hash, &err);
   if (!other)
    goto out;

@@ -1015,6 +1024,7 @@ static int unix_stream_connect(struct socket *sock, struct sockaddr
*uaddr,
 {
  struct sockaddr_un *sunaddr=(struct sockaddr_un *)uaddr;
  struct sock *sk = sock->sk;
+ struct net *net = sk->sk_net;
  struct unix_sock *u = unix_sk(sk), *newu, *otheru;
  struct sock *newsk = NULL;
  struct sock *other = NULL;
@@ -1054,7 +1064,7 @@ static int unix_stream_connect(struct socket *sock, struct sockaddr
*uaddr,

 restart:
```

```
  /*  Find listening sock. */
- other = unix_find_other(sunaddr, addr_len, sk->sk_type, hash, &err);
+ other = unix_find_other(net, sunaddr, addr_len, sk->sk_type, hash, &err);
  if (!other)
   goto out;

@@ -1330,6 +1340,7 @@ static int unix_dgram_sendmsg(struct kiocb *kiocb, struct socket
*sock,
 {
  struct sock_iocb *siocb = kiocb_to_siocb(kiocb);
  struct sock *sk = sock->sk;
+ struct net *net = sk->sk_net;
  struct unix_sock *u = unix_sk(sk);
  struct sockaddr_un *sunaddr=msg->msg_name;
  struct sock *other = NULL;
@@ -1393,7 +1404,7 @@ restart:
   if (sunaddr == NULL)
    goto out_free;

-  other = unix_find_other(sunaddr, namelen, sk->sk_type,
+  other = unix_find_other(net, sunaddr, namelen, sk->sk_type,
       hash, &err);
   if (other==NULL)
    goto out_free;
@@ -1999,12 +2010,18 @@ static unsigned int unix_poll(struct file * file, struct socket *sock,
poll_tabl


 #ifdef CONFIG_PROC_FS
-static struct sock *unix_seq_idx(int *iter, loff_t pos)
+struct unix_iter_state {
+ struct net *net;
+ int i;
+};
+static struct sock *unix_seq_idx(struct unix_iter_state *iter, loff_t pos)
 {
  loff_t off = 0;
  struct sock *s;

- for (s = first_unix_socket(iter); s; s = next_unix_socket(iter, s)) {
+ for (s = first_unix_socket(&iter->i); s; s = next_unix_socket(&iter->i, s)) {
+  if (s->sk_net != iter->net)
+   continue;
   if (off == pos)
    return s;
   ++off;
@@ -2015,17 +2032,24 @@ static struct sock *unix_seq_idx(int *iter, loff_t pos)
```

```
 static void *unix_seq_start(struct seq_file *seq, loff_t *pos)
 {
+ struct unix_iter_state *iter = seq->private;
  spin_lock(&unix_table_lock);
- return *pos ? unix_seq_idx(seq->private, *pos - 1) : ((void *) 1);
+ return *pos ? unix_seq_idx(iter, *pos - 1) : ((void *) 1);
 }

 static void *unix_seq_next(struct seq_file *seq, void *v, loff_t *pos)
 {
+ struct unix_iter_state *iter = seq->private;
+ struct sock *sk = v;
  ++*pos;

  if (v == (void *)1)
-  return first_unix_socket(seq->private);
- return next_unix_socket(seq->private, v);
+  sk = first_unix_socket(&iter->i);
+ else
+  sk = next_unix_socket(&iter->i, sk);
+ while (sk && (sk->sk_net != iter->net))
+  sk = next_unix_socket(&iter->i, sk);
+ return sk;
 }

 static void unix_seq_stop(struct seq_file *seq, void *v)
@@ -2087,7 +2111,27 @@ static const struct seq_operations unix_seq_ops = {

 static int unix_seq_open(struct inode *inode, struct file *file)
 {
- return seq_open_private(file, &unix_seq_ops, sizeof(int));
+ struct unix_iter_state *it;
+
+ it = __seq_open_private(file, &unix_seq_ops,
+    sizeof(struct unix_iter_state));
+ if (it == NULL)
+  return -ENOMEM;
+
+ it->net = get_proc_net(inode);
+ if (it->net == NULL) {
+  seq_release_private(inode, file);
+  return -ENXIO;
+ }
+ return 0;
+}
+
+static int unix_seq_release(struct inode *inode, struct file *file)
+{
```

```
+ struct seq_file *seq = file->private_data;
+ struct unix_iter_state *iter = seq->private;
+ put_net(iter->net);
+ return seq_release_private(inode, file);
 }

 static const struct file_operations unix_seq_fops = {
@@ -2095,7 +2139,7 @@ static const struct file_operations unix_seq_fops = {
  .open  = unix_seq_open,
  .read  = seq_read,
  .llseek  = seq_lseek,
- .release = seq_release_private,
+ .release = unix_seq_release,
 };

 #endif
@@ -2106,6 +2150,30 @@ static struct net_proto_family unix_family_ops = {
  .owner = THIS_MODULE,
 };

+
+static int unix_net_init(struct net *net)
+{
+ int error = -ENOMEM;
+
+#ifdef CONFIG_PROC_FS
+ if (!proc_net_fops_create(net, "unix", 0, &unix_seq_fops))
+  goto out;
+#endif
+ error = 0;
+out:
+ return 0;
+}
+
+static void unix_net_exit(struct net *net)
+{
+ proc_net_remove(net, "unix");
+}
+
+static struct pernet_operations unix_net_ops = {
+ .init = unix_net_init,
+ .exit = unix_net_exit,
+};
+
 static int __init af_unix_init(void)
 {
  int rc = -1;
@@ -2121,9 +2189,7 @@ static int __init af_unix_init(void)
```

```
 }

 sock_register(&unix_family_ops);
-#ifdef CONFIG_PROC_FS
- proc_net_fops_create(&init_net, "unix", 0, &unix_seq_fops);
-#endif
+ register_pernet_subsys(&unix_net_ops);
 unix_sysctl_register();
 out:
 return rc;
@@ -2133,8 +2199,8 @@ static void __exit af_unix_exit(void)
 {
 sock_unregister(PF_UNIX);
 unix_sysctl_unregister();
- proc_net_remove(&init_net, "unix");
 proto_unregister(&unix_proto);
+ unregister_pernet_subsys(&unix_net_ops);
 }

 module_init(af_unix_init);
--
1.5.3.rc5
```

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers