

---

Subject: Re: [PATCH][DECNET] dn\_nl\_deladdr() almost always returns no error  
Posted by [Steven Whitehouse](#) on Thu, 29 Nov 2007 16:35:43 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Hi,

On Thu, Nov 29, 2007 at 07:29:20PM +0300, Pavel Emelyanov wrote:

> As far as I see from the err variable initialization  
> the dn\_nl\_deladdr() routine was designed to report errors  
> like "EADDRNOTAVAIL" and probaby "ENODEV".

>  
> But the code sets this err to 0 after the first nlmsg\_parse  
> and goes on, returning this 0 in any case.

>  
> Is this made deliberately, or the patch below is correct?

>  
The patch looks good to me.

> Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

Acked-by: Steven Whitehouse <swhiteho@redhat.com>

Steve.

>  
> ---  
>  
> diff --git a/net/decnet/dn\_dev.c b/net/decnet/dn\_dev.c  
> index 66e266f..3bc82dc 100644  
> --- a/net/decnet/dn\_dev.c  
> +++ b/net/decnet/dn\_dev.c  
> @@ -651,16 +651,18 @@ static int dn\_nl\_deladdr(struct sk\_buff \*skb, struct nlmsg\_hdr \*nlh,  
> void \*arg)  
> struct dn\_dev \*dn\_db;  
> struct ifaddrmsg \*ifm;  
> struct dn\_ifaddr \*ifa, \*\*ifap;  
> - int err = -EADDRNOTAVAIL;  
> + int err;  
>  
> err = nlmsg\_parse(nlh, sizeof(\*ifm), tb, IFA\_MAX, dn\_ifa\_policy);  
> if (err < 0)  
> goto errout;  
>  
> + err = -ENODEV;  
> ifm = nlmsg\_data(nlh);  
> if ((dn\_db = dn\_dev\_by\_index(ifm->ifa\_index)) == NULL)  
> goto errout;  
>  
> + err = -EADDRNOTAVAIL;

```
> for (ifap = &dn_db->ifa_list; (ifa = *ifap); ifap = &ifa->ifa_next) {  
>   if (tb[IFA_LOCAL] &&  
>     nla_memcmp(tb[IFA_LOCAL], &ifa->ifa_local, 2))  
> -  
> To unsubscribe from this list: send the line "unsubscribe netdev" in  
> the body of a message to majordomo@vger.kernel.org  
> More majordomo info at http://vger.kernel.org/majordomo-info.html
```

---