
Subject: [PATCH net-2.6.25 1/3][IPV6] Cleanup the addrconf_sysctl_register
Posted by [Pavel Emelianov](#) on Fri, 30 Nov 2007 18:51:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

This only includes fixing the space-indented lines and removing one unneeded else after the goto.

Signed-off-by: Pavel Emelianov <xemul@openvz.org>

```
diff --git a/net/ipv6/addrconf.c b/net/ipv6/addrconf.c
```

```
index f177424..2d2886a 100644
```

```
--- a/net/ipv6/addrconf.c
```

```
+++ b/net/ipv6/addrconf.c
```

```
@@ -4127,7 +4127,8 @@ static void addrconf_sysctl_register(struct inet6_dev *idev, struct  
ipv6_devconf
```

```
    t = kmemdup(&addrconf_sysctl, sizeof(*t), GFP_KERNEL);
```

```
    if (t == NULL)
```

```
-    return;
```

```
+    goto out;
```

```
+
```

```
    for (i=0; t->addrconf_vars[i].data; i++) {
```

```
        t->addrconf_vars[i].data += (char*)p - (char*)&ipv6_devconf;
```

```
        t->addrconf_vars[i].extra1 = idev; /* embedded; no ref */
```

```
@@ -4147,7 +4148,7 @@ static void addrconf_sysctl_register(struct inet6_dev *idev, struct  
ipv6_devconf
```

```
    /*
```

```
    dev_name = kstrdup(dev_name, GFP_KERNEL);
```

```
    if (!dev_name)
```

```
-    goto free;
```

```
+    goto free;
```

```
    t->addrconf_dev[0].procname = dev_name;
```

```
@@ -4159,16 +4160,15 @@ static void addrconf_sysctl_register(struct inet6_dev *idev, struct  
ipv6_devconf
```

```
    t->sysctl_header = register_sysctl_table(t->addrconf_root_dir);
```

```
    if (t->sysctl_header == NULL)
```

```
        goto free_procname;
```

```
-    else
```

```
-    p->sysctl = t;
```

```
+
```

```
+    p->sysctl = t;
```

```
    return;
```

```
- /* error path */
```

```
- free_procname:  
+free_procname:  
  kfree(dev_name);  
- free:  
+free:  
  kfree(t);  
-  
+out:  
  return;  
}
```

```
--  
1.5.3.4
```
