Subject: RE: init output
Posted by Dietmar Maurer on Tue, 11 Dec 2007 12:36:23 GMT
View Forum Message <> Reply to Message

OK, tried it both ways, but output is truncated by vzctl stop.

For example the following init script:

#!/bin/sh

file must be there - create it
echo >/var/log/init.log
export CONSOLE=/var/log/init.log
exec /sbin/init.org

---

then I start the VE and try to view the log:

> vzctl start 777

> tail -100f /var/lib/vz/root/777/var/log/init.log
stty: standard input: Inappropriate ioctl for device
/etc/rcS.d/S03udev: line 265: echo: write error: Operation not permitted
Activating swap...done.
mount: permission denied
Cleaning up ifupdown....
....

That works quite good so far, but when I stop the VE the file gets
truncated:

tail: /var/lib/vz/root/777/var/log/init.log: file truncated

Any idea why? I already searched the sysvinit code sources, but found
nothing there.

- Dietmar

> or you can replace /sbin/init with some script adding this to
> env and running original init binary.
>
> Kirill
>
> Dietmar Maurer wrote:

> > But I cant do that with current vzctl, instead I need to modify the
> > source?
> >
> > env.c 301: char *envp[] = {"HOME=/", "TERM=linux",
> > "CONSOLE=/var/log/init.log", NULL};
> >