Subject: [PATCH 5/7] uts namespaces: sysctl hack
Posted by serue on Sat, 08 Apr 2006 04:52:07 GMT
View Forum Message <> Reply to Message

Sysctl uts patch. This clearly will need to be done another way, but
since sysctl itself needs to be container aware, 'the right thing' is
a separate patchset.

Signed-off-by: Serge E. Hallyn <serue@us.ibm.com>

---

 kernel/sysctl.c | 38 ++++++++++++++++++++++++++++++++++++++----------
 1 files changed, 28 insertions(+), 10 deletions(-)

280d6a838396d93984159765d4aed499bbd3281c
diff --git a/kernel/sysctl.c b/kernel/sysctl.c
index e82726f..c2b18ef 100644
--- a/kernel/sysctl.c
+++ b/kernel/sysctl.c
@@ -233,8 +233,8 @@ static ctl_table kern_table[] = {
  {
   .ctl_name = KERN_OSTYPE,
   .procname = "ostype",
- .data = system_utsname.sysname,
- .maxlen = sizeof(system_utsname.sysname),
+ .data = init_uts_ns.name.sysname,
+ .maxlen = sizeof(init_uts_ns.name.sysname),
   .mode = 0444,
   .proc_handler = &proc_doutsstring,
   .strategy = &sysctl_string,
@@ -242,8 +242,8 @@ static ctl_table kern_table[] = {
  {
   .ctl_name = KERN_OSRELEASE,
   .procname = "osrelease",
- .data = system_utsname.release,
- .maxlen = sizeof(system_utsname.release),
+ .data = init_uts_ns.name.release,
+ .maxlen = sizeof(init_uts_ns.name.release),
   .mode = 0444,
   .proc_handler = &proc_doutsstring,
   .strategy = &sysctl_string,
@@ -251,8 +251,8 @@ static ctl_table kern_table[] = {
  {
   .ctl_name = KERN_VERSION,
   .procname = "version",
- .data = system_utsname.version,
- .maxlen = sizeof(system_utsname.version),

```
+  .data  = init_uts_ns.name.version,
+  .maxlen  = sizeof(init_uts_ns.name.version),
   .mode  = 0444,
   .proc_handler = &proc_doutsstring,
   .strategy = &sysctl_string,
@@ -260,8 +260,8 @@ static ctl_table kern_table[] = {
  {
   .ctl_name = KERN_NODENAME,
   .procname = "hostname",
-  .data  = system_utsname.nodename,
-  .maxlen  = sizeof(system_utsname.nodename),
+  .data  = init_uts_ns.name.nodename,
+  .maxlen  = sizeof(init_uts_ns.name.nodename),
   .mode  = 0644,
   .proc_handler = &proc_doutsstring,
   .strategy = &sysctl_string,
@@ -269,8 +269,8 @@ static ctl_table kern_table[] = {
  {
   .ctl_name = KERN_DOMAINNAME,
   .procname = "domainname",
-  .data  = system_utsname.domainname,
-  .maxlen  = sizeof(system_utsname.domainname),
+  .data  = init_uts_ns.name.domainname,
+  .maxlen  = sizeof(init_uts_ns.name.domainname),
   .mode  = 0644,
   .proc_handler = &proc_doutsstring,
   .strategy = &sysctl_string,
@@ -1619,6 +1619,24 @@ static int proc_doutsstring(ctl_table *t
 {
  int r;

+ switch (table->ctl_name) {
+  case KERN_OSTYPE:
+   table->data = utsname()->sysname;
+   break;
+  case KERN_OSRELEASE:
+   table->data = utsname()->release;
+   break;
+  case KERN_VERSION:
+   table->data = utsname()->version;
+   break;
+  case KERN_NODENAME:
+   table->data = utsname()->nodename;
+   break;
+  case KERN_DOMAINNAME:
+   table->data = utsname()->domainname;
+   break;
+ }
```

```
+
  if (!write) {
   down_read(&uts_sem);
   r=proc_dostring(table,0,filp,buffer,lenp, ppos);
--
1.2.4
```