Subject: [PATCH 3/17] [IPV4]: Consolidate masq_inet_event and masq_device_event.
Posted by den on Wed, 06 Feb 2008 10:53:23 GMT
View Forum Message <> Reply to Message

They do exactly the same job.

Signed-off-by: Denis V. Lunev <den@openvz.org>
---
net/ipv4/netfilter/ipt_MASQUERADE.c | 14 ++----------
1 files changed, 2 insertions(+), 12 deletions(-)

```
diff --git a/net/ipv4/netfilter/ipt_MASQUERADE.c b/net/ipv4/netfilter/ipt_MASQUERADE.c
index d80fee8..313b3fc 100644
--- a/net/ipv4/netfilter/ipt_MASQUERADE.c
+++ b/net/ipv4/netfilter/ipt_MASQUERADE.c
@@ -139,18 +139,8 @@ static int masq_inet_event(struct notifier_block *this,
       unsigned long event,
       void *ptr)
 {
- const struct net_device *dev = ((struct in_ifaddr *)ptr)->ifa_dev->dev;
-
- if (event == NETDEV_DOWN) {
-  /* IP address was deleted.  Search entire table for
-     conntracks which were associated with that device,
-     and forget them. */
-  NF_CT_ASSERT(dev->ifindex != 0);
-
-  nf_ct_iterate_cleanup(device_cmp, (void *)(long)dev->ifindex);
- }
-
- return NOTIFY_DONE;
+ struct net_device *dev = ((struct in_ifaddr *)ptr)->ifa_dev->dev;
+ return masq_device_event(this, event, dev);
 }

 static struct notifier_block masq_dev_notifier = {
--
1.5.3.rc5
```