Subject: [patch 3/3] add the clone64() and unshare64() syscalls
Posted by Cedric Le Goater on Thu, 07 Feb 2008 10:31:38 GMT
View Forum Message <> Reply to Message

From: Cedric Le Goater <clg@fr.ibm.com>

This patch adds 2 new syscalls :

long sys_clone64(unsigned long flags_high, unsigned long flags_low,
unsigned long newsp);

long sys_unshare64(unsigned long flags_high, unsigned long flags_low);

clone64() does not support CLONE_PARENT_SETTID and CLONE_CHILD_CLEARTID
because we would exceed the 6 registers limit of some arches.

This is work in progress but already includes support for x86, x86_64,
x86_64(32), ppc64, ppc64(32), s390x, s390x(31).

ia64 already supports 64bits clone flags through the clone2() syscall.
should we harmonize the name to clone2 ?

Signed-off-by: Cedric Le Goater <clg@fr.ibm.com>

---
arch/powerpc/kernel/entry_32.S | 8 ++++++++
arch/powerpc/kernel/entry_64.S | 5 +++++
arch/powerpc/kernel/process.c | 15 +++++++++++++++
arch/s390/kernel/compat_linux.c | 15 +++++++++++++++
arch/s390/kernel/compat_wrapper.S | 6 ++++++
arch/s390/kernel/process.c | 15 +++++++++++++++
arch/s390/kernel/syscalls.S | 2 ++
arch/x86/ia32/ia32entry.S | 4 ++++
arch/x86/ia32/sys_ia32.c | 12 ++++++++++++
arch/x86/kernel/entry_64.S | 1 +
arch/x86/kernel/process_32.c | 14 ++++++++++++++
arch/x86/kernel/process_64.c | 15 +++++++++++++++
arch/x86/kernel/syscall_table_32.S | 2 ++
include/asm-powerpc/systbl.h | 2 ++
include/asm-powerpc/unistd.h | 4 +++-
include/asm-s390/unistd.h | 4 +++-
include/asm-x86/unistd_32.h | 2 ++
include/asm-x86/unistd_64.h | 4 ++++
include/linux/syscalls.h | 2 ++
kernel/fork.c | 7 +++++++
kernel/sys_ni.c | 3 +++
21 files changed, 140 insertions(+), 2 deletions(-)

```
Index: 2.6.24-mm1/arch/s390/kernel/syscalls.S
===================================================================
--- 2.6.24-mm1.orig/arch/s390/kernel/syscalls.S
+++ 2.6.24-mm1/arch/s390/kernel/syscalls.S
@@ -327,3 +327,5 @@ SYSCALL(sys_utimensat,sys_utimensat,comp
 SYSCALL(sys_signalfd,sys_signalfd,compat_sys_signalfd_wrapper)
 NI_SYSCALL      /* 317 old sys_timer_fd */
 SYSCALL(sys_eventfd,sys_eventfd,sys_eventfd_wrapper)
+SYSCALL(sys_clone64,sys_clone64,sys32_clone64)
+SYSCALL(sys_unshare64,sys_unshare64,sys_unshare64_wrapper)
Index: 2.6.24-mm1/arch/x86/kernel/syscall_table_32.S
===================================================================
--- 2.6.24-mm1.orig/arch/x86/kernel/syscall_table_32.S
+++ 2.6.24-mm1/arch/x86/kernel/syscall_table_32.S
@@ -326,3 +326,5 @@ ENTRY(sys_call_table)
  .long sys_fallocate
  .long sys_timerfd_settime /* 325 */
  .long sys_timerfd_gettime
+ .long sys_clone64
+ .long sys_unshare64
Index: 2.6.24-mm1/include/asm-powerpc/systbl.h
===================================================================
--- 2.6.24-mm1.orig/include/asm-powerpc/systbl.h
+++ 2.6.24-mm1/include/asm-powerpc/systbl.h
@@ -314,3 +314,5 @@ SYSCALL_SPU(eventfd)
 COMPAT_SYS_SPU(sync_file_range2)
 COMPAT_SYS(fallocate)
 SYSCALL(subpage_prot)
+PPC_SYS(clone64)
+SYSCALL_SPU(unshare64)
Index: 2.6.24-mm1/include/asm-powerpc/unistd.h
===================================================================
--- 2.6.24-mm1.orig/include/asm-powerpc/unistd.h
+++ 2.6.24-mm1/include/asm-powerpc/unistd.h
@@ -333,10 +333,12 @@
 #define __NR_sync_file_range2 308
 #define __NR_fallocate  309
 #define __NR_subpage_prot 310
+#define __NR_clone64  311
+#define __NR_unshare64  312

 #ifdef __KERNEL__

-#define __NR_syscalls  311
+#define __NR_syscalls  313

 #define __NR__exit __NR_exit
 #define NR_syscalls __NR_syscalls
```

```
Index: 2.6.24-mm1/include/asm-s390/unistd.h
===================================================================
--- 2.6.24-mm1.orig/include/asm-s390/unistd.h
+++ 2.6.24-mm1/include/asm-s390/unistd.h
@@ -256,7 +256,9 @@
 #define __NR_signalfd  316
 #define __NR_timerfd  317
 #define __NR_eventfd  318
-#define NR_syscalls 319
+#define __NR_clone64  319
+#define __NR_unshare64  320
+#define NR_syscalls 321

 /*
  * There are some system calls that are not present on 64 bit, some
Index: 2.6.24-mm1/include/asm-x86/unistd_32.h
===================================================================
--- 2.6.24-mm1.orig/include/asm-x86/unistd_32.h
+++ 2.6.24-mm1/include/asm-x86/unistd_32.h
@@ -332,6 +332,8 @@
 #define __NR_fallocate  324
 #define __NR_timerfd_settime 325
 #define __NR_timerfd_gettime 326
+#define __NR_clone64  327
+#define __NR_unshare64  328

 #ifdef __KERNEL__

Index: 2.6.24-mm1/include/asm-x86/unistd_64.h
===================================================================
--- 2.6.24-mm1.orig/include/asm-x86/unistd_64.h
+++ 2.6.24-mm1/include/asm-x86/unistd_64.h
@@ -639,6 +639,10 @@ __SYSCALL(__NR_fallocate, sys_fallocate)
 __SYSCALL(__NR_timerfd_settime, sys_timerfd_settime)
 #define __NR_timerfd_gettime   287
 __SYSCALL(__NR_timerfd_gettime, sys_timerfd_gettime)
+#define __NR_clone64  288
+__SYSCALL(__NR_clone64, stub_clone64)
+#define __NR_unshare64  289
+__SYSCALL(__NR_unshare64, sys_unshare64)


 #ifndef __NO_STUBS
Index: 2.6.24-mm1/include/linux/syscalls.h
===================================================================
--- 2.6.24-mm1.orig/include/linux/syscalls.h
+++ 2.6.24-mm1/include/linux/syscalls.h
@@ -615,6 +615,8 @@ asmlinkage long sys_timerfd_gettime(int
```

```
 asmlinkage long sys_eventfd(unsigned int count);
 asmlinkage long sys_fallocate(int fd, int mode, loff_t offset, loff_t len);

+asmlinkage long sys_unshare64(unsigned long clone_flags_high, unsigned long
clone_flags_low);
+
 int kernel_execve(const char *filename, char *const argv[], char *const envp[]);

 #endif
Index: 2.6.24-mm1/kernel/sys_ni.c
===================================================================
--- 2.6.24-mm1.orig/kernel/sys_ni.c
+++ 2.6.24-mm1/kernel/sys_ni.c
@@ -161,3 +161,6 @@ cond_syscall(sys_timerfd_gettime);
 cond_syscall(compat_sys_timerfd_settime);
 cond_syscall(compat_sys_timerfd_gettime);
 cond_syscall(sys_eventfd);
+
+cond_syscall(sys_clone64);
+cond_syscall(sys_unshare64);
Index: 2.6.24-mm1/arch/x86/kernel/process_32.c
===================================================================
--- 2.6.24-mm1.orig/arch/x86/kernel/process_32.c
+++ 2.6.24-mm1/arch/x86/kernel/process_32.c
@@ -768,6 +768,20 @@ asmlinkage int sys_clone(struct pt_regs
  return do_fork(clone_flags, newsp, &regs, 0, parent_tidptr, child_tidptr);
 }

+asmlinkage int sys_clone64(struct pt_regs regs)
+{
+ u64 clone_flags;
+ unsigned long newsp;
+
+ clone_flags = ((u64) regs.bx << 32 | regs.cx);
+ clone_flags &= ~(CLONE_PARENT_SETTID|CLONE_CHILD_CLEARTID);
+
+ newsp = regs.dx;
+ if (!newsp)
+  newsp = regs.sp;
+ return do_fork(clone_flags, newsp, &regs, 0, NULL, NULL);
+}
+
 /*
  * This is trivial, and on the face of it looks like it
  * could equally well be done in user mode.
Index: 2.6.24-mm1/arch/x86/kernel/process_64.c
===================================================================
--- 2.6.24-mm1.orig/arch/x86/kernel/process_64.c
```

```
+++ 2.6.24-mm1/arch/x86/kernel/process_64.c
@@ -772,6 +772,21 @@ sys_clone(unsigned long clone_flags, uns
  return do_fork(clone_flags, newsp, regs, 0, parent_tid, child_tid);
 }

+asmlinkage long
+sys_clone64(unsigned long clone_flags_high, unsigned long clone_flags_low,
+    unsigned long newsp, struct pt_regs *regs)
+{
+ u64 clone_flags;
+
+ clone_flags = ((u64) clone_flags_high << 32 | clone_flags_low);
+ clone_flags &= ~(CLONE_PARENT_SETTID|CLONE_CHILD_CLEARTID);
+
+ if (!newsp)
+  newsp = regs->sp;
+ return do_fork(clone_flags, newsp, regs, 0, NULL, NULL);
+}
+
+
 /*
  * This is trivial, and on the face of it looks like it
  * could equally well be done in user mode.
Index: 2.6.24-mm1/arch/s390/kernel/compat_linux.c
===================================================================
--- 2.6.24-mm1.orig/arch/s390/kernel/compat_linux.c
+++ 2.6.24-mm1/arch/s390/kernel/compat_linux.c
@@ -940,6 +940,21 @@ asmlinkage long sys32_clone(void)
         parent_tidptr, child_tidptr);
 }

+asmlinkage long sys32_clone64(void)
+{
+ struct pt_regs *regs = task_pt_regs(current);
+ u64 clone_flags;
+ unsigned long newsp;
+
+ clone_flags = ((u64) (regs->orig_gpr2  & 0xffffffffUL) << 32 |  (regs->gprs[3]  & 0xffffffffUL));
+ clone_flags &= ~(CLONE_PARENT_SETTID|CLONE_CHILD_CLEARTID);
+
+ newsp = regs->gprs[4] & 0x7fffffffUL;
+ if (!newsp)
+  newsp = regs->gprs[15];
+ return do_fork(clone_flags, newsp, regs, 0, NULL, NULL);
+}
+
 /*
  * 31 bit emulation wrapper functions for sys_fadvise64/fadvise64_64.
```

```
  * These need to rewrite the advise values for POSIX_FADV_{DONTNEED,NOREUSE}
Index: 2.6.24-mm1/arch/s390/kernel/process.c
===================================================================
--- 2.6.24-mm1.orig/arch/s390/kernel/process.c
+++ 2.6.24-mm1/arch/s390/kernel/process.c
@@ -323,6 +323,21 @@ asmlinkage long sys_clone(void)
         parent_tidptr, child_tidptr);
 }

+asmlinkage long sys_clone64(void)
+{
+ struct pt_regs *regs = task_pt_regs(current);
+ u64 clone_flags;
+ unsigned long newsp;
+
+ clone_flags = ((u64) regs->orig_gpr2 << 32 |  regs->gprs[3]);
+ clone_flags &= ~(CLONE_PARENT_SETTID|CLONE_CHILD_CLEARTID);
+
+ newsp = regs->gprs[4];
+ if (!newsp)
+  newsp = regs->gprs[15];
+ return do_fork(clone_flags, newsp, regs, 0, NULL, NULL);
+}
+
 /*
  * This is trivial, and on the face of it looks like it
  * could equally well be done in user mode.
Index: 2.6.24-mm1/arch/powerpc/kernel/process.c
===================================================================
--- 2.6.24-mm1.orig/arch/powerpc/kernel/process.c
+++ 2.6.24-mm1/arch/powerpc/kernel/process.c
@@ -829,6 +829,21 @@ int sys_clone(unsigned long clone_flags,
   return do_fork(clone_flags, usp, regs, 0, parent_tidp, child_tidp);
 }

+int sys_clone64(unsigned long clone_flags_high, unsigned long clone_flags_low,
+  unsigned long usp, unsigned long p4, unsigned long p5,
+  unsigned long p6, struct pt_regs *regs)
+{
+ u64 clone_flags;
+
+ clone_flags = ((u64) clone_flags_high << 32 | clone_flags_low);
+ clone_flags &= ~(CLONE_PARENT_SETTID|CLONE_CHILD_CLEARTID);
+
+ CHECK_FULL_REGS(regs);
+ if (usp == 0)
+  usp = regs->gpr[1]; /* stack pointer for child */
+  return do_fork(clone_flags, usp, regs, 0, NULL, NULL);
```

```
+}
+
 int sys_fork(unsigned long p1, unsigned long p2, unsigned long p3,
       unsigned long p4, unsigned long p5, unsigned long p6,
       struct pt_regs *regs)
Index: 2.6.24-mm1/arch/x86/kernel/entry_64.S
===================================================================
--- 2.6.24-mm1.orig/arch/x86/kernel/entry_64.S
+++ 2.6.24-mm1/arch/x86/kernel/entry_64.S
@@ -425,6 +425,7 @@ END(\label)
  PTREGSCALL stub_rt_sigsuspend, sys_rt_sigsuspend, %rdx
  PTREGSCALL stub_sigaltstack, sys_sigaltstack, %rdx
  PTREGSCALL stub_iopl, sys_iopl, %rsi
+ PTREGSCALL stub_clone64, sys_clone64, %rcx

 ENTRY(ptregscall_common)
  popq %r11
Index: 2.6.24-mm1/arch/powerpc/kernel/entry_32.S
===================================================================
--- 2.6.24-mm1.orig/arch/powerpc/kernel/entry_32.S
+++ 2.6.24-mm1/arch/powerpc/kernel/entry_32.S
@@ -452,6 +452,14 @@ ppc_clone:
  stw r0,_TRAP(r1)  /* register set saved */
  b sys_clone

+ .globl ppc_clone64
+ppc_clone64:
+ SAVE_NVGPRS(r1)
+ lwz r0,_TRAP(r1)
+ rlwinm r0,r0,0,0,30  /* clear LSB to indicate full */
+ stw r0,_TRAP(r1)  /* register set saved */
+ b sys_clone64
+
  .globl ppc_swapcontext
 ppc_swapcontext:
  SAVE_NVGPRS(r1)
Index: 2.6.24-mm1/arch/powerpc/kernel/entry_64.S
===================================================================
--- 2.6.24-mm1.orig/arch/powerpc/kernel/entry_64.S
+++ 2.6.24-mm1/arch/powerpc/kernel/entry_64.S
@@ -298,6 +298,11 @@ _GLOBAL(ppc_clone)
  bl .sys_clone
  b syscall_exit

+_GLOBAL(ppc_clone64)
+ bl .save_nvgprs
+ bl .sys_clone64
+ b syscall_exit
```

```
+
 _GLOBAL(ppc32_swapcontext)
  bl .save_nvgprs
  bl .compat_sys_swapcontext
Index: 2.6.24-mm1/arch/s390/kernel/compat_wrapper.S
===================================================================
--- 2.6.24-mm1.orig/arch/s390/kernel/compat_wrapper.S
+++ 2.6.24-mm1/arch/s390/kernel/compat_wrapper.S
@@ -1712,3 +1712,9 @@ sys_fallocate_wrapper:
  sllg %r5,%r6,32  # get high word of 64bit loff_t
  l %r5,164(%r15)  # get low word of 64bit loff_t
  jg sys_fallocate
+
+ .globl sys_unshare64_wrapper
+sys_unshare64_wrapper:
+ llgfr %r2,%r2   # unsigned long
+ llgfr %r3,%r3   # unsigned long
+ jg sys_unshare64
Index: 2.6.24-mm1/kernel/fork.c
===================================================================
--- 2.6.24-mm1.orig/kernel/fork.c
+++ 2.6.24-mm1/kernel/fork.c
@@ -1793,3 +1793,10 @@ asmlinkage long sys_unshare(unsigned lon
 {
  return do_unshare(unshare_flags);
 }
+
+asmlinkage long sys_unshare64(unsigned long flags_high, unsigned long flags_low)
+{
+ u64 unshare_flags = ((u64) flags_high << 32 | flags_low);
+
+ return do_unshare(unshare_flags);
+}
Index: 2.6.24-mm1/arch/x86/ia32/sys_ia32.c
===================================================================
--- 2.6.24-mm1.orig/arch/x86/ia32/sys_ia32.c
+++ 2.6.24-mm1/arch/x86/ia32/sys_ia32.c
@@ -824,6 +824,18 @@ asmlinkage long sys32_clone(unsigned int
  return do_fork(clone_flags, newsp, regs, 0, parent_tid, child_tid);
 }

+asmlinkage long sys32_clone64(unsigned int flags_high, unsigned int flags_low,
+         unsigned int newsp, struct pt_regs *regs)
+{
+ u64 clone_flags = ((u64) flags_high << 32 | flags_low);
+
+ clone_flags &= ~(CLONE_PARENT_SETTID|CLONE_CHILD_CLEARTID);
+
```

```
+ if (!newsp)
+  newsp = regs->sp;
+ return do_fork(clone_flags, newsp, regs, 0, NULL, NULL);
+}
+
 /*
  * Some system calls that need sign extended arguments. This could be
  * done by a generic wrapper.
Index: 2.6.24-mm1/arch/x86/ia32/ia32entry.S
===================================================================
--- 2.6.24-mm1.orig/arch/x86/ia32/ia32entry.S
+++ 2.6.24-mm1/arch/x86/ia32/ia32entry.S
@@ -373,6 +373,7 @@ quiet_ni_syscall:
  PTREGSCALL stub32_vfork, sys_vfork, %rdi
  PTREGSCALL stub32_iopl, sys_iopl, %rsi
  PTREGSCALL stub32_rt_sigsuspend, sys_rt_sigsuspend, %rdx
+ PTREGSCALL stub32_clone64, sys32_clone64, %rcx

 ENTRY(ia32_ptregs_common)
  popq %r11
@@ -727,4 +728,7 @@ ia32_sys_call_table:
  .quad sys32_fallocate
  .quad compat_sys_timerfd_settime /* 325 */
  .quad compat_sys_timerfd_gettime
+ .quad stub32_clone64
+ .quad sys_unshare64
+
 ia32_syscall_end:

--
_____________________________________________
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers
```