Subject: [PATCH 1/7][v2]: Propagate error code from devpts_pty_new
Posted by Sukadev Bhattiprolu on Thu, 03 Apr 2008 07:07:17 GMT
View Forum Message <> Reply to Message

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH 1/7][v2]: Propagate error code from devpts_pty_new

Have ptmx_open() propagate any error code returned by devpts_pty_new().

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: containers@lists.osdl.org
---
 drivers/char/tty_io.c | 4 ++--
 1 file changed, 2 insertions(+), 2 deletions(-)

Index: 2.6.25-rc5-mm1/drivers/char/tty_io.c
===
--- 2.6.25-rc5-mm1.orig/drivers/char/tty_io.c 2008-03-21 20:13:38.000000000 -0700
+++ 2.6.25-rc5-mm1/drivers/char/tty_io.c 2008-03-24 20:04:07.000000000 -0700
@@ -2835,8 +2835,8 @@ static int ptmx_open(struct inode *inode
  filp->private_data = tty;
  file_move(filp, &tty->tty_files);

- retval = -ENOMEM;
- if (devpts_pty_new(tty->link))
+ retval = devpts_pty_new(tty->link);
+ if (retval)
   goto out1;

  check_tty_count(tty, "tty_open");

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers